



AHT1U

LOW VOLTAGE ASYNCHRONOUS HTU-C LINE CARD

PRODUCT FEATURES

- RS-232 maintenance port
- 784 kbps dual duplex 2B1Q HDSL transmission over two wire pairs
- Front panel status LEDs conforming to the appearance and function of typical Litespan line cards
- Performance monitoring and alarm reporting
- Low power consumption
- -135 volt span powering capability of the Low Voltage HDSL Range Extender (HRE) and HDSL Transceiver Unit, Remote (HTU-R)
- Troubleshooting functionality
- Licensed by the DSC Corporation
- Supports DSC Litespan software release 7.1.3 or later
- Can be used in Litespan 2000, Litespan 2012, and Litespan ONU channel banks

The ADTRAN Low Voltage Asynchronous Litespan HDSL Transceiver Unit for the central office (HTU-C) is a DS1 interface unit that provides T1 service over four-wire interface facilities. The Low Voltage Litespan HTU-C combine ADTRAN HDSL technology and DSC Litespan technology to provide an HDSL interface to a Litespan system.

ADTRAN's Low Voltage Litespan HTU-C is Licensed by DSC to safely operate in Litespan 2000 and Starspan systems. The unit is licensed under the Asynchronous High bit-rate Digital Subscriber Line T1 Interface Unit (AHT1U) channel unit type.

The Low Voltage Litespan HTU-C can be used in Litespan 2000, Litespan 2012, and Litespan ONU channel bank assembly systems containing Litespan system software versions of 7.1.3 or higher.

The ADTRAN provides the HTU-C products for narrowband and wideband connections. The Litespan HTU-C is compatible with all ADTRAN HDSL transceivers for remote sites (HTU-R) and the HDSL Range Extension (HRE).



CORPORATE OFFICE

901 Explorer Boulevard
Huntsville, AL 35806

800 9ADTRAN
Local: 256 963-8000
Fax: 256 963-8699
Fax Back: 256 963-8200
http://www.adtran.com
email: info@adtran.com

TELCO TECHNICAL SUPPORT

800 726-8663

REGIONAL OFFICES

Irvine, CA
800 788-5408

Denver, CO
800 471-8651

Atlanta, GA
800 332-6945

Kansas City, KS
800 471-8649

Philadelphia, PA
800 471-8656

Dallas, TX
800 471-8648

Canada
800 232-6811



ADTRAN is an ISO 9001 registered company.



Printed in U.S.A. on recycled paper
61245.002L6-8A May 1998
©ADTRAN, Inc. 1998

Product Specifications

LOOP INTERFACE

- *Modulation Type:* 2B1Q
- *Mode:* Full duplex, echo cancelling
- *Number of pairs:* Two
- *Bit Rate:* 784 kbps per pair
- *Baud Rate:* 392 kbps per pair
- *Service Range:* Defined by CSA guidelines
- *Loop Loss:* 36 dB maximum @ 200kHz
- *Bridged Taps:* Single Taps <2 kft, total taps ≤ 2.5 kft
- *Performance:* Compliant with Bellcore TA-NWT-001210
- *HDSL Tx Signal Level:* 13.5 dBm
- *Imput Impedance:* 135Ω
- *Return Loss:* 20 dB (40 kHz to 200 kHz)

DIAGNOSTICS

- Local loopback (HTU-C)
- Remote loopback (HTU-R)
- Troubleshooting screen

MOUNTING

- Litespan 2000 DBA, Litespan 2012 CBA, or an ONU CBA

ENVIRONMENT

- *Operating (standard):* -40° to 70°C
- *Storage Temperature:* -40° to 85°C

PHYSICAL

- *Dimensions:* 4.42" H, 0.84" W, 10.4" D
- *Weight:* Less than one pound
- *Humidity:* Up to 95% non-condensing

POWER

- *Max Power Dissipation HTU-C and HTU-R:* < 4 watts
- *Span Power:* -135 VDC internally generated from the -48 VDC

Ordering Information

EQUIPMENT

PART

AHT1U HTU-C for DSC Litespan

AHT1U Narrowband

Wideband Wiring.....1245002L6

Call for individual module information.

Specifications subject to change without notice.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>