



SCM100ASL PRO : 3 - w a y a c t i v e

- Features
- 25mm soft dome tweeter.
 - Full "SL" spec 12"/314mm bass driver.
 - ATC 75mm "Super Dome" mid driver.
 - On board ATC grounded plane 350W Tri-amplifier.
 - LF contour control.
 - Clip indication.
 - 6 year warranty.

Specifications

Drivers : HF 25mm, Mid 75mm, LF 314mm **Amplitude Linearity (± 2 dB) :** 65Hz-17kHz **Cut-off Frequencies (-6dB, free-standing) :** 32Hz, 22kHz
Horizontal Dispersion : $\pm 80^\circ$, Coherent **Vertical Dispersion :** $\pm 10^\circ$, Coherent **Max. Continuous SPL (1 metre) :** 115dB **Crossover Frequencies :** 380Hz, 3.5kHz
Input Connectors : Male XLR **Input Sensitivity :** 1V **Input Sensitivity Trim :** ± 6 dB **Input Impedance :** Balanced > 10k Ω
Amplifier Output : Bass 200W, Mid 100W, High 50W **Filters :** Even Order Critically Damped
Overload Protection : Active FET momentary gain reduction plus thermal tweeter protection **Front Panel Indicators :** Power On indicator, Gain Reduction warning
LF EQ : +6dB @ 40Hz **Dimensions (HxWxD) :** 832 x 398 x 581mm (32.8" x 15.7" x 22.9") Depth with amplifier at rear adds 3" **Weight :** 65kg / 143lbs

Passive versions available. ATC reserves the right to vary products and specifications without prior notice.



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>