



## SCM50ASL PRO : 3 - w a y   a c t i v e

- Features
- 25mm soft dome tweeter.
  - Full "SL" spec 9"/234mm bass driver.
  - ATC 75mm "Super Dome" mid driver.
  - On board ATC grounded plane 350W Tri-amplifier.
  - LF contour control.
  - Clip indication.
  - 6 year warranty.

## Specifications

**Drivers :** HF 25mm, Mid 75mm, LF 234mm    **Amplitude Linearity ( $\pm 2\text{dB}$ ) :** 70Hz-17kHz    **Cut-off Frequencies ( $-6\text{dB}$ , free-standing) :** 38Hz, 22kHz  
**Horizontal Dispersion :**  $\pm 80^\circ$ , Coherent    **Vertical Dispersion :**  $\pm 10^\circ$ , Coherent    **Max. Continuous SPL (1 metre) :** 112dB    **Crossover Frequencies :** 380Hz, 3.5kHz  
**Input Connectors :** Male XLR    **Input Sensitivity :** 1V    **Input Sensitivity Trim :**  $\pm 6\text{dB}$     **Input Impedance :** Balanced  $> 10\text{k}\Omega$   
**Amplifier Output :** Bass 200W, Mid 100W, High 50W    **Filters :** Even Order Critically Damped  
**Overload Protection :** Active FET momentary gain reduction plus thermal tweeter protection    **Front Panel Indicators :** Power On indicator, Gain Reduction warning  
**LF EQ :**  $+6\text{dB}$  @ 40Hz    **Dimensions (HxWxD) :** 716 x 351 x 400mm (28.2" x 13.8" x 15.8") Depth with amplifier at rear adds 3"    **Weight :** 49kg / 107.8lbs

Passive versions available. ATC reserves the right to vary products and specifications without prior notice.



## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>