

# SwitchView SC

## Enhanced Secure KVM Switching

### FEATURES AND BENEFITS

- **Agency Approval.** Evaluated to NIAP Common Criteria EAL 4 security requirements.
- **Controlled KVM Switching.** Separate I/O processors for control KVM switching and access to computers.
- **Cable Management.** Avocent's locking cables provide secure connections and reduce cable volume.
- **Custom-Designed Firmware.** Custom-designed encrypted internal firmware made in the U.S.
- **Standard PS/2 Protocol.** Standard PS/2 protocol is maintained to avoid the possibility of any external device detecting the presence of the SwitchView SC.
- **Clears Buffer.** Automatically clears the keyboard buffer immediately after data is transmitted through the switch, so no data is ever left in the switch.
- **Reliable Performance.** 8-port model uses an internal power supply for optimal processing performance.
- **Space Saving.** Compact 4-port model saves space on the desktop and 8-port model doubles as monitor stand for zero footprint on the desktop.

Switch between multiple computers without compromising network security.

With SwitchView SC, you can safely switch between as many as eight classified and unclassified computers, all from one keyboard, monitor and mouse. The SwitchView SC design makes it impossible to transfer data between the connected computers --- an important factor for a user who may access secure and non-secure networks from one point of contact. The Cybex SwitchView SC from Avocent is the only KVM switch evaluated to NIAP Common Criteria EAL 4 security requirements.

Available in 4-port and 8-port models, the SwitchView SC puts secure access and control at your fingertips. Plus, the 8-port model doubles as a monitor stand, leaving zero footprint on the desktop.

When combined with Avocent's LongView extension technology, critical computers and other related assets can be located in secure (locked) areas, providing controlled access with the SwitchView SC.



*SwitchView provides secure access and control to classified and unclassified computers, all from one switch.*

# SWITCHVIEW SC SPECIFICATIONS

## MECHANICAL

### 10040-SC (4-port)

- **Height** - 1.9" (4.83 cm)
- **Depth** - 11" (27.94 cm)
- **Width** - 8.1" (20.6 cm)
- **Weight** - 0.9 lbs. (0.4 kg)
- **Style** - Desktop

### 10080SC-AM (8-port)

- **Height** - 1.7" (4.5 cm)
- **Depth** - 8.5" (21.6 cm)
- **Width** - 17.2" (43.7 cm)
- **Weight** - 6.3 lbs. (2.9 kg)
- **Style** - Desktop or rack mount

## ENVIRONMENTAL / POWER / HARDWARE

### 10040-SC (4-port)

- **Operating Temperature** - 41° (5°C) to 104° (40°C)
- **Storage** - -4° (-20°C) to 122° (50°C)
- **Power** - 6 VDC @ 700 mA (optional)
- **Computer** - IBM PC/AT, PS/2 and 100% compatible
- **Video Modes** - VGA and SVGA, maximum resolution 1600x1200 @ 75 Hz
- **Peripherals** - PS/2 keyboard, PS/2 mouse, Microsoft IntelliMouse (PS/2 only)

### 10080SC-AM (8-port)

- **Operating Temperature** - 41° (5°C) to 104° (40°C)
- **Storage** - -4° (-20°C) to 122° (50°C)
- **Power** - Input Power: 8.0 W; Operating Voltage: 100 - 230 VAC; Power Frequency: 50 - 60 Hz
- **Computer** - IBM PC/AT, PS/2 and 100% compatible
- **Video Modes** - VGA, SVGA, (XGA, XGA-II with adaptor), maximum resolution 1280x1024 @ 60 Hz
- **Peripherals** - PS/2 keyboard, PS/2 mouse, Microsoft IntelliMouse (PS/2 only)

## STANDARDS

### • Approved Agency

#### 10040-SC (4-port)

UL 1950, CSA C22.2 No. 950, EN60950  
FCC part 15B, EN55022, EN50082

#### 10080SC-AM (8-port)

UL, cUL, FCC, IC and CE

### • NSA Requirements

NIAP Comm Criteria Tested to EAL 4

## ORDERING DETAILS

10040-SC Single user, 4-port

10080SC-AM Single user, 8-port

### • Cable Assemblies

#### 10040-SC (4-port)

CPS2-6A - 6 feet color-coded VGA, PS/2 keyboard and mouse

#### 10080SC-AM (8-port)

CIFCA-4 - 4 feet single sheath VGA, PS/2 keyboard and mouse

CIFCA-8 - 8 feet single sheath VGA, PS/2 keyboard and mouse

CIFCA-15 - 15 feet single sheath VGA, PS/2 keyboard and mouse

CIFCA-30 - 30 feet single sheath VGA, PS/2 keyboard and mouse


RMK-39 - 19 inch rack mount kit

## WARRANTY

- Two Year

## GSA NUMBER

- GS-35F0264K



SwitchView SC security features let you switch safely between secured and non-secured networks



4991 Corporate Drive, Huntsville, AL 35805  
TEL 866 286-2368 FAX 256 430-4030  
www.avocent.com

Avocent, the Avocent logo, The Power of Being There and SwitchView are trademarks of Avocent Corporation. All other marks are the property of their respective owners. Copyright © 2003, Avocent Corporation.

0403-SVSC-TP-02

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>