

ACA-ATR13 - RFID Tag

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Robust and reliable
- ▶ Water-resistant

The ACA-ATR13 proximity read-only tag offers universal compability with the Wiegand IF reader type W 3. The tag includes an embedded antenna, and an RFID integrated circuit enabling infinite numbers of reads by Wiegand type W3 readers.

The key-ring sized credential tag is durable with IP 68 and can be fully submerged, all the electronics is sealed inside.

Technical Specifications

| | |
|-----------------------|---------------------------------------|
| Type | Contactless passive |
| Materials | PVC / PET |
| IC Chip | EM4102 |
| ISO Standard | ISO/IEC 10536 |
| Environment class | IP 68 |
| Operating frequency | 125 kHz |
| Operating temperature | -20 °C to +50 °C (-4 °F to 122 °F) |
| Storage temperature | -20 °C to +50 °C (-4 °F to 122 °F) |
| Humidity | Up to 90% (non-condensing) |

| | |
|----------------|-----------------------------------------------|
| Surface finish | Matt |
| Antenna | Copper coil |
| Dimensions | 54,5 x 35 x 7,3 mm (2.14" x 1.37" x 0.28") |
| Weight | 9,6 g (0.331 oz) |

Ordering Information

ACA-ATR13 - RFID Tag

125 kHz proximity read-only tag for Wiegand readers type W 3. Packing information: 25 tags/ each unit
Order number **ACA-ATR13**

Represented by:

© Bosch Security Systems 2012 | Data subject to change without notice
1371220619 | en, V1, 13. Apr 2012

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>