

Bush Hog® TOUGH

2715L Flex Wing Rotary Cutters

Recommended Tractor HP Minimum 60 PTO

BUSH HOG® TOUGH FEATURES

TOUGH EZ Clean Deck 11 Gauge Top & 10 Gauge Bottom

TOUGH 7 Gauge Strongbacks

TOUGH 1/4 Inch Sidebands

TOUGH Independent Spring Cushion At Each Axle Arm

TOUGH Heavy Duty Axle Turn Buckles

TOUGH Greaseable Axle Pivot Points

TOUGH Heavy Duty Wheel Hubs And Axle Spindles

TOUGH Driveline Safety Retaining Rings

TOUGH 6 Year Gearbox Limited Warranty

TOUGH Powder Coat Paint



MODEL	2715L
Cutting Width	15 ft
Cutting Capacity	3 1/2 inch diameter
Cutting Height	2 to 14 inches
Overall Width x Length (from Clevis to Wheel Hub at Transport Height)	15 ft 6 inches x 14 ft 6 inches
Transport Width (outside wing skid to outside wing skid)	8 ft 2 inches
Tractor PTO	540/1000 RPM
Minimum Tractor HP	60 PTO
Deck Thickness	Top Deck - 11 gauge, Bottom Deck - 10 gauge
Side Bands	1/4 x 12 1/2 inch
Gearbox HP	235 - Transfer, 205 - Center, 205 - Wings
PTO Drivelines	Input: Constant Velocity or Cardan/jackshaft - Cat. 5 at 540 RPM Cat. 4 or 5 (1000 RPM)
Wing Drivelines	ASAE Cat. 4
Slip Clutches	(3) Slip clutches, 2 - Friction Plates Each
Blade Tip Speed	16,000 FPM /540 RPM; 15,912 FPM /1000 RPM
Blades	1/2 x 4 inch uplift with 6 inch overlap
Type Hitch	Self-Leveling with Perma-Level® Hitch, or available with 2 inch Ball Hitch or Swivel Clevis Hitch
Wing Flex	87° up to 22° down
Tires	Laminated Tire, Used Aircraft Tire, Foam Filled Used Aircraft Tire, Pneumatic 15 inch Wheel (tire not included), 15 inch x 6 inch wheel for 9.5L x 15 inch tire, modified laminated tire with 10 bolts
Axles	Choice of Dual or Walking Tandem on Center Section, Choice of Single or Dual Wing Axles
Wheel Shock Protection	Independent springs on each axle
Deflectors	Standard Front Belting, Optional front and rear chains
Options	Chain Shielding, Valve & Stand Kit, Deck Rings
Warranty	1 year limited warranty with a 6 year gearbox limited warranty

FEATURES

• EZ clean double deck • Perma Level Hitch • Grass baffles • Cylinder style anti wrap device around lower gearbox housing • High blade tip speeds • Deep sidebands • Heavy duty wheel hubs • Quick detach gearbox shields • Greaseable Bushings on Axle Pivots • Greaseable Axle Arm Pivots

BUSH HOG EXCLUSIVE:

Driveline safety retaining rings

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>