

Bush Hog® TOUGH Gasoline Powered GT Rotary Cutters

BUSH HOG® TOUGH FEATURES
TOUGH Fabricated Deck Construction
TOUGH Centrifugal Clutch
TOUGH Kevlar Reinforced Belt
TOUGH Powder Coat Paint



Model GT48

MODELS	GT42	GT48
Cutting Width	3 ft 6 inches	4 ft
Cutting Capacity	Up to 1/2 inch diameter	Up to 3/4 inch diameter
Cutting Height	1 to 5 inches	1 to 6 inches
Transport Width	54 inches	64 inches
Engines	10.5 HP Briggs & Stratton® optional electric start; 11 HP Honda electric start	13 HP Honda electric start
Type Hitch	Swivel Ball and Pin	Swivel Ball and Pin
Deck Thickness	12 gauge	11 gauge
Blades	(1) 5/16 x 3 x 42 inches	(2) 3/8 x 3 x 13 inches
Blade Tip Speed	16,300 FPM	16,450 FPM
Tire Size	12 x 3 inches 5 Rib Solid or 13 x 5 x 6 Inch Pneumatic	13 x 5 inches Solid or 13 x 5 x 6 Inch Pneumatic
Drive Belt	V-Belt, Kevlar Construction	V-Belt, Kevlar Construction
Slip Protection	Centrifugal Clutch	Centrifugal Clutch
Approximate Weight	285 lbs	425 lbs
Options	Antiscalp Rollers (two for front and one for rear) Electric Start Package for 10.5 HP Engine Bumper Kit, Offset Hitch (14 inches) for 48 inch Model only Spark Arrestor Kit*	
Warranty	1 year limited warranty; Engine limited warranty administered by manufacturer	

* Spark arrestors are mandatory in the State of California

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>