




MODEL CAPO-6403S
Full Size Stacking Kit with
CAPO-403 & CAPO-603 Line Chef™ Combination Ovens



Standard configuration

*****Standard configuration = CAPO-603 on top.**

You may specify CAPO-403 on top when ordering, if preferred.



Optional configuration

Full Size Stacking Kit Includes:

- CAPO-403 Oven with 4 shelves
- CAPO 603-6 Oven with 6 shelves
(stand from standard CAPO-603 oven not included)
- Stacking Separator
- Base dolly with wheels
- Pressure Regulator (1)
- Water Filter (1)
- Water & drain connection (1)
- Hoses

CAPO-6403S


UPC # 654796-51640-7

Width	Height	Depth	Ship Wt.*
37"	72"	34-3/4"	489 lbs.

* Does not include weight of shipping skids
Ships in 3 cartons on 2 skids



NEMA 6-50 Plug (1 plug per oven)



Stacking Separator for CAPO-403 & CAPO 603 Ovens (Included in CAPO-6403S)

Will hold up to 6 pans (3 sheet pans & 3 steam table pans) (3 of each pan shown in use in Stacking Separator. **Pans not included.**)

For more information, please contact Cadco, Ltd, 145 Colebrook River Road, Winsted, CT 06098
Tel. (860)738-2500 • Fax (860) 738-9772 • E-mail: info@cadco-ltd.com • Web site: www.cadco-ltd.com

9/22/2006 RV05



(NOTE: This page contains specs for the individual CAPO-403 oven. The CAPO-6403S Stacking Kit includes ONE of these ovens, minus the 4" feet, plus a CAPO-603 oven & other accessories listed on front page.)

Model # CAPO-403

Product Name: Countertop Combination Oven; 4 Full Size Sheet Pan Capacity



Line Chef™

Full Size Countertop Combination Oven



Specifications:

Countertop Combination Oven. 4.6 cubic feet cooking chamber has capacity for up to 4 full size steam table pans or 4 full size sheet pans. Steam & convection: roast, bake, cook & hold or any combination. Digital controls for easy operation. Programmable. Probe. Variable steam Venturi drying system. 10 hour timer or continuous on. All stainless double wall insulated construction. **208-240 volts** - Single phase /10,000 watts / 50 amps / NEMA 6-50 Plug /8' cord

Model CAPO-403 - Countertop combination oven provides steam & convection: roast, bake, cook & hold or any combination



NEMA 6-50 Plug

Our combination ovens are made to Cadco Ltd. specifications by UNOX S.p.A., Italy ♦ NSF, UL through CSA Standards
Cadco Model CAPO-403 = UNOX Model XAV403

Standard Features

- **Steam & convection: roast, bake, cook & hold or any combination**
- **4.6 cubic feet cooking chamber (14-1/2" H x 27-1/2" W x 20" D)**
- **Handles 4 full size steam pans** or 4 full size size sheet pans (pans not included)**
Pan spacing 3" (** based on 2-1/2" deep steam pans).
- **Four shelves included**
- Compact design maximizes available space
- Digital controls provide easy operation
- Programmable (Memory for 70 programs)
- Variable steam ● Venturi drying system
- Heat settings from 175° - 500° F
- Even heat system ● Two fans ● Probe
- 10 hour timer or continuous on
- Cool-touch, easy-clean safety door
- Insulated double wall construction
- All stainless exterior; easy to clean
- Water feed, drain lines, filter and pressure regulator not included with product
- **Water filter required** - Call Cadco for current filter model
- Full one year on-site warranty covering parts and labor **plus** two-year warranty on heating element; 90 day warranty on light bulbs & gasket
- Complete internet or phone technical support for installation of water, electricity, drainage, controls and general start-up
- After-market support system to insure that units are properly serviced.
- Chef Support – on-line and via phone
- 208/240 volts /10,000watts/50 amps/single phase/ NEMA 6-50 plug/8' cord
- NSF, UL (through CSA standards)
- Unit must ship by truck, NOT UPS
- Freight class 85

OPTIONAL ACCESSORIES:

XR401: : Oven Stand for CAPO-403. 7 double tiers (adjustable width) for pans
WPR-2B: Water Pressure Regulator 2 BAR
GR1090AO: Shelf for CAPO-403

Model	Color	Electrical			Unit Dimensions	Ship Wt./lbs.	Carton Dimensions	UPC#
		Volts	Watts	Amps				
CAPO-403	Brushed Stainless	208-240	10,000	50	w:37", h:30", l:34-3/4" ~26" without legs	165*	w:40-1/4", h:26", l:37"	654796-51475-5

For more information, please contact Cadco, Ltd, 145 Colebrook River Road, Winsted, CT 06098
Tel. (860)738-2500 ♦ Fax (860) 738-9772 ♦ E-mail: info@cadco-ltd.com ♦ Web site: www.cadco-ltd.com

Due to continual product improvement, specifications and design are subject to change without notice.
9/18/2006 RV05





Cadco, Ltd. Countertop Combination Oven - 4 full size sheet pan capacity Model # CAPO-403




(NOTE: This page contains specs for the individual CAPO-403 oven. The CAPO-6403S Stacking Kit includes ONE of these ovens, minus the 4" feet, plus a CAPO-603 oven & other accessories listed on front page.)

Model # CAPO-403

Product Name: Countertop Combination Oven; 4 Full Size Sheet Pan Capacity



Steam: Water is injected directly into the baking chamber, vaporized and changed into steam when touching the hot heating element. Water should be connected to the oven water inlet by a mechanical filter and a cut-off valve. Water must have a hardness between 0.5°-5°F in order to reduce formation of limestone deposits inside the electro-valve and inside the cooking chamber, and a pressure value between 0.5 - 2 bar (7.25 - 29 PSI.)



Cross corner air flow -High speed, automatic oscillating reversible fan for even cavity heating.



Venturi system - pulls in cool air and pushes out damp air, creating a dry environment.



● CAPO-403 is made to Cadco Ltd. specifications by UNOX S.p.A.

● NSF, UL through CSA Standards
(Cadco Model CAPO-403 = UNOX Model XAV403)

● CSA File No. 202281-0-000 (UNOX) / covers Classes 2831-83 (US) and 2831-03 (Canada)

● NSF Listed (UNOX) to ANSI/NSF Standard 4



Combustible Wall Clearance Required:

Sides: 2"
Rear: 4" from back
Top: 3"



(NOTE: This page contains specs for the individual CAPO-603-6 oven. The CAPO-6403S Stacking Kit includes ONE of these ovens, minus the stand shown below, plus a CAPO-403 oven & other accessories listed on front page.)

Model # CAPO-603-6

Product Name: Full Size Combination Oven; 6 Full Size Sheet Pan Capacity



Line Chef™ Full Size Combination Oven w/ Stand



CAPO-603-6
(pans not included)

(stand not included
in CAPO-6403S
Stacking Kit)

Specifications:

Full Size Combination Oven. 7.0 cubic feet cooking chamber. 6 shelves; capacity for 6 full size sheet pans or steam pans. Steam/ convection: roast, bake, cook & hold or any combination. Digital controls for easy operation. Programmable. Probe. Variable steam Venturi drying system. 10 hour timer or continuous on. All stainless double wall insulated construction. **Stand included. 208-240 volts** - Single phase /10,000 watts / 50 amps / NEMA 6-50 Plug / 8' cord

Models CAPO-603-6 Countertop combination ovens provides steam & convection: roast, bake, cook & hold or any combination



Standard Features- Both Models

- **Steam & convection: roast, bake, cook & hold or any combination**
 - 7.0 cu. ft. cooking chamber (22" H x 27-1/2" W x 20" D)
 - Six shelves included
 - Handles 6 full size steam pans* or 6 full size sheet pans (pans not included)
 - Pan spacing: CAPO-603-6 = 3"; CAPO 603-7 = 2-3/4"
 - Compact design maximizes available space
 - Oven Stand included (*not in CAPO-6403S*). 7 double tiers (adjustable width)
 - Digital controls provide easy operation
 - Programmable (Memory for 70 programs)
 - Variable steam ● Venturi drying system
 - Heat settings from 175° - 500° F
 - Even heat system ● Two fans ● Probe
 - 10 hour timer or continuous on
 - Cool-touch, easy-clean safety door
 - Insulated double wall construction
 - All stainless exterior; easy to clean
 - Water feed, drain lines, filter and pressure regulator
- not included with product
- **Water filter required** - Call Cadco for current filter model
 - Full one year on-site warranty covering parts and labor **plus** two-year warranty on heating element; 90 day warranty on light bulbs & gasket
 - Complete internet or phone technical support for installation of water, electricity, drainage, controls and general start-up
 - After-market support system to insure that units are properly serviced.
 - Chef Support – on-line and via phone
 - 208/240 volts /10,000watts/50 amps/single phase/ NEMA 6-50 plug/ 8' cord
 - NSF, UL (through CSA standards)
 - Unit must ship by truck, NOT UPS
 - Freight class 85
- OPTIONAL ACCESSORIES:**
WPR-2B: Water Pressure Regulator 2 BAR
GR1090AO: Shelf for CAPO-603-6; **GR1055AO:** Shelf for CAPO-603-7
LSR-603-7: Lateral Side Rack/Shelf Supports for CAPO-603-7 (set) (can use on CAPO-603-6 to hold 7 steam pans)

Model	Color	Electrical			Unit Dimensions	Ship Wt./lbs.	Carton Dimensions**	UPC#
		Volts	Watts	Amps				
CAPO-603-6	Brushed Stainless	208-240	10,000	50	w:37", h:60", l:34 3/4"	262*	w:40 1/4", h:33 1/2", l:37"***	654796-51675-9

*does not include weight of shipping skid **& Stand ctn: w: 38 1/4" x h:105/8" x l: 24 1/4"

For more information, please contact Cadco, Ltd, 145 Colebrook River Road, Winsted, CT 06098
 Tel. (860)738-2500 ♦ Fax (860) 738-9772 ♦ E-mail: info@cadco-ltd.com ♦ Web site: www.cadco-ltd.com

Due to continual product improvement, specifications and design are subject to change without notice. 8/28/2006 RV04

Cadco, Ltd. Full Size Combination Oven - up to 6 full size sheet pan capacity



Model # CAPO-603



(NOTE: This page contains specs for the individual CAPO-603-6 oven. The CAPO-6403S Stacking Kit includes ONE of these ovens, minus the stand shown below, plus a CAPO-403 oven & other accessories listed on front page.)

Model # CAPO-603-6



Product Name: Full Size Combination Oven; 6 Full Size Sheet Pan Capacity



CAPO-603-6 comes with 6 shelves; will handle 6 full size sheet pans)

Side View

Top View




Back View



Steam: Water is injected directly into the baking chamber, vaporized and changed into steam when touching the hot heating element. Water should be connected to the oven water inlet by a mechanical filter

and a cut-off valve. Water must have a hardness between 0.5°-5°F in order to reduce formation of limestone deposits inside the electro-valve and inside the cooking chamber, and a pressure value between 0.5 - 2 bar (7.25 - 29 PSI.)



Cross corner air flow - High speed, automatic oscillating reversible fan for even cavity heating.



Venturi system - pulls in cool air and pushes out damp air, creating a dry environment.



- CAPO-603 is made to Cadco Ltd. specifications by UNOX S.p.A.
- NSF, UL through CSA Standards (Cadco Model CAPO-603 = UNOX Model XAV603)
- CSA File No. 202281-0-000 (UNOX) / covers Classes 2831-83 (US) and 2831-03 (Canada)
- NSF Listed (UNOX) to ANSI/NSF Standard 4



Combustible Wall Clearance Required:

- Sides: 2"
- Rear: 4" from back
- Top: 3"

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>