



VX412C SPDT Switching Module

The VX412C is a C size, Register based switching card that provides 32 channels of 5A, Form-C switching. User connection to the module is through two (2) DIN 41612 Type F48M connectors. Normally closed, normally open and common terminals are provided for each of the non-latching relays. MODID and Board Select indicators are included. Module is equipped with BIT capability and shielding.

Specifications:

Maximum Input Voltage:

Terminal to Terminal:

250 Vdc or ac_{rms}

Terminal to Chassis:

250 Vdc or ac_{rms}

Maximum Switchable Voltage:

100 Vdc, 200 Vac_{rms}

Maximum Switchable Current:

(DC or AC_{rms}):

Per Contact: 5A

Per Module: 50A

Maximum Switchable Power:

Per Channel: 150W, 1250VA

Per Module: 1500W, 12500VA

Closed Channel Resistance:

Initially $\leq 0.1 \Omega$

(6Vdc @ 1A)

Insulation Resistance

(between any two points):

$>10^9 \Omega$

Relay Life (operations):

No Load 1×10^7

250 Vac, 5A, Resistive 1×10^5

Relay Operative Time:

4 to 7 msec

Relay Release Time:

1 to 2 msec

Power Up/Down States:

Normally open contact is open.

Power: +5V @ 1.0A typical

+12V @ 1.5A typical

Ordering Information:

Description	Part Number
VX412C	11026205-0001
Locking Conn	See Accessories

VXIbus Compliance

Complies with ANSI/IEEE Std. 1014-1987 and VXIbus Rev 1.4

A16:D16 DTB Slave

Register based

No Interrupts

IACKIN tied to IACKOUT

BRX tied to BGX

Form Factor: Size C

Built-in test via register feedback

Applications

- Power Switching
- Control
- LF Signal Switching

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>