


Overview



- | | |
|--------------------------------|--------------------------------|
| 1. Auto Adjust | 4. OSD Navigation/Input Select |
| 2. Menu/Select | 5. Power |
| 3. OSD Navigation/Input Select | |

Models

Part Number: PL766AA#ABA

HP Care Pack Services

Next Day Onsite Response, 3 years	H2754E
Next Day Onsite Response, 4 years	U7934E
Next Day Onsite Response, 5 years	U7935E
Basic 8-5, 4 Hour Onsite Response, 3 years	U8317E
Basic 8-5, 4 Hour Onsite Response, 4 years	U8318E
Basic 8-5, 4 Hour Onsite Response, 5 years	U8319E
Post Warranty Service, Next Day Onsite	U4925PE

NOTE: For additional information on HP Care Pack Services, please see <http://www.hp.ca/hps/carepack/>.

Technical Specifications

Panel	Type	Active matrix, thin film transistor (TFT)
	Viewable Image Area (diagonal)	17 in (43.2 cm)
	Screen Opening (WxH)	13.4 x 10.7 in (34.0 x 27.2 cm)
	Viewing Angle (typical)	Up to 150° horizontal/135° vertical (10:1 minimum contrast ratio)
	Brightness (typical)	Up to 300 nits (cd/m ²)
	Contrast Ratio (typical)	Up to 500:1
	Response Rate (typical)	8 ms (rise + fall)
	Pixel Pitch	0.264 mm
	Colour Depth Support	16.7 million colors
	Backlight Lamp Life (to half brightness)	40K hours
Video/Other Inputs	Plug and Play	Yes (supports VESA DDC2B and DDC/CI; PC2001 compliant)
	USB 2.0 Hub	Self-powered; two ports (cable included)
	Input Signal	Two connectors: one 15-pin mini D-sub analog VGA and one DVI-D
	Input Impedance	75 ohms ± 2%
	Sync Input	Separate sync (HSYNC/VSYNC)
	Video Cable	15-pin D-sub mini connector; detached
	Video Cable Length	70.9 in (1.8 m); detached
Signal Interface/ Performance	Horizontal Frequency	30 to 83 kHz
	Vertical Frequency	56 to 76 Hz
	Native Resolution	1280 x 1024 @ 60 Hz (analog) 1280 x 1024 @ 60 Hz (digital)
	Max Resolution (Analog)	1280 x 1024 @ 75 Hz
	Max Resolution (Digital)	1280 x 1024 @ 75 Hz
	Preset VESA Graphic Modes (non-interlaced)	640 x 480 @ 60 Hz, 72 Hz, 75 Hz
		720 x 400 @ 70 Hz
		800 x 600 @ 60 Hz, 72 Hz, 75 Hz
		1024 x 768 @ 60 Hz, 70 Hz, 75 Hz
		1280 x 1024 @ 60 Hz, 75 Hz
	Preset MAC Mode	832 x 624 @ 75 Hz
		1152 x 870 @ 75 Hz
	Preset SUN Mode	1152 x 900 @ 76 Hz
	Fail Safe Mode	Yes (limits out of range signal messages)
	Maximum Pixel Clock Speed	140 MHz
	User Programmable Modes	Yes, 15
	Anti-Glare	Yes
Anti-Static	Yes	
AssetControl	Yes (accessible on HP Compaq Business Desktops featuring HP Client Manager)	

Technical Specifications

	Default Colour Temperature	6500° Kelvin	
On Screen Display (OSD) Controls	Buttons and Switches	4-button OSD (auto-adjust, menu, minus, plus); power on/off; second-level OSD buttons include dual-input switch	
	Languages	English, Spanish, French, German, Dutch, Italian, Simplified Chinese	
	User Controls	Size and positioning, contrast, brightness, clock, clock phase, selectable colour temperature, serial number, mode displayed, sleep timer, input selection, factory reset, individual colour contrast, full-screen resolution	
Power	Power Supply	Auto-ranging, 90 to 265 VAC; internal power supply	
	Input Power	100 ~ 240 VAC	
	Nominal Current	1.5 A maximum	
	Frequency	50 ~ 60 Hz	
	Avg. Power Consumption	~33 watts (when displaying standard office applications)	
	Typ. Power Consumption	< 40 watts	
	Max. Power Consumption	< 60 watts	
	Power Saving Mode	< 2 watts	
	Off Mode	< 2 watts	
	Power Cable Length	74.8 in (1.9 m); detached	
Mechanical	Dimensions (H x W x D)	Packaged	17.5 x 17.5 x 8.5 in (44.5 x 44.5 x 21.6 cm)
		Unpacked with stand (minimum height)	13.8 x 14.6 x 10.5 in (35.1 x 37.1 x 26.7 cm)
		Unpacked with stand (maximum height)	19.3 x 14.6 x 9.75 in (49.0 x 37.1 x 24.8 cm)
		Base area (footprint)	11.75 x 9.75 in (29.8 x 24.8 cm)
		Panel only (without stand)	12.4 x 14.6 x 2.5 in (31.5 x 37.1 x 6.4 cm)
	Weight	Packaged	19.5 lb (8.8 kg)
		Unpacked with stand	15.4 lb (7.0 kg)
		Panel Only (without stand)	8.3 lb (3.76 kg)
	Bezel Width	17 mm left and right, 17 mm top, and 24 mm bottom	
	Tilt Range	-5° to +35°	
	Swivel Range	± 170° horizontal swivel	
	Height Adjustable	Yes (5.1 in/13 cm adjustment range)	
Pivot Rotation	Yes, 90° into portrait orientation		
Base	Ships attached and is removable (four screws)		

Technical Specifications

Environmental	Temperature – Operating	41° to 95° F (5° to 35° C)
	Temperature – Non-operating	-4° to 140° F (-20° to 60° C)
	Humidity – Operating	20% to 80%, non-condensing
	Humidity – Non-operating	5% to 90%
	Altitude – Operating	0 to 12,000 ft (0 to 3,658 m)
	Altitude – Non-operating	0 to 40,000 ft (0 to 12,192 m)
Options	HP Silver Flat Panel Speaker Bar – Part number: EE418AA	Powered directly by the monitor or PC, the Speaker Bar seamlessly attaches to the monitor's lower bezel to bring full audio support to select HP flat panel monitors. Features include dual speakers with full sound range and external jack for headphones. Sold separately. For more information, refer to the HP Silver Flat Panel Speaker Bar QuickSpec document.
	HP Compaq 7000 Series Ultra-slim Desktop Integrated Work Centre Stand – Part number: DL641B	Allows mounting of a 15-, 17- or 19-inch HP flat panel monitor and an HP Compaq dc7600 Ultra-slim Desktop PC on a single stand for the convenience of an "all-in-one" form factor. Sold separately. For more information, refer to this product's QuickSpec document.
	HP Flat Panel Monitor Quick Release – Part number: EM870AA*	An easy-to-use, VESA-compliant, flat panel monitor mounting solution that allows you to quickly and securely attach a flat panel monitor to a variety of stands, brackets, arms or wall mounts. For more information, refer to this product's QuickSpec document.
	<p>*NOTE: The HP Flat Panel Monitor Quick Release has been designed to support a maximum of up to 24 lbs (10.9 kg) depending upon the mounting configuration used. Please note this is a total weight limit for all devices mounted, i.e. the combined weight of the monitor and a second device such as the HP Compaq t5720 Thin Client cannot exceed 24 pounds. Because mounting surfaces vary widely and the final mounting method and configuration may vary, mounting fasteners are not supplied (other than the VESA-compliant screws). HP recommends that you consult with a qualified engineering, architectural or construction professional to determine the appropriate type and quantity of mounting fasteners required for your application and to ensure that your mounting solution is properly installed to support applied loads.</p>	
Other	Accessories Included	VGA cable, AC power cord, USB cable, user CD-ROM
	Software	HP Display LiteSaver feature allows you to schedule Sleep mode at preset times to help protect the monitor against image retention, drastically lower power consumption and energy costs, and extend the lifespan of the monitor.
	User Guide Languages	English
	Warranty Languages	English
	Colour	Carbonite black and silver (two-tone)
	VESA External Mounting Kensington Lock-Ready	Yes (standard 4 hole pattern, 100 mm); base must first be removed Yes

Technical Specifications

Certification and Compliance

Australian ACA Approval, Canadian Requirements/CSA, CE Marking, China CCIB/CCEE Approval, CISPR Requirements, Eastern European Approvals, Energy Star Compliant, FCC Approval, German Ergonomic (TUV and GS Mark), ISO 13406-2 Compliant (Pixel Defect Guidelines), Mexican NOM Approval, MPR-II Compliant, PC2001 Compliant, PC99 Certified, S. Korean MIC Approval, Taiwan BSMI Approval, TCO 99 or 03 depending on region (emissions, ergonomics, environment), TUV-Ergo, UL Listed, VCCI Approvals, Microsoft® Windows® Certification

Compatibility

VESA Video Signal Standard (VSI) Compliant video cards have been tested and proven compatible for use with the HP L1740 Flat Panel Monitor. Recommended for use with HP products.

Service and Warranty

Three years parts, labour, and on-site service. 24-hour, 90-day, toll-free technical support. Replacement options may include second business day on-site service, or next business day direct replacement, at HP's sole discretion. With direct replacement, HP will ship a replacement display product directly to you. Using the prepaid shipping labels provided, return your failed display to HP in the same packaging as the replacement. Certain restrictions and exclusions apply. For details see your product warranty or contact HP Customer Support.

© Copyright 2006 Hewlett-Packard Development Company, L.P.

Microsoft and Windows are trademarks or registered trademarks of Microsoft Corporation in the U.S. and other countries.

All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

The information contained herein is subject to change without notice. Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>