

MIMO Wireless ADSL2+ Router

8X coverage, 30% faster
then standard 802.11g



MIMO XR™ Wireless ADSL2+ Router Integrated 4 Ports 10/100Mbps Switch

AR-7064Mg+

✓ RoHS Compliant

Features

ADSL Compliance

- ITU-T G.992.2 (G.lite) and G.992.1 (G.dmt) compliant for Annex A, B, I, J, L, M, and U-R2
- ITU-T G.992.3, G.992.4 for ADSL2
- ITU-T G.992.5 for ADSL2+
- Downstream rates at up to 24Mbps and upstream rates at up to 2Mbps

Network Protocol and Features

- PPPoA (RFC2364), PPPoE (RFC2516), classical IPOA (RFC1577), multiple protocol over AAL5 (RFC1483, RFC2684), DHCP client mode support
- DHCP server and client mode, NAT/NAPT support
- Dynamic Domain Name System (DDNS)
- Software DMZ and Port Forwarding
- 4-port 10/100Mbps Switch with MDI/MDI-X, compliant with IEEE802.3 and 802.3u
- Ethernet to ADSL-self-learning (up to 128MAC) transparent bridging

Management


- Configuration and management via WWW browser with password protected access
- Firmware upgraded via Web-based GUI
- Easy of use with quick start setup
- Factory default setting reset button

Hardware Interface

- IEEE 802.11b/g and MIMO wireless access point
- Up to 108Mbps wireless operation rate
- Wireless security with up to 128-bit WEP Encryption, WPA-PSK, WPA2-PSK, 802.11x



EDIMAX
NETWORKING PEOPLE TOGETHER



Taiwan / Headquarters

Edimax Technology Co., LTD.
TEL:886-2-7739-6888
FAX:886-2-7739-6887
sales@edimax.com.tw

Europe

Edimax Technology Europe B.V.
TEL:31-499-377344
FAX:31-499-372647
sales@edimax.nl

U.K.

Edimax Technology (UK) Ltd.
TEL:44-870-7740226
FAX:44-870-7740227
info@edimax.co.uk

Poland

Edimax Technology Europe
B.V. SP. Z O.O.
Tel: +48(22)-6060-255
Fax: +48(22)-6060-254
sales@edimax.nl

U.S.A.

Edimax Computer Company
TEL:1-408-496-1105
FAX:1-408-980-1530
sales@edimax.com

Latin America

TEL:1-786-845-8099
FAX:1-786-331-8490
sales_latinamerica@edimax.com

China

TEL:8610-6213-9288
FAX:8610-6213-9231

ATM Features

- WAN Mode Support : PPP Over ATM (RFC2364) and PPP Over Ethernet (RFC2516)
- LAN Mode Support : Routed / Bridge Ethernet Over ATM (RFC-2684)
- Classical Internet Protocol Over ATM (RFC-1577)
- Support ATM SAR, ATM AAL5, ATM Forum UNI3.1 / 4.0
- PVC and support up to 15 PVCS

Router Features

- DHCP Server and Client
- NAT (Network Address and Port Translation)
- NAT (Network Address Translation)
- ICMP (Internet Control Message Protocol)
- IGMP (Internet Group Management Protocol)

Bridge Mode

- Ethernet to ADSL self-learning Transparent Bridging (IEEE 802.1D)
- Supports up to 128 MAC learning addresses

Wireless Features

- Support IEEE 802.11g/b Wireless Access Point
- Support 128-Bit and 64-Bit WEP encryption, WPA-PSK, WPA2-PSK
- Transmit Power : 15 dBm with 4dBi SMA antenna
- Receive Sensitivity : 11Mbps : -80dBm / 54Mbps : -65dBm

Specification

Product	AR-7064Mg+
CPU	PSB50505
Flash	4Mbyte
WAN Port	One RJ-11 ADSL Port
LAN Ports	Four 10/100Base-TX Fast Ethernet
Power	9V/1.5A DC Power Adaptor
Dimension	70(H) x 140(W) x 275(D) mm
Temperature	0° ~ 55°C / 32°F ~ 131°F
Humidity	10~90% (Non-Condensing)
Certification	FCC Class B, CE Mark



Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>