



3990BPA

KEY FEATURES: Model 3990BPA

- Power to project in normal room light. Eiki's 3900 series Projectors use a 4,000 ANSI Lumens lamp that's ideal for LCD panel presentations.
- Eiki's steel frame offers structural rigidity and durability that plastic projectors can't match.
- Eiki's patented die-cast aluminum arm and rigid post design eliminates vibration and ensures rock-steady images.
- Match your lens to your screen requirements. Select from models with Triplet high resolution or Singlet wideangle lens.
- Fade-proof LCD presentations. Proper cooling is vital to LCD panel efficiency. Eiki's dual cooling fans keep LCD computer projection panels at peak performance.
- Designed with convenience in mind, Eiki Projectors are even equipped with dual AC power outlets for LCD panel and computer hook-up.
- It's not what you spend today but what you don't spend tomorrow. Eiki protects your investment by using proven, reliable components and backs-up your purchase with an unequalled 5-year factory warranty.
- Transmissive Optical system.
- Built-in storage compartment for transparencies, roll feed and power cord.
- Slide type lamp changer lets you shift to a spare lamp in seconds.
- Hinged platen for easy cleaning and fast lamp replacement.
- Full-sized 10.5" x 10.5" stage with tempered safety glass.

Optional Accessories

- EVD Replacement Lamp
- Transparency Roll Feed Attachment

SPECIFICATIONS: Model 3990BPA

Type	Transmissive console projector	Construction	Die-Cast
ANSI Lumens	4000	Dimensions	22" x 16" x 18"
Projection Lamp	410 Watt 82 Volt FXL	Mirror	Dichroic surface high reflection type
Estimated Lamp Life	50 Hours (Hi lamp setting)	Stage Aperture	10.5" x 10.5"(267 x 267mm)
Lens Speed & Focal Length	12.2~14.2 Vari-Focal Triplet (high resolution)	Power Switch	On/Off push button type
Front Elevation	Up to 25 degrees, down to 5 degrees	Cooling System	Dual fan forced air system
Condenser System	Glare-free plastic fresnel	Weight	27 lbs.
Projection Heads	Folding	Packaged Weight	33 lbs.
Lamp Changer	Yes	Power Requirements	120 Volt, 50/60 Hz; 100/110V or 220/240V
LCD Outlet	Yes	Power Consumption	450 W Approx.
High Lo Switch	Yes	Power Cord	15', 3-prong (grounded) attached
		Safety Compliance	UL Listed
		Warranty - Unit	5 Year limited warranty from date of original purchase for parts and labor(projection lamp and platen glass not covered in warranty coverage).

Prices and Specifications subject to change without notice. ©2001 Eiki International, Inc. 2/13/2003

Eiki International, Inc., 30251 Esperanza, Rancho Santa Margarita, CA 92688-2132. Tel: 800-242-3454; Fax: 800-457-3454, E-mail: usa@eiki.com
 In Canada: 310 First St., Unit 2, P.O. Box 156, Midland, ON L4R 4K8. Tel: 800-563-3454, Fax: 800-567-4069, E-mail: canada@eiki.com
 Fax-on-Demand: (Toll Free) 877-345-4329 Visit our World Wide Web site: <http://www.eiki.com>

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>