


LC-6000: Multimedia with Maximum Impact.

KEY FEATURES:

- 600 ANSI LUMENS LIGHT output at 70% uniformity for brilliant images--even in normal light!
- High-performance lens with power zoom and focus projects up to a 450" diagonal picture from distances up to 86.7'.
- True 640x480 pixel resolution.
- Optical Keystone correction eliminates off axis distortion.
- New Wireless remote mouse controls your computer software from anywhere in the room.



OTHER IMPORTANT FEATURES:

- High light output, long-life 400-Watt Metal Halide lamp.
- Accepts International Video Standards: NTSC, NTSC 4.43, PAL and SECAM., 100-240V, 50/60 Hz.
- Included Accessories: VGA Cable and MAC II Adaptor, Lens Cap, Owner's Manual, Dust Cover, Remote Control, AC Power Cord.
- Optional Accessories: Padded Dust Cover, Hard Shipping Case with wheels, Wired Remote Cord (30 ft. -9M), Mindpath IR50 F/X Windows '95 (3.1), or MindPath IR50 for MAC.

LC-6000 SPECIFICATIONS:

Screen Brightness	.600 ANSI Lumens
Illumination Uniformity	.70%
Size of Color Palette	.16.7 Million
Contrast Ratio	.100 :1
Horizontal Resolution	.550 TV Lines
Projection Lamp	.400-Watt, Long-Life Metal-Halide
Light - RGB Distribution	.Dichroic Mirror System
Imaging System	.3.1" Amorphous TFT Panels x 3
Screen Pixels	.640 x 480 + 307,200
Total Pixels	.307,200 x 3 = 921,600
Lens Type	.Power Zoom and Focus
Image Min. - Max. (Diag.)	.20" - 450" diagonal
Image Min. - Max. (Wide)	.1.3' - 30' (0.41m - 9.14m)
Throw - Min. - Max.	.3.8' - 86.7.' (1.17m - 26.42m)
Width-to-Throw Factor	.Approx. 1.8-2.9
Elevation: Front/Rear	.Variable up to 5 Degrees Up
Keystone Elimination	.Power Shift (B:T) 1:2.3/2.3:1
Scanning	.Auto: H Sync. 15-37.9kHz; V Sync. 49.1-74.4Hz
Image Orientation	.Normal, Left, Right
Remote Control	.IR Projector & Mouse Control
Computer Standards	.VGA, EGA, CGA, MAC
Computer Channels	.1
Computer Inputs	.Supplied VGACable & MAC Adaptor to HDB 15 x 1

SPECIFICATIONS (cont.)

Computer Monitor Out	. "Y" Input Cable
Computer Audio In	. RCA x 2 (L/R)
Video Standards	. NTSC/PAL/SECAM/NTSC 4.43
Video Channels	. 2
Video Input	. AV1: RCAx1, BNC x 1, S-Video x 1, AV2: 1 x RCA
Video Output	. RCAx 1
Video Audio Input	. AV1: RCAx 2 (L/R), AV2: RCA x 2 (L/R)
Audio - Amplifier	. 3 Watts RMS Mono
Audio - Built-in Speaker	. 2" x 3.5" (5cm x 9cm) x 1
Audio - Audio Monitor	. RCA x 2 (L/R)
Size (HxWxD)	. 12.1" x 15.4" x 21.8" (310 x 394 x 560 mm)
Weight	. 51.8Lb. (23.5 kg)
Power Requirements	. AC, 120-240 50/60 Hz
Power Consumption	. 630 Watts
Power Cord	. 10' (3M) Type 3, Detachable
Safety Compliances	. UL Listed
Warranty - Projector	. 1 Year Parts & Labor
Warranty - Projection Lamp	. 90 Days Or 2,000 Hours, Whichever Occurs First.

Specifications subject to change without notice.

©1997 EIKI International, Inc. Printed in the USA. 1/8/97



Eiki International, Inc., 26794 Vista Terrace Dr., Lake Forest, CA 92630 Phone: 800-242-3454; Fax: 800-457-3454, E-mail: eikiusa@ibm.net
 EIKI CANADA, 355 Cranston Cres., P.O. Box 156, Midland, ON L4R 4K8 Tel: 800-563-3454, Fax: 800-567-4069 E-mail: eikicda@eiki.ca
 Visit our World Wide Web site: <http://www.eiki.ca>

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>