

The Genesis 6.1e is the solution for the customer who loves the fidelity and styling of the G6.1, but because of lifestyle considerations, requires a smaller loudspeaker, or a system that can be built in stages. Voiced as an *absolute fidelity*<sup>™</sup> loudspeaker, the G6.1e has the same driver complement as the G6.1, but in a smaller cabinet, and without the built-in subwoofer with two 12-inch woofers and the servo-controlled bass amplifier.

The G6.1e is designed to stand-alone as a stereo pair, or as a component of a high-end home theater, or multi-channel music system together with other models in the 6-Series.

The G6.1e has spectacular imaging and soundstage, and works better in small rooms than the much larger G6.1. The G6.1e is LC-tuned to have optimal bass response down to 48Hz from a relatively small cabinet. This results in phenomenal value for money in a Genesis loudspeaker.

A speaker level through-put allows convenient connection to any Genesis ServoSub<sup>™</sup> for full frequency response. Partnering a pair of G6.1e's with a single G928 results in a stereo system that is "almost" a full-sized pair of G6.1's.

The G6.1e has a rear tweeter that can be turned on or off. Driven out of phase from the front tweeter, this makes the speaker a dipole in the high frequencies, enhancing "air", and soundstage and imaging when the speaker is positioned away from a rear wall.

The G6.1e has aesthetic styling and a range of finishes to suit any décor. Subtle tricks of the architect's and photographer's art have produced a cabinet that is elegant and stylish as well as technically excellent.

Rare and beautiful natural wood veneers are used for the shield, which ensures that no two pairs of the G6.1e will be identical. Optionally, high gloss automotive finishes are available for contemporary homes. Custom colors can also be achieved to suit any décor.



### Genesis Advanced Technologies 6.1e Elegant Floorstander

Frequency Response	48Hz to 36kHz, ± 3dB
Sensitivity	89 dB 1 watt 1 meter
Max/Min Tube Power	500/75 watts
Max/Min Solid State Power	1000/100 watts
Input Impedance	4 ohms (nominal)
HF Transducers	Two Genesis 1" circular ribbon (front & rear)
Midrange Transducer	One Genesis 5" titanium cone
LF Transducers	Two Genesis 6.5" aluminum cone
Controls	Front Tweeter Level (± 1.0 dB) Midrange Level (± 0.75 dB) Rear Tweeter Defeat
Inputs	Speaker level 5-way binding posts
Outputs	Speaker level throughput with 5-way binding posts
Dimensions	H 41 3/4" x W 10 1/4" x D 14" H 1060mm x W 262mm x D 355mm
Weight	79 lbs (35.9 kg)
Finish Options	Maple body with Cebuano Rosewood shield (Standard Finish) Maple body with Olive Burl shield (Premium Finish) Arctic Silver body with Slate Grey shield (Standard Automotive)

\* Specifications are subject to change without notice

**absolute fidelity**<sup>™</sup>

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>