

Specifications — SVDA 6 A MX Distribution Amplifier

Video

Gain	Unity
Bandwidth	30 MHz (-3 dB)
Frequency response	< ± 0.1 dB @ 15 MHz
Differential phase error	0.03° at 3.58 MHz and 4.43 MHz
Differential gain error	0.05% at 3.58 MHz and 4.43 MHz
Crosstalk	-60 dB @ 3.58 MHz

Video input

Number/signal type	1 S-video
Connectors	(1) 4-pin mini DIN female
Nominal level	1 Vp-p for Y of S-video 0.3 Vp-p for C of S-video
Minimum/maximum levels	Analog: 0.4 V to 1.4 Vp-p with no offset at unity gain
Impedance	75 ohms
Return loss	<-30 dB @ 5 MHz

Video output

Number/signal type	6 S-video
Connectors	(6) 4-pin mini DIN
Nominal level	1 Vp-p for Y of S-video 0.3 Vp-p for C of S-video
Minimum/maximum levels	0.4 V to 1.4 Vp-p
Impedance	75 ohms
Return loss	<-30 dB @ 5 MHz
DC offset	±5 mV with input at 0 offset

Sync

Standards	NTSC 3.58, NTSC 4.43, PAL, SECAM
-----------------	----------------------------------

Audio

Gain	Unbalanced output: 0 dB; balanced output: +6 dB
Frequency response	20 Hz to 20 kHz, ±0.05 dB
THD + Noise	0.03% @ 1 kHz at nominal level
S/N	>90 dB, output 21 dB, balanced, at maximum output (unweighted)
Stereo channel separation	>80 dB @ 1 kHz; >60 dB @ 20 kHz
CMRR	>75 dB @ 20 Hz to 20 kHz

Audio input

Number/signal type	1, 2, or 4 stereo balanced (Hi Z or 600 ohms), unbalanced (Hi Z)
Connectors	(1, 2, or 4) 3.5 mm captive screw connector, 5 pole
Impedance	>25k ohms balanced, 50k ohms unbalanced, DC coupled
Maximum level	+24 dBu (balanced or unbalanced) at 1%THD+N

NOTE 0 dBu = 0.775 Vrms, 0 dBV = 1 Vrms, 0 dBV ≈ 2 dBu

Audio output

Number/signal type	6, 12, or 24 stereo, balanced/unbalanced
Connectors	(6, 12, or 24) 3.5 mm captive screw connector, 5 pole
Impedance	50 ohms unbalanced, 100 ohms balanced
Gain error	±0.1 dB channel to channel
Maximum level (Hi-Z)	>+24 dBu, balanced or unbalanced at 1%THD+N
Maximum level (600 ohm)	>+15 dBm, balanced or unbalanced at 1%THD+N

General

Power	100 VAC to 240 VAC, 50/60 Hz, 10 watts, internal, autoswitchable
Temperature/humidity	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Rack mount	Yes, with optional 1U rack shelf, part #60-190-01 or 60-604-01
Enclosure type	Metal
Enclosure dimensions	1.75" H x 8.7" W x 9.4" D (1U high, half rack wide) 4.4 cm H x 22.1 cm W x 23.9 cm D (Depth excludes connectors.)
Product weight	2.5 lbs (1.1 kg)
Shipping weight	5 lbs (3 kg)
Vibration	ISTA 1A in carton (International Safe Transit Association)
Listings	UL, CUL
Compliances	CE, FCC Class A
MTBF	30,000 hours
Warranty	3 years parts and labor

NOTE *All nominal levels are at ±10%.*

NOTE *Specifications are subject to change without notice.*

(7.51-081904-D3)

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>