



LCD MONITOR

|                     |   |      |           |       |      |       |
|---------------------|---|------|-----------|-------|------|-------|
| Display size        | 22" (55,88 cm) WIDE   |      |           |       |      |       |
| Panel Type          | Active Matrix TFT   |      |           |       |      |       |
| Brightness          | 300 cd/m <sup>2</sup> (typ.)                                      |      |           |       |      |       |
| Contrast (typ.)     | 1000:1  |      |           |       |      |       |
| X-Contrast (dyn.)   | -   |      |           |       |      |       |
| Pixel pitch         | 0,282(H) x 0,282(V) mm  |      |           |       |      |       |
| Resolution (H x V)  | WSXGA+ 1680 x 1050  |      |           |       |      |       |
| Response time       | 5 ms (typ.)   |      |           |       |      |       |
| View angles (CR>10) | H/V 170° / 160°   |      |           |       |      |       |
| View angles (CR>5)  |   |      |           |       |      |       |
| Display colors      | 16,7 Mio colors   |      |           |       |      |       |
| Display Surface     | AG  |      |           |       |      |       |
| Input 1             | VGA, Audio  |      |           |       |      |       |
| Input 2             | DVI (HDCP)  |      |           |       |      |       |
| Input 3             |   |      |           |       |      |       |
| Headphone           |   |      |           |       |      |       |
| Speakers            | 1,5 W x 2   |      |           |       |      |       |
| Supply              | AC 100~240V, 50~60Hz  |      |           |       |      |       |
| Consumption         | On:   | 40 W | Stand-by: | < 2 W | Off: | < 1 W |
| Operation Temp/Hum  | 5 ~ 40°C  |      | 20 ~ 80%  |       |      |       |
| Dimension (W*D*H)   | 510 x 202 x 424 mm  |      |           |       |      |       |
| Net weight          | 4,9 kg  |      |           |       |      |       |
| Tilt                | 0°~ 20°   |      |           |       |      |       |
| Kensington Lock     | ✓   |      |           |       |      |       |
| VESA mounting       | VESA Standard, 100mm  |      |           |       |      |       |
| On screen display   | EN, GE, FR, IT, SP, JP, CN, RU, NO, NL, PL, PT, SW,               |      |           |       |      |       |
| Safety              | CE, FCC, BSMI, C-Tick, VCCI, CB, UL/CUL, MIC, BAU-MARK, CCC, GOST |      |           |       |      |       |
| Emission            | TCO03   |      |           |       |      |       |
| Power saving        | EnergyStar  |      |           |       |      |       |
| Extras 1            | Windows VISTA Premium   |      |           |       |      |       |
| Extras 2            |   |      |           |       |      |       |
| Extras 3            |   |      |           |       |      |       |
| EAN                 | 4710859555267   |      |           |       |      |       |
| incl Accessory      | 1.8m Power Cord, 1.8m VGA cable, Audio Cable, CD Menu & QSG       |      |           |       |      |       |



© HANNspree Europe GmbH. Information in this document is subject to change without notice. All brand-, product-, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies. Screenshots are simulated.

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>