



# QuickSpecs

## Overview



- |  |   |
|--|---|
| 1. WWAN antennas (select models)               | 13. Touchpad                                  |
| 2. WLAN antennas                               | 14. Touchpad pick buttons                     |
| 3. Dual-microphone array*                      | 15. Touchpad on/off button with LED indicator |
| 4. Webcam LED indicator (with optional webcam) | 16. Stereo microphone in                      |
| 5. Optional 720p HD webcam                     | 17. Stereo headphone/line out                 |
| 6. Stereo speakers                             | 18. Media Card Reader                         |
| 7. HP QuickWeb button with LED indicator       | 19. Hard drive activity LED indicator         |
| 8. Wireless on/off button with LED indicator   | 20. Power button with LED indicator           |
| 9. Optical drive (select models)               | 21. HP Power Assistant function key           |
| 10. Optional RJ-11/modem port                  | 22. Volume mute function key                  |
| 11. (2) USB 2.0 ports                          | 23. Volume down function key                  |
| 12. Optional HP Fingerprint Sensor             | 24. Volume up function key                    |

\* Models without optional webcam have single integrated microphone.




- |                                   |                                   |
|-----------------------------------|-----------------------------------|
| 1. Battery charging LED indicator | 6. RJ-45/Ethernet port            |
| 2. HDMI port                      | 7. VGA/external monitor connector |

# QuickSpecs

## Overview

- |                        |                        |
|------------------------|------------------------|
| 3. USB 2.0 port        | 8. Vent                |
| 4. USB 2.0 port        | 9. Power connector     |
| 5. ExpressCard/34 slot | 10. Security lock slot |




- |   |                   |
|---|-------------------|
| 1. Battery and access cover release latches                 | 4. Vents          |
| 2. Battery bay  | 5. Hard drive bay |
| 3. SIM card slot (select units, located inside battery bay) |                   |


## HP ProBook 4530s Notebook PC HP ProBook 4730s Notebook PC

# QuickSpecs

## Overview



- |  |   |
|--|---|
| 1. WWAN antennas (select models)               | 14. Touchpad                                  |
| 2. WLAN antennas                               | 15. Touchpad pick buttons                     |
| 3. Dual-microphone array*                      | 16. Touchpad on/off button with LED indicator |
| 4. Webcam LED indicator (with optional webcam) | 17. Stereo microphone in                      |
| 5. Optional 720p HD webcam                     | 18. Stereo headphone/line out                 |
| 6. Stereo speakers                             | 19. Media Card Reader                         |
| 7. HP QuickWeb button with LED indicator       | 20. Hard drive activity LED indicator         |
| 8. Wireless on/off button with LED indicator   | 21. Power button with LED indicator           |
| 9. Optical drive (select models)               | 22. HP Power Assistant function key           |
| 10. Numeric keypad                             | 23. Volume mute function key                  |
| 11. Optional RJ-11/modem port                  | 24. Volume down function key                  |
| 12. (2) USB 2.0 ports                          | 25. Volume up function key                    |
| 13. Optional HP Fingerprint Sensor             |   |




- |                                   |                                   |
|-----------------------------------|-----------------------------------|
| 1. Battery charging LED indicator | 6. RJ-45/Ethernet port            |
| 2. HDMI port                      | 7. VGA/external monitor connector |
| 3. USB 2.0 port                   | 8. Vent                           |
| 4. USB 2.0 port                   | 9. Power connector                |

# QuickSpecs

## Overview

5. ExpressCard/34 slot

10. Security lock slot



1. Battery and access cover release latches

4. Vents

2. Battery bay

5. Hard drive bay

3. SIM card slot (select units, located inside battery bay)

## At A Glance

- Genuine Windows 7 versions, Genuine Windows Vista Home Basic, SUSE Linux, or FreeDOS
- Thin, lightweight design with brushed aluminum finish for durability and style, wear-resistant HP DuraFinish
- Full-sized spill-resistant keyboard; full separate numeric keypad on HP ProBook 4530s and 4730s
- Larger Touchpad with gestures support, on/off button with LED indicator
- Enhanced security features including HP ProtectTools, HP Face Recognition, optional HP Fingerprint Sensor, and optional HP Privacy Filter
- Optional HD webcam with dual-microphone array for video conferencing
- HDMI port for connecting to high-resolution displays; USB 2.0 ports
- ArcSoft TotalMedia Suite for playing, creating, and editing video and audio files
- SRS Premium Sound optimized for high fidelity audio
- Widescreen LED-backlit HD display with 16:9 aspect ratio
  - HP ProBook 4330s: 13.3-inch diagonal HD, BrightView optional
  - HP ProBook 4430s: 14.0-inch diagonal HD, BrightView optional
  - HP ProBook 4530s: 15.6-inch diagonal HD, BrightView optional, or HD+
  - HP ProBook 4730s: 17.3-inch diagonal HD+
- Choice of 2nd generation Intel® Core™ i7, i5 and i3 processors, and Intel Celeron processor
- HP QuickWeb for convenient online access without long boot-up times
- Flexible wireless connectivity options controlled by HP Connection Manager:
  - Integrated HP Mobile Broadband Module\*
  - Integrated 802.11 b/g/n wireless LAN module
  - Integrated 802.11 a/b/g/n or b/g/n with Bluetooth 3.0 High Speed (HS) combo card\*\*
- HP DayStarter for calendar display during startup
- HP Power Assistant to conserve power, increase battery run-time, monitor power needs, report workforce power consumption
- BFR/PVC-free\*\*\*, ENERGY STAR qualified and EPEAT TBD registered in the U.S. EPEAT status varies by country- please see epeat.net.

## Overview

\* Available only on HP ProBook 4330s and 4530s with integrated graphics.

\*\* Available on select models.

\*\*\* This notebook is brominated flame retardant and polyvinyl chloride-free (BFR/PVC-free) on notebooks that are non-WWAN; meeting the evolving definition of 'BFR/PVC-free' as set forth in the "iNEMI Position Statement on the 'Definition of Low-Halogen' Electronics (BFR/CFR/PVC-Free)". Plastic parts contain < 1000 ppm (0.1%) of bromine [if the Br source is from BFRs] and < 1000 ppm (0.1%) of chlorine [if the Cl source is from CFRs or PVC or PVC copolymers]. Power supply and power cords are not BFR/PVC-free. Service parts after purchase may not be BFR/PVC-free.

# QuickSpecs

Standard Features (availability may vary by country)

## Processors

### 2<sup>nd</sup> Generation Intel Core i7 Processors

Intel Core i7-2630QM Processor (2.0 GHz, 6 MB L3 cache, 4 cores/8 threads, 45W)\* †  
Up to 2.9 GHz with Intel Turbo Boost Technology

Intel Core i7-2620M Processor (2.70 GHz, 4 MB L3 cache, 2 cores/4 threads, 35W)\*  
Up to 3.40 GHz with Intel Turbo Boost Technology

### 2<sup>nd</sup> Generation Intel Core i5 Processors

Intel Core i5-2540M Processor (2.60 GHz, 3 MB L3 cache, 2 cores/4 threads, 35W)\*  
Up to 3.30 GHz with Intel Turbo Boost Technology

Intel Core i5-2520M Processor (2.50 GHz, 3 MB L3 cache, 2 cores/4 threads, 35W)\*  
Up to 3.20 GHz with Intel Turbo Boost Technology

Intel Core i5-2410M Processor (2.30 GHz, 3 MB L3 cache, 2 cores/4 threads, 35W)\*  
Up to 2.90 GHz with Intel Turbo Boost Technology

### 2<sup>nd</sup> Generation Intel Core i3 Processors

Intel Core i3-2310M Processor (2.10 GHz, 3 MB L3 cache, 2 cores/4 threads, 35W)\*

### Intel Celeron Processor

Intel B810 Processor (1.60GHz, 2MB L3 Cache, 2 threads, 35W)\*

**NOTE:** Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

\* Intel's numbering is not a measurement of higher performance.

† Only available on HP ProBook 4530s and 4730s with discrete graphics.

## Operating System

### Preinstalled

Genuine Windows 7 Professional 32\*  
Genuine Windows 7 Professional 64\*  
Genuine Windows 7 Home Premium 32\*  
Genuine Windows 7 Home Premium 64\*  
Genuine Windows 7 Home Basic 32\* (select countries)  
Genuine Windows 7 Starter\* (select countries and configurations)  
Genuine Windows Vista Home Basic 32\*\*  
SuSE Linux Enterprise Desktop 11  
FreeDOS

### Supported

Genuine Windows XP Professional 32

\* System may require upgraded and/or separately purchased hardware and/or a DVD drive to install the Windows 7 software and take full advantage of Windows 7 functionality.

See: <http://www.microsoft.com/windows/windows-7/> for details.

\*\* Certain Windows Vista product features require advanced or additional hardware. See: <http://www.microsoft.com/windowsvista/getready/hardwarereqs.mspx> and <http://www.microsoft.com/windowsvista/getready/capable.mspx> for details. Windows Vista Upgrade Advisor can help you determine which features of Windows Vista will run on your computer. To download the tool, visit: <http://www.windowsvista.com/upgradeadvisor>.

## Chipset

Mobile Intel HM65 Express Chipset

## Standard Features (availability may vary by country)

### Graphics

Models with integrated graphics (not an option on HP 4730s):

Intel HD Graphics 3000

Microsoft DirectX 10.1 (Shader Model 4.1) and OpenGL 3.0 capable

**NOTE:** Intel HD Graphics for configurations with Celeron processor

Models with discrete graphics (not available at product introduction)\*:

AMD Radeon™ HD 6490M with 512 MB or 1 GB dedicated DDR3 video memory

Microsoft DirectX 11 (Shader Model 5.0) and OpenGL 4.0 capable

\* Because the HP ProBook 4730s comes only with discrete graphics, it will become available after initial product introduction. Discrete graphics is planned to be available on all of these models in May 2011.

### Display

#### Internal

HP ProBook 4330s:

13.3-inch diagonal LED-backlit HD anti-glare (1366 x 768 resolution)

13.3-inch diagonal LED-backlit HD BrightView (1366 x 768 resolution)

HP ProBook 4430s:

14.0-inch diagonal LED-backlit HD anti-glare (1366 x 768 resolution)

14.0-inch diagonal LED-backlit HD BrightView (1366 x 768 resolution)

HP ProBook 4530s:

15.6-inch diagonal LED-backlit HD anti-glare (1366 x 768 resolution)

15.6-inch diagonal LED-backlit HD BrightView (1366 x 768 resolution)

15.6-inch diagonal LED-backlit HD+ WVA anti-glare (1600 x 900 resolution)

HP ProBook 4730s:

17.3-inch diagonal LED-backlit HD+ anti-glare (1600x900 resolution)

#### External

Optional HP Privacy Filter

Up to 32-bit per pixel color depth

**VGA** port supports resolutions up to 2048 x 1536 at 75 Hz, and lower resolutions at up to 100 Hz.

**HDMI** port supports direct connection to high-definition displays with up to 1920 x 1080 resolution and 7-channel audio with one convenient cable (not included).

**NOTE:** Resolutions are dependent upon monitor capability, and resolution and color depth settings.

### Memory

#### Standard

DDR3 PC3-10600 SDRAM (1333 MHz)

Two SODIMM slots supporting dual-channel memory

1 GB, 2 GB, and 4 GB SODIMMs

#### Maximum

Upgradeable to 8 GB with 4 GB SODIMMs

in slots 1 and 2

#### Dual-channel

Maximized dual-channel performance requires SODIMMs of the same size and speed in both memory slots.

**NOTE:** Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed. Full availability of 4 GB or more of memory requires Windows Vista Business 64-bit or Linux. With Windows 32-bit operating systems, the amount of usable memory is dependent upon your configuration, so that above 3 GB all memory may not be available due to system resource requirements.

# QuickSpecs

## Standard Features (availability may vary by country)

**Communications** Realtek Ethernet (10/100/1000 NIC)\*  
Optional 56K V.92 modem\*\*

\* The term "10/100/1000" or "Gigabit" Ethernet indicates compatibility with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/s. For high-speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

\*\* Designed for downloads from 56K modem compliant sources. Maximum achievable download transmission rates currently do not reach 56 KB/s, and will vary with line conditions. Modem availability is subject to country regulatory approval.

**Wireless Devices** Support for a broad range of secure, integrated wireless options featuring support for the latest industry standards.

**Mobile Broadband options** Mobile Broadband (WWAN) requires a Windows operating system and is available in select countries as a factory configurable feature for the HP ProBook 4330s and 4530s with integrated graphics only. Two 850/900/1575/1700/1800/1900/2100 MHz antennas integrated in the top of the display panel support current and future WWAN technologies.

**NOTE:** Separately purchased mobile network operator service is required.

**HP Ic2010 HSPA Mobile Broadband Module** Integrated mobile broadband module that provides connectivity to UMTS (HSPA) networks.

**HP un2430 EV-DO/HSPA Mobile Broadband Module** Integrated mobile broadband module with Gobi global mobile Internet technology that provides connectivity to both CDMA (EVDO) and UMTS (HSPA) networks. It also provides GPS functionality for various mapping applications and security applications such as Computrace Pro for HP ProtectTools.  
(not available at product introduction)

**802.11 integrated wireless LAN options** Wi-Fi certified\*  
Wired Equivalent Privacy (WEP) support up to 128-bit keys  
Wi-Fi Protected Access (WPA) and WPA2 support  
802.1x authentication support, including EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, and LEAP  
Advanced Encryption Standard (AES) support  
Dual antennas integrated in the display enclosure

**Realtek 8188GN 802.11 b/g/n 1x1 WiFi Adapter** Integrated support for 802.11 b, g, and n  
Up to 150 mbps data rate

**Intel Centrino Advanced-N 6230 802.11 a/b/g/n 2x2 WiFi and Bluetooth 2.1+EDR Combo Adapter** Integrated support for 802.11 a, b, g, and n  
Up to 300 mbps data rate  
Bluetooth Specification 2.1+EDR compliant  
Works with a wide range of Bluetooth devices

**Ralink 3592BC8 802.11 a/b/g/n 2x2 WiFi and Bluetooth 3.0+HS Combo Adapter\*** Integrated support for 802.11 a, b, g, and n  
Up to 300 mbps data rate  
Bluetooth Specification 3.0 High Speed (HS)\* and 2.1 compliant  
Works with a wide range of Bluetooth devices





# QuickSpecs

Standard Features (availability may vary by country)

<b>Atheros 9285GN 802.11 b/g/n 1x1 WiFi and 3011 Bluetooth 3.0+HS Combo Adapter*</b>	Integrated support for 802.11 b, g, and n Up to 150 mbps data rate Bluetooth Specification 3.0 High Speed (HS)* and 2.1 compliant Works with a wide range of Bluetooth devices
--	---

\* Bluetooth 3.0+HS support requires a Windows operating system.

## Keyboard

The HP spill-resistant keyboard is designed using a thin layer of Mylar film under the keyboard and a drain system that funnels fluid through a hole in the bottom of the notebook. This minimizes the risk of damage to sensitive components underneath. The 101/102-key compatible keyboard features a full-pitch key layout with desktop keyboard features, such as editing keys, both left and right control and alt keys, and function keys. US and International key layouts are available. The HP ProBook 4530s and 4730s include a separate numeric keypad.

## Launch Buttons and Function Keys

Separate launch buttons provide easy access to wireless on/off and HP QuickWeb. Function keys provide control of features including: standby mode, display brightness, external display, HP Power Assistant, volume mute, volume down, volume up, and media control.

## Pointing device

Touchpad with gestures support, on/off button with LED indicator, two-way scroll, two pick buttons

## Expansion card slots

<b>ExpressCard/34 slot</b>	Supports ExpressCard/34 (34 mm x 75 mm x 5 mm) card sizes
<b>Media Card Reader</b>	Supports High Speed SD 3.0 (Secure Digital), MMC (MultiMedia Card), Memory Stick, Memory Stick Pro, Memory Stick Pro Duo*, SD Micro, MMC Micro

\* Memory Stick Pro Duo Adapters are required and sold separately. Inserting a Memory Stick Pro Duo Card directly into your notebook could damage the memory card and/or notebook.

## Internal Storage

<b>Hard drives</b>	250/320/500/750 GB 7200 rpm SMART SATA II 250/320/500/640 GB 5400 rpm SMART SATA II
--------------------	--

**NOTE:** Up to 15 GB is reserved for the system recovery software.

<b>HP 3D DriveGuard</b> (Windows models only)	The hard drive is mounted directly to the notebook frame, reducing the transmission of shock to the hard drive. Uses three-axis digital motion detection with intelligent sensitivity to help protect the hard drive during normal use from shock and vibration. The digital accelerometer temporarily halts all data transfer and parks the hard drive when abrupt motion is detected.
--	---

## Removable Storage

<b>Fixed optical drives</b>	Blu-ray R/RE DVD+/-RW SuperMulti DL Drive* Blu-ray ROM DVD+/-RW SuperMulti DL Drive* DVD+/-RW SuperMulti DL Drive DVD-ROM Drive
-----------------------------	--

### Weight saver

\* Blu-ray drives not available on configurations with an Intel Celeron processor.



# QuickSpecs

Standard Features (availability may vary by country)

<b>Interfaces</b>	<b>VGA</b>	One
	<b>HDMI</b>	One
	<b>Stereo microphone in</b>	One
	<b>Stereo headphone/line out</b>	One
	<b>Power connector</b>	One
	<b>RJ-11/modem (optional)</b>	One
	<b>RJ-45/Ethernet</b>	One
	<b>USB 2.0</b>	Four
	<b>LED status indicators</b>	Nine

## Audio/Visual

SRS Premium Sound™  
 Integrated stereo speakers  
 Integrated microphone (dual-microphone array when equipped with optional webcam)  
 Function keys for volume mute, volume up, volume down; play, rewind, and fast-forward of video and audio files  
 Stereo headphone/line out  
 Stereo microphone/line in

Optional 720p HD webcam

- HD format (widescreen)
- Supports videoconferencing and still image capture
- High quality fixed focus lens
- Video capture at various resolutions up to 1280x720 resolution (720p) and up to 30fps
- M-JPEG compression supports higher frame rates for video capture and videoconferencing
- Improved low light sensitivity
- Improved dynamic range

## Software

<b>Preinstalled software with Windows Operating System</b>	HP Recovery Manager
	HP Support Assistant
	HP ProtectTools Security Manager
	HP ProtectTools for Central Management
	HP Hotkey Support
	HP QuickWeb
	HP Power Assistant
	HP Connection Manager 4.0
	HP DayStarter
	Microsoft Office 2010 preloaded (purchase of a Product Key required to activate a full Office 2010 suite)*
	Norton Internet Security 2011**
	PDF Complete Special Edition***
	ArcSoft Total Media Suite
	HP Webcam Software (select models)
	Skype
<b>Additional software available from the web</b>	HP SoftPaq Download Manager



## Standard Features (availability may vary by country)

\* Microsoft Office 2010 Preloaded includes reduced functionality versions of Word and Excel. Purchase of Product Key required to activate full Office 2010 suite available at participating resellers/retailers and <http://www.office.com>.

\*\* Norton Internet Security 2011 includes 60 days of complimentary live updates; subscription required for live updates thereafter. Internet access required to receive updates.

\*\*\* PDF Complete Special Edition 60 day trial; purchase license afterwards for full functionality.

---

**HP Recovery Manager** Models shipped with Windows 7 or Windows Vista include HP Recovery Manager. HP Recovery Manager enables fast recovery of the factory preinstalled image if the system becomes corrupted or if important system files are accidentally deleted. Up to 20 GB of the hard drive is reserved for the system recovery software.

---

## Security

### Standard Features

HP ProtectTools Security Manager (standard modules include)

- Credential Manager
- Computrace\* Pro
- Device Access Manager
- Drive Encryption
- Face Recognition (webcam configurations only)
- File Sanitizer
- Privacy Manager
- Embedded Security

Enhanced Pre-Boot Security

HP SpareKey

One-Step Logon

Security lock slot

Support for Intel AT\*\*

### Optional Features

HP Fingerprint Sensor

HP Privacy Filter

\* The Computrace agent is shipped turned off, and must be activated by customers when they purchase a subscription with terms ranging from one to five years.

For more information on HP security solutions refer to: <http://www.hp.com/products/security>.

\*\* Intel AT security requires a separately purchased Absolute Computrace service subscription and must be activated and configured. Check with Absolute for availability in your country. Intel and HP assume no liability for lost or stolen data and/or systems or any other damages resulting therefrom. See <http://www.intel.com/technology/anti-theft/>

---

# QuickSpecs

## Standard Features (availability may vary by country)

**HP ProtectTools Security Manager with Central Management** HP ProtectTools Security Manager is the security platform for business notebooks and desktops. The HP ProtectTools Security Manager is an extensible client security console that delivers enhanced security capabilities through add-on software modules. The ProtectTools modules are available on the hard drive (also downloadable from the web) and can be configured in Software Setup.

HP ProtectTools is centrally manageable with the capability to manage notebooks from a single point. HP ProtectTools is management ready out of the box, in partnership with Digital Persona. Features address requirements that customers expect from a centrally managed security solution such as user provisioning, credential reset, and credential revocation.

HP ProtectTools provides two separate management solutions, targeted at the enterprise and the SMB:

- Digital Persona Pro AD: Designed for the enterprise customer. Integrates with Active Directory and gives IT Managers the ability to provision users, create login policies based on passwords, biometrics or smartcards. Management features also include remote credential recovery in case the user forgets the password, loses the smartcard or cannot use the fingerprint reader for any reason. In addition, advanced auditing capabilities are also built in. Digital Persona Pro AD is available now.
- Digital Persona Pro Workgroup: Designed for the small business customer. Provides features similar to the Active Directory version, but for workgroups. Workgroup activation is built into HP ProtectTools, and activation of up to 5 seats is completely free.

For more information on Central Management for HP ProtectTools, refer to: <http://www.hp.com/products/security>.

## Power Supply

Models with integrated graphics: External 65-watt Smart AC adapter  
 Models with discrete graphics: External 90-watt Smart AC adapter  
 6-foot (1.8-meter) power cord included; total length including external AC adapter is 12 feet (3.66 meter)  
 HP Fast Charge\*

\* HP Fast Charge recharges your battery up to 90% within 90 minutes when the system is off. HP Fast Charge does not apply to the HP 9-cell battery.

## Battery

### Primary battery

HP ProBook 4330s, 4430s, and 4530s:  
 HP 9-cell (93 WHr) Li-Ion battery  
 HP 6-cell (47 WHr) Li-Ion battery

HP ProBook 4730s:  
 HP 8-cell (73 WHr) Li-Ion battery

## Standard Features (availability may vary by country)

### Battery Life

	Configurations with integrated graphics
<b>HP ProBook 4330s</b>	
<b>9-cell battery</b>	Up to 12 hours 15 minutes
<b>6-cell battery</b>	Up to 6 hours
<b>HP ProBook 4430s</b>	
<b>9-cell battery</b>	Up to TBD
<b>6-cell battery</b>	Up to TBD
<b>HP ProBook 4530s</b>	
<b>9-cell battery</b>	Up to 12 hours 45 minutes
<b>6-cell battery</b>	Up to 6 hours 15 minutes
<b>HP ProBook 4730s</b>	
<b>8-cell battery</b>	Up to TBD

**NOTE:** Battery life will vary depending on the product model, configuration, loaded applications, features, use, wireless functionality and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See MobileMark07 battery benchmark [www.bapco.com/products/mobilemark2007](http://www.bapco.com/products/mobilemark2007) for additional details.

**System Standby Time** Up to 1 week

---

**Power Conservation** Supports enhanced Intel SpeedStep technology (allows Battery Optimized Mode, Maximum Performance Mode, or Automatic mode)  
ATI PowerPlay technology  
Hibernation  
Standby  
ACPI compliance

---

**Service and Support** HP Services offers limited 3-year, 1-year and 90-day warranty options depending on country; 1-year limited warranty on primary battery. Warranty upgrades are also available. HP Care Pack Services extend service contracts beyond the standard warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/lookuptool>. Additional HP Care Pack Services information by product is available at: <http://www.hp.com/hps/carepack>.  
**NOTE:** Certain restrictions and exclusions apply. Consult the HP Customer Support Center for details.  
<http://h20000.www2.hp.com/bizsupport/TechSupport/ProductRoot.jsp>.

# QuickSpecs

Options (availability may vary by country)

<b>Memory</b>	HP 1 GB (DDR3 1333 MHz) SODIMM	AT911AA#xxx
	HP 2 GB (DDR3 1333 MHz) SODIMM	AT912AA#xxx
	HP 4 GB (DDR3 1333 MHz) SODIMM	AT913AA#xxx
<b>Storage</b>	HP 250 GB Pocket Media Drive	FE477AA
	HP Mobile USB DVD	XQ543AA
	HP Mobile USB DVDRW	BU516AA
	HP Mobile Blu-ray USB DVDRW	XQ546AA
<b>Power</b>	HP 90W Smart AC Adapter	ED495AA#xxx
	HP 90W Smart AC/Auto/Air Combo Adapter	AJ652AA#xxx
	HP 90W Smart Auto/Truck Adapter	ED493AA
	HP 65W Slim Adapter	AX727AA#xxx
	HP 90W Slim Adapter	BT796AA#xxx
<b>Carrying Cases</b>	HP Basic Carrying Case	AJ078AA
	HP Business Nylon Case	BP848AA
	HP Professional Slim Top Load Case	AY530AA
<b>Security</b>	HP Notebook Combo Lock	AY475AA#xxx
	HP Keyed Cable Lock	BV411AA
	HP 13.3-inch Display Privacy Filter	AU649AA#xxx
	HP 14.0-inch Display Privacy Filter	AU100AA#xxx
	HP 15.6-inch Display Privacy Filter	AU103AA#xxx
	HP 17.3-inch Display Privacy Filter	AU650AA#xxx
<b>Input/Output Devices</b>	HP USB Optical Travel Mouse	RH304AA
	HP USB/PS2 Optical 2-Button Scroll Mouse	DC369A
	HP USB Keyboard & Mouse Bundle	RC465AA#xxx
	HP Notebook Projection Companion	AX325AA#xxx

# QuickSpecs

## Technical Specifications

<b>System Unit</b>	<b>Dimensions (HxWxD)</b>	HP ProBook 4330s: 1.10 in (at front) x 12.99 in x 9.28 in 2.79 cm (at front) x 33.0 cm x 23.5 cm
		HP ProBook 4430s: 1.11 in (at front) x 13.0 in x 9.26 in 2.81 cm (at front) x 33.9 cm x 23.5 cm
		HP ProBook 4530s: 1.13 in (at front) x 14.76 in x 10.1 in 2.87 cm (at front) x 37.4 cm x 25.6 cm
		HP ProBook 4730s: 1.15 in (at front) x 16.29 in x 11.00 in 2.9 cm (at front) x 41.4 cm x 27.9 cm
<b>Weight</b>		HP ProBook 4330s: Starting at 4.41 lb (2.0 kg) without optical drive or 4.7 lb (2.13 kg) with optical drive
		HP ProBook 4430s: Starting at 4.51 lb (2.04 kg) without optical drive or 4.83 lb (2.218 kg) with optical drive
		HP ProBook 4530s: Starting at 5.22 lb (2.36 kg) without optical drive or 5.55 lb (2.51 kg) with optical drive
		HP ProBook 4730s: Starting at 6.44 lb (2.92 kg) without optical drive or 6.72 lb (3.05 kg) with optical drive
<b>NOTE:</b> Height varies depending upon where on the notebook the measurement is made. Weight varies by configuration and components.		
<b>Stand-Alone Power Requirements</b> (AC Power)	Nominal Operating Voltage	18.5 V
	Average Operating Power	with integrated graphics: TBD W with discrete graphics: TBD W
	Max Operating Power	< 90 W or < 65W
<b>Temperature</b>	Operating*	32° to 95° F (0° to 35° C) (not writing optical) 41° to 95° F (5° to 35° C) (writing optical)
	Non-operating	-4° to 140° F (-20° to 60° C)
<b>Relative Humidity</b>	Operating	10% to 90%, non-condensing
	Non-operating	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature
<b>Shock</b>	Operating	125 G, 2 ms, half-sine
	Non-operating	200 G, 2 ms, half-sine
<b>Random Vibration</b>	Operating	0.75 grms
	Non-operating	1.50 grms
<b>Altitude</b> (unpressurized)	Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
	Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)
<b>Planned Industry Standard Certifications</b>	UL	Yes
	CSA	Yes
	FCC Compliance	Yes



## Technical Specifications

ENERGY STAR®	Select models**
EPEAT	Registered TBD in United States***
ICES	Yes
Australia / NZ A-Tick Compliance	Yes
CCC	Yes
Japan VCCI Compliance	Yes
KCC	Yes
BSMI	Yes
CE Marking Compliance	Yes

\* At temperatures above 86° F (30° C), the Intel Core i3-2310M Processor may not run at maximum clock speed.

\*\* Configurations of the HP ProBook 4330s, HP Probook 4430s, HP ProBook 4530s, and HP Probook 4730s that are ENERGY STAR qualified are identified as HP ProBook 4330s ENERGY STAR, HP ProBook 4430s ENERGY STAR, HP ProBook 4530s ENERGY STAR, and HP Probook 4730s ENERGY STAR on HP websites and on [www.energystar.gov](http://www.energystar.gov).

\*\*\* EPEAT registration varies by country. See [www.epeat.net](http://www.epeat.net) for registration status by country. EPEAT status listed above applies to U.S.

**NOTE:** For accessibility information on HP products, please visit: <http://www.hp.com/accessibility>.

---

### Audio SRS Premium Sound

---

<b>Hardware</b>	<b>Implementation</b>	IDT 92HD87 High Definition CODEC
	<b>Touch-Sensitive Volume Controls</b>	Volume up, volume down, and mute
	<b>Full Duplex</b>	Yes
	<b>Microphone In</b>	Stereo
	<b>Headphone/Line Out</b>	Stereo
	<b>Integrated Microphone</b>	Yes, dual digital microphone array when equipped with optional webcam

---

<b>Audio Output Quality</b>	<b>Frequency Response</b>	20 Hz – 20 kHz
	<b>Signal to Noise Ratio</b>	>85 dB
	<b>Total Harmonic Distortion</b>	0.01%
	<b>Noise Floor</b>	-110 dB
	<b>Play/Record Sampling Rate(s)</b>	8 kHz – 48kHz
	<b>DAC</b>	16, 20 or 24-bit
	<b>ADC</b>	16 or 20-bit

---

<b>Integrated Stereo Speakers</b>	<b>Power Rating</b>	2 Watts
	<b>Impedance</b>	4 Ohms

---



# QuickSpecs

## Technical Specifications

### Power

<b>HP 90W Smart AC Adapter</b>	<b>Dimensions</b>	5.00 x 1.97 x 1.1 in (12.7 x 5.0 x 2.9 cm)		
	<b>Weight</b>	0.82 lb (370 g)		
	<b>Input</b>	100 to 240 VAC		
		Input Efficiency	87% min at 115 VAC	
		Input frequency range	47 to 63 Hz	
		Input AC current	1.5 A at 90 VAC, 0.75 A at 180 VAC PFC Version	
			2.4 A at 90 VAC, 1.2 A at 180 VAC NON PFC Version	
	<b>Output</b>	Output power	90W	
		DC output	19.0V	
		Hold-up time	5 msec at 115 VAC input	
		Output current limit	<11A, Over voltage protection- 29V max automatic shutdown	
	<b>Connector</b>	3 pin/grounded, mates with interchangeable cords		
	<b>Environmental Design</b>	Operating temperature	32° to 104° F (0° to 40° C)	
		Non-operating (storage) temperature	-4° to 149° F (-20° to 65° C)	
		Altitude	0 to 10,000 ft (0 to 3,048 m)	
	Humidity	20% to 80%		
	Storage Humidity	10% to 90%		
<b>EMI and Safety Certifications</b>	CE Mark - full compliance with LVD and EMC directives; Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE; MTBF- over 200,000 hours at 25°C ambient condition.			

<b>HP 65W Smart AC Adapter</b>	<b>Dimensions</b>	4.17 x 1.85 x 1.1 in (10.6 x 4.7 x 2.8 cm)		
	<b>Weight</b>	0.62 lb (280 g)		
	<b>Input</b>	100 to 240 VAC		
		Input Efficiency	87% min at 115 VAC	
		Input frequency range	47 to 63 Hz	
		Input AC current	1.7 A at 90 VAC, 0.85 A at 180 VAC	
	<b>Output</b>	Output power	65W	
		DC output	18.5V	
		Hold-up time	5 msec at 115 VAC input	
		Output current limit	<11A, Over voltage protection- 29V max automatic shutdown	
	<b>Connector</b>	3 pin/grounded, mates with interchangeable cords		
	<b>Environmental Design</b>	Operating temperature	32° to 104° F (0° to 40° C)	
		Non-operating (storage) temperature	-4° to 149° F (-20° to 65° C)	
		Altitude	0 to 10,000 ft (0 to 3,048 m)	
		Humidity	20% to 80%	
	Storage Humidity	10% to 90%		



## Technical Specifications

### EMI and Safety Certifications

CE Mark - full compliance with LVD and EMC directives; Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE; MTBF - over 200,000 hours at 25°C ambient condition.

### 9-Cell (93 WHr) Lithium-Ion battery

<b>Dimensions (H x W x L)</b>	0.8 x 2.9 x 8.3 in (2.0 x 7.3 x 21.0 cm)	
<b>Weight</b>	1.07 lb (0.488 kg)	
<b>Cells/Type</b>	9-cell Lithium-Ion	
<b>Energy</b>	Watt-hour Capacity	93 WHr
<b>Temperature</b>	Operating (Charging)	32° to 113° F (0° to 45° C)
	Operating (Discharging)	14° to 140° F (-10° to 60° C)
	Non-operating	-4° to 140° F (-20° to 60° C)
<b>Battery Re-Charge Time</b>	System in OFF mode or Standby	3 to 4 hours
	System ON	4 to 6 hours (depending on system power consumption)

### 8-Cell (73 Whr) Lithium-Ion Primary battery

<b>Dimensions (HxWxL)</b>	0.8 x 1.9 x 10.6 in (2.0 x 4.8 x 27.0 cm)	
<b>Weight</b>	0.980 lb (0.445 kg)	
<b>Cells/Type</b>	8-cell Lithium-Ion	
<b>Energy</b>	Watt-hour Capacity	73 Wh
<b>Temperature</b>	Operating (Charging)	32° to 113° F (0° to 45° C)
	Operating (Discharging)	14° to 140° F (-10° to 60° C)
	Non-operating	-4° to 140° F (-20° to 60° C)
<b>Battery Re-Charge Time</b>	System in OFF mode or Standby	2.5 hours
	System ON	3 to 5 hours (depending on system power consumption)
	HP Fast Charge Technology	Charges the battery up to 90% within 1.5 hours when system is OFF

### 6-Cell (62 WHr) Lithium-on battery

<b>Dimensions (HxWxL)</b>	0.8 x 2.0 x 8.3 in (2.0 x 5.1 x 21.1 cm)	
<b>Weight</b>	0.72 lb (0.325 kg)	
<b>Cells/Type</b>	6-cell Lithium-Ion	
<b>Energy</b>	Watt-hour Capacity	62Wh
<b>Temperature</b>	Operating (Charging)	32° to 113° F (0° to 45° C)
	Operating (Discharging)	14° to 140° F (-10° to 60° C)
	Non-operating	-4° to 140° F (-20° to 60° C)
<b>Battery Re-Charge Time</b>	System in OFF Mode or Standby	2.5 hours
	System ON	3 to 5 hours (depending on system power consumption)

## Internal Storage



# QuickSpecs

## Technical Specifications

<b>750 GB 7200 rpm SATA Hard Drive</b>	<b>Drive Weight</b>	0.25 lbs (115g)		
	<b>Capacity</b>	750 GB		
	<b>Height</b>	0.37 in (9.5 mm)		
	<b>Width</b>	2.75 in (70 mm)		
	<b>Interface</b>	ATA-8, SATA 2.6, 3.0 Gb/s, NCQ		
	<b>Transfer Rate</b>	<b>Synchronous</b> (maximum)	300 MB/s (Drive Capability)	
	<b>Seek Time</b> (typical reads, including settling)	<b>Single Track</b>	1.5 ms	
		<b>Average</b>	11 ms	
		<b>Maximum</b>	22 ms	
	<b>Rotational Speed</b>	7200 rpm		
	<b>Logical Blocks</b>	1,465,149,168		
	<b>Operating Temperature</b>	32° to 140° F (0° to 60° C) [case temp]		
	<b>Features</b>	ATA Security		

<b>500 GB 7200 rpm SATA Hard Drive</b>	<b>Drive Weight</b>	0.25 lbs (115g)		
	<b>Capacity</b>	500 GB		
	<b>Height</b>	0.37 in (9.5 mm)		
	<b>Width</b>	2.75 in (70 mm)		
	<b>Interface</b>	ATA-8, SATA 2.6, 3.0 Gb/s, NCQ		
	<b>Transfer Rate</b>	<b>Synchronous</b> (maximum)	300 MB/s (Drive Capability)	
	<b>Seek Time</b> (typical reads, including settling)	<b>Single Track</b>	1.5 ms	
		<b>Average</b>	11 ms	
		<b>Maximum</b>	22 ms	
	<b>Rotational Speed</b>	7200 rpm		
	<b>Logical Blocks</b>	976,773,168		
	<b>Operating Temperature</b>	32° to 140° F (0° to 60° C) [case temp]		
	<b>Features</b>	ATA Security		

<b>320 GB 7200 rpm SATA Hard Drive</b>	<b>Drive Weight</b>	0.25 lbs (115 g)		
	<b>Capacity</b>	320 GB		
	<b>Height</b>	0.37 in (9.5 mm)		
	<b>Width</b>	2.75 in (70 mm)		
	<b>Interface</b>	ATA-8, SATA 2.6, 3.0 Gb/s, NCQ		
	<b>Transfer Rate</b>	<b>Synchronous</b> (maximum)	300 MB/s (Drive Capability)	
	<b>Seek Time</b> (typical reads, including settling)	<b>Single Track</b>	1.5 ms	
		<b>Average</b>	11 ms	
		<b>Maximum</b>	22 ms	
	<b>Rotational Speed</b>	7200 rpm		
	<b>Logical Blocks</b>	625,142,448		
	<b>Operating Temperature</b>	32° to 140° F (0° to 60° C) [case temp]		
	<b>Features</b>	ATA Security		



# QuickSpecs

## Technical Specifications

<b>250 GB 7200 rpm SATA Hard Drive</b>	<b>Drive Weight</b>	0.25 lbs (115g)		
	<b>Capacity</b>	250 GB		
	<b>Height</b>	0.37 in (9.5 mm)		
	<b>Width</b>	2.75 in (70 mm)		
	<b>Interface</b>	ATA-8, SATA 2.6, 3.0 Gb/s, NCQ		
	<b>Transfer Rate</b>	<b>Synchronous</b> (maximum)	300 MB/s (Drive Capability)	
	<b>Seek Time</b> (typical reads, including settling)	<b>Single Track</b>	1.5 ms	
		<b>Average</b>	11 ms	
		<b>Maximum</b>	22 ms	
	<b>Rotational Speed</b>	7200 rpm		
	<b>Logical Blocks</b>	488,397,168		
	<b>Operating Temperature</b>	32° to 140° F (0° to 60° C) [case temp]		
	<b>Features</b>	ATA Security		

<b>750 GB 5400 rpm SATA Hard Drive</b>	<b>Drive Weight</b>	0.27 lb (125 g) or 0.22 lb (101 g)		
	<b>Capacity</b>	750 GB		
	<b>Height</b>	0.50 in (12.7 mm) or 0.37 in (9.5 mm)		
	<b>Width</b>	2.75 in (70 mm)		
	<b>Interface</b>	ATA-8, SATA 2.6, 3.0 Gb/s, NCQ		
	<b>Transfer Rate</b>	<b>Synchronous</b> (maximum)	300 MB/s (Drive Capability)	
	<b>Seek Time</b> (typical reads, including settling)	<b>Single Track</b>	3 ms	
		<b>Average</b>	13 ms	
		<b>Maximum</b>	24 ms	
	<b>Rotational Speed</b>	5400 rpm		
	<b>Logical Blocks</b>	1,465,149,168		
	<b>Operating Temperature</b>	32° to 140° F (0° to 60° C) [case temp]		
	<b>Features</b>	ATA Security		

<b>640 GB 5400 rpm SATA Hard Drive</b>	<b>Drive Weight</b>	0.22 lb (101 g)		
	<b>Capacity</b>	640 GB		
	<b>Height</b>	0.37 in (9.5 mm)		
	<b>Width</b>	2.75 in (70 mm)		
	<b>Interface</b>	ATA-8, SATA 2.6, 3.0 Gb/s, NCQ		
	<b>Transfer Rate</b>	<b>Synchronous</b> (maximum)	300 MB/s (Drive Capability)	
	<b>Seek Time</b> (typical reads, including settling)	<b>Single Track</b>	3 ms	
		<b>Average</b>	13 ms	
		<b>Maximum</b>	24 ms	
	<b>Rotational Speed</b>	5400 rpm		
	<b>Logical Blocks</b>	1,250,263,728		
	<b>Operating Temperature</b>	32° to 140° F (0° to 60° C) [case temp]		
	<b>Features</b>	ATA Security		

# QuickSpecs

## Technical Specifications

<b>500 GB 5400 rpm SATA Hard Drive</b>	<b>Drive Weight</b>	0.22 lb (101 g)
	<b>Capacity</b>	500 GB
	<b>Height</b>	0.37 in (9.5 mm)
	<b>Width</b>	2.75 in (70 mm)
	<b>Interface</b>	ATA-8, SATA 2.6, 3.0 Gb/s, NCQ
	<b>Transfer Rate</b>	<b>Synchronous</b> 300 MB/s (Drive Capability) (maximum)
	<b>Seek Time</b>	<b>Single Track</b> 3 ms
(typical reads, including settling)	<b>Average</b>	13 ms
	<b>Maximum</b>	24 ms
	<b>Rotational Speed</b>	5400 rpm
	<b>Logical Blocks</b>	976,773,168
	<b>Operating Temperature</b>	32° to 140° F (0° to 60° C) [case temp]
	<b>Features</b>	ATA Security

<b>250 GB 5400 rpm SATA Hard Drive</b>	<b>Drive Weight</b>	0.22 lb (101 g)
	<b>Capacity</b>	250 GB
	<b>Height</b>	0.37 in (9.5 mm)
	<b>Width</b>	2.75 in (70 mm)
	<b>Interface</b>	ATA-8, SATA 2.6, 3.0 Gb/s, NCQ
	<b>Transfer Rate</b>	<b>Synchronous</b> 300 MB/s (Drive Capability) (maximum)
	<b>Seek Time</b>	<b>Single Track</b> 3 ms
(typical reads, including settling)	<b>Average</b>	13 ms
	<b>Maximum</b>	24 ms
	<b>Rotational Speed</b>	5400 rpm
	<b>Logical Blocks</b>	488,397,168
	<b>Operating Temperature</b>	32° to 140° F (0° to 60° C) [case temp]
	<b>Features</b>	ATA Security

## Optical Drives

# QuickSpecs

## Technical Specifications

<b>DVD-ROM Drive</b>	<b>Access Times</b>	Random	< 140 ms CD (typical) < 160 ms DVD (typical)
	<b>Max Data Transfer Rate</b>	24X CD-ROM 8X-DVD	
	<b>Transfer Mode</b>	UDMA Mode 5	
	<b>Interface</b>	Gen 1 SATA	
	<b>Supported Media (read)</b>	CD-DA, CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD+R, DVD+RW, DVD-RAM	
	<b>Supported Media (write)</b>	None	
	<b>Max Media Capacity (read)</b>	8.5GB	
	<b>Transport</b>	Tray Loading	

<b>DVD+/-RW SuperMulti DL Drive</b>	<b>Access Times</b>	Random	<140ms CD (typical) < 160 ms DVD (typical)
	<b>Max Data Transfer Rate</b>	24X CD-ROM 8X DVD 24X CD-R 24X CD-RW 8X DVD+R 8X DVD+RW 8X DVD-R 6X DVD-RW 6X - DVD+R Dual Layer 6X - DVD-R Dual Layer 5X DVD-RAM	
	<b>Transfer Mode</b>	UDMA Mode 5	
	<b>Interface</b>	Gen 1 SATA	
	<b>Supported Media (read)</b>	CD-DA, CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD+R, DVD+RW, DVD-RAM	
	<b>Supported Media (write)</b>	CD-R, CD-RW, DVD+R, DVD+RW, DVD-R, DVD-RW, DVD-RAM, DVD+R DL, DVD-R DL	
	<b>Max Media Capacity (read)</b>	8.5 GB	
	<b>Max Media Capacity (write)</b>	8.5 GB	
	<b>Transport</b>	Tray Loading	



## Technical Specifications

<b>Blu-ray ROM DVD+/-RW Access Times</b>	Random	<190 ms CD-ROM (typical)
<b>SuperMulti DL Drive</b>		< 180ms DVD-ROM (typical)
		<230 ms BD-ROM (typical)
<b>Max Data Transfer Rate</b>	24X CD-ROM	
	8X DVD-ROM	
	24X CD-R	
	16X CD-RW	
	8X DVD+R	
	8X DVD+RW	
	8X DVD-R	
	6X DVD-RW	
	4X - DVD+R Dual Layer	
	4X - DVD-R Dual Layer	
	5X DVD-RAM	
	6X BD-ROM	
<b>Transfer Mode</b>	UDMA Mode 5	
<b>Interface</b>	Gen 1 SATA	
<b>Supported Media (read)</b>	CD-DA, , CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD+R, DVD+RW. DVD-RAM, BD-ROM, BD-R, BD-RE	
<b>Supported Media (write)</b>	CD-R, CD-RW, DVD+R, DVD+R DL, DVD+RW, DVD-R, DVD-R DL, DVD-RW, DVD-RAM	
<b>Max Media Capacity (read)</b>	50.0 GB	
<b>Max Media Capacity (write)</b>	8.5GB	
<b>Transport</b>	Tray Loading	

---

<b>Blu-ray R/RE DVD+/-RW SuperMulti DL Drive</b>	<b>Access Times</b>	Random	<165 ms CD-ROM (typical)
			<185 ms DVD-ROM (typical)
			<205 ms BD-ROM (typical)
	<b>Max Data Transfer Rate</b>	24X CD-ROM	
		8X DVD-ROM	
		24X CD-R	
		16X CD-RW	
		8X DVD+R	
		8X DVD+RW	
		8X DVD-R	
		6X DVD-RW	
		6X DVD+R Dual Layer	
		6X DVD-R Dual Layer	
		5X DVD-RAM	
		6X BD-ROM	
		6X BD-R	
		2X BD-RE	
	<b>Transfer Mode</b>	UDMA Mode 5	



# QuickSpecs

## Technical Specifications

<b>Interface</b>	Gen 1 SATA
<b>Supported Media (read)</b>	CD-DA, , CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD+R, DVD+RW. DVD-RAM, BD-ROM, BD-R, BD-RE
<b>Supported Media (write)</b>	CD-R, CD-RW, DVD+R, DVD+R DL, DVD+RW, DVD-R, DVD-R DL, DVD-RW, DVD-RAM, BD-R, BD-RE
<b>Max Media Capacity (read)</b>	50.0 GB
<b>Max Media Capacity (write)</b>	50.0 GB
<b>Transport</b>	Tray Loading

## Security

<b>HP Fingerprint Sensor (optional)</b>	<b>Mobile Voltage Operation</b>	3.0V-3.6V Single Supply
	<b>Operating Temperature</b>	32° – 158°F (0° – 70°C)
	<b>Current Consumption @ 3.3V</b>	Less than 70 mA peak imaging and scrolling Less than 25 mA hardware finger detection Advanced Power Management
	<b>High-Rate Image Capture</b>	Up to 240 image frames /sec
	<b>ESD Resistance</b>	IEC 61000-4-2 Level 4 (±15KV)
	<b>Detection Matrix</b>	192 x 16 Pixels 9.7 mm x 0.81 mm 500 ppi High-Resolution Images

## Communications

<b>Integrated Realtek RTL8153EH-CG 10/100/1000 NIC</b>	<b>Ethernet Features</b>	10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 802.3 clauses 40) Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s IEEE 802.1p QoS (Quality of Service) Support IEEE 802.1q VLAN support IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable) IEEE 802.3az EEE (Energy Efficient Ethernet) Jumbo Frame 9K Auto MDI/MDIX Crossover cable detection
	<b>Power Management</b>	ACPI compliant - multiple power modes Situation-sensitive features reduce power consumption Advanced link down power saving for reducing link down power consumption



## Technical Specifications

<b>Performance Features</b>	TCP/IP/UDP Checksum Offload (configurable) Protocol Offload (ARP & NS) Large send offload and Giant send offload Receiving Side Scaling
<b>Manageability</b>	Wake-on-LAN from standby and hibernation (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only) PXE 2.1 Remote Boot Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30)) Comprehensive diagnostic and configuration software suite Virtual Cable Doctor for Ethernet cable status
<b>Interface NIC Device Driver Name</b>	PCI Express 1.1 x1 to fully support ASPM L0s/L1 and CLKREQ Realtek PCIe GBE Ethernet Family Controller

### V.92 56K Data/Fax Modem

<b>Form Factor</b>	MDC 1.5 Daughtercard
<b>Power Management Support</b>	APM Revision 1.2, ACPI
<b>Approvals/Certifications</b>	UL, CSA, NEMKO, CCIB, Industry Canada, FCC Part 68, CTR21, FCC Part 15 Class B, Canadian ICES-003 Class B, C.I.S.P.R.22, Australian ACA, CE Mark, Other Countries
<b>Data Mode Capabilities</b>	V.92 data V.8bis V.80 V44, V.42bis, MNP5 (Compression) V.42 (LAPM, MNP2-4) (Error Correction) <b>Optional symbol rates:</b> 2800, 3429 Asymmetric Symbol rates <b>Synchronous primary channel data signaling rates:</b> 3600, 31200 Automatic rate re-negotiation V.34 V.32bis V.32 V.23 V.22bis V.22 V.21 Bell 212A Bell 103J
<b>Fax Mode Capabilities</b>	TIA/EIA-578-B (Class 1) T.30, T.4 (Group 3) V.17 V.29 V.27ter V.21 Channel 2 T.31
<b>Command Set</b>	V.250 (Partial) TIA-602 Identification: +GMI, +GMM, +GMR Port control: +IPR, +ICF, +IFC, +ILRR Modulation: +MS, +MR, +MA Error control: +ES, +ER, +EB, +ESR, +ETBM

## Technical Specifications

Data compression: +DS, +DR  
V.251

<b>HP un2430 EV-DO/HSPA Mobile Broadband Module</b>	<b>Technology/Operating Bands</b>	GSM/GPRS/EDGE: 850MHz(Cell), 900MHz(EGSM), 1800MHz(DCS), 1900MHz (PCS) UMTS/WCDMA with receive diversity: 2100MHz (UTRA FDD Band I), 1900MHz (UTRA FDD Band II), AWS (UTRA FDD Band IV), 900MHz(UTRA FDD Band VIII), 850MHz (UTRA FDD Band V) 1xEVDO/1xRTT with receive diversity: 850MHz (Band Class0-Cell), 1900MHz (Band Class1-PCS)
	<b>Wireless Protocol Standards</b>	GSM/GPRS/EDGE: Class A, Multi-slot class 10 operation, coding schemes CS1 - CS4 and MSC1 - MSC9. UMTS/WCDMA: Release 99 and Release 6 CDMA: 1xEVDO Release 0 and Release A, IS-95A, IS-95B, IS-856, IS-2000
	<b>Wireless Parametric Standards</b>	Meets or exceeds TIA/EIA IS-98-D
	<b>Maximum Data Rates</b>	UMTS (HSPA) - 14.4 Mbps (Download ), 5.76Mbps (Upload) CDMA (EVDO Release A) - 3.1 Mbps (Download), 1.8Mbps (Upload)
	<b>GPS</b>	Standalone GPS enabled gpsOneXTRATM™
	<b>GPS Bands</b>	L1 - 1575.42 MHz
	<b>Maximum Output Power</b>	GSM/GPRS/EDGE: 32dBm (+/-1) WCDMA: 24dBm (+0.7/-2.3) CDMA: 24dBm (+0.7/-2)
	<b>Maximum Power Consumption</b>	2750mA (peak); 1100mA (average)
	<b>Power Consumption, Idle Not Connected</b>	20 mA
	<b>Power Management</b>	USB selective suspend Integrated notebook wireless button
	<b>Antenna Type</b>	Dual high efficiency 5 band antennae with spatial diversity, mounted in the display enclosure
	<b>Form Factor</b>	PCI-Express MiniCard, USB 2.0 interface
	<b>Weight</b>	11.5 g
	<b>Dimensions (Length x Width x Thickness)</b>	2.01 x 1.18 x 0.18 in (51 x 30 x 5 mm)
	<b>Voltage, Operating</b>	3.3v +/- 10%
	<b>Temperature, Operating (from TIA/EIA/IS-98-D)</b>	-22° to 158° F (-30° to 70° C) (full RF performance) -22° to 167° F (-30° to 75° C) (reduced RF performance)
	<b>Temperature, Non-operating, 96 hours (from MIL-STD 202 Method 108)</b>	-40° to 185° F (-40° to 85° C)
	<b>Humidity, Non-operating</b>	95% relative humidity for 48 hours @ 185° F (85° C) (non-condensing)
	<b>Configuration Utilities</b>	HP Connection Manager
	<b>LED Activity</b>	LED Off - Radio Off; Solid LED On - Radio On

## Technical Specifications

<b>HP Ic2010 Mobile Broadband Module</b>	<b>Technology/Operating Bands</b>	GSM/GPRS/EDGE: 850MHz(Cell), 900MHz(EGSM), 1800MHz(DCS), 1900MHz (PCS) UMTS/WCDMA with receive diversity: 2100MHz (UTRA FDD Band I), 900MHz(UTRA FDD Band VIII)
	<b>Wireless Protocol Standards</b>	GSM/GPRS/EDGE: Class B, Multi-slot class 10 operation, coding schemes CS1 - CS4 and MSC1 - MSC9. UMTS/WCDMA: Release 99 and Release 6
	<b>Wireless Parametric Standards</b>	Complies with 3GPP specifications
	<b>Maximum Data Rates</b>	UMTS (HSPA) - 7.2 Mbps (Download ), 2.0Mbps (Upload)
	<b>GPS</b>	n/a
	<b>GPS Bands</b>	
	<b>Maximum Output Power</b>	GSM/GPRS/EDGE: 32dBm (+/-1) WCDMA: 23dBm (+/-1)
	<b>Maximum Power Consumption</b>	2000mA (peak); 600mA (average)
	<b>Power Consumption, Sleep Mode</b>	5 mA
	<b>Power Management</b>	USB selective suspend Integrated notebook wireless button
	<b>Antenna Type</b>	Dual high efficiency 5 band antennae with spatial diversity, mounted in the display enclosure
	<b>Form Factor</b>	PCI-Express MiniCard, USB 2.0 interface
	<b>Weight</b>	< 10 g
	<b>Dimensions</b> (Length x Width x Thickness)	2.01 x 1.18 x 0.18 in (51 x 30 x 5 mm)
	<b>Voltage, Operating</b>	3.3v +/- 10%
	<b>Temperature, Operating</b>	14° to 149° F (-10° to 65° C) (full RF performance) 14° to 167° F (-10° to 75° C) (reduced RF performance)
	<b>Temperature, Non-operating, 96 hours</b> (from MIL-STD 202 Method 108)	-22° to 185° F (-30° to 85° C)
	<b>Humidity, Non-operating</b>	85% relative humidity for 48 hours @ 185° F (85° C) (non-condensing)
	<b>Configuration Utilities</b>	HP Connection Manager
	<b>LED Activity</b>	LED Off - Radio Off; Solid LED On - Radio On

<b>Intel Centrino Advanced-N 6230 WiFi and Bluetooth Combo Adapter</b>	<b>Wireless LAN Standards</b>	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n
	<b>Interoperability</b>	Wi-Fi certified Cisco Compatible Extensions Program compliant with Microsoft Windows Vista and XP (details at: <a href="http://www.hp.com/go/notebooks/WLAN">http://www.hp.com/go/notebooks/WLAN</a> )
	<b>Frequency Band</b>	2.4 GHz and 5GHz
	<b>Data Rates</b>	802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: 66 possible data rates, ranging from 6 Mbps to 300 Mbps,

## Technical Specifications

	depending on the combination of Bandwidth, Modulation Coding Scheme, and Guard Interval used, as defined in IEEE 802.11n specification
<b>Modulation</b>	Direct Sequence Spread Spectrum DBPSK, DQPSK, CCK, OFDM, BPSK, QPSK, 16-QAM, 64-QAM
<b>Security<sup>1</sup></b>	Supports 64- and 128-bit WEP, WPA, WPA2, hardware-accelerated AES, 802.1x authentication types EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, LEAP, EAP-FAST.  Support for Cisco Security Features (proven compatibility with Cisco Aironet infrastructure products through the Cisco Compatible Extensions Program Version 4) with Microsoft Windows Vista and XP only.
<b>Sub-channels</b>	Multinational support with frequency bands and channels compliant to local regulations.
<b>Media Access Protocol</b>	CSMA/CA (Collision Avoidance) with ACK
<b>Network Architecture Models</b>	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
<b>Roaming</b>	IEEE 802.11 compliant roaming between access points
<b>Output Power</b> (for CCK and OFDM) <sup>2</sup>	17 dBm , nominal
<b>Output Power</b> (for OFDM; power varies by data rate) <sup>2</sup>	15 dBm , nominal
<b>Power Consumption</b>	Idle associated: 250 mW Idle unassociated: 150 mW Transmit: 2.0 W (max) Receive: 2.0 W (max)
<b>Power Management</b>	ACPI compliant power management 802.11 compliant power saving mode
<b>Receiver Sensitivity<sup>3</sup></b>	54 Mbps: -71 dBm, 11 Mbps: -85 dBm , 1 Mbps: -95 dBm
<b>Antenna type</b>	High efficiency dual band antenna with spatial diversity, mounted in the display enclosure
<b>Form Factor</b>	PCI-Express Half-MiniCard
<b>Weight</b>	0.013 lb (6 g)
<b>Dimensions</b>	0.19 x 1.06 x 1.18 in (4.75 x 26.8 x 30 mm)
<b>Operating Voltage</b>	3.3v +/- 10%
<b>Temperature</b>	Operating 14° to 149° F (-10° to 65° C) Non-operating -40° to 176° F (-40° to 80° C)
<b>Humidity</b>	Operating 10% to 90% (non-condensing) Non-operating 5% to 95% (non-condensing)
<b>Altitude</b>	Operating 0 to 10,000 ft (3,048 m) Non-operating 0 to 50,000 ft (15,240 m)
<b>Configuration Utility<sup>4</sup></b>	Microsoft Windows XP Choice of Configuration Utility: <ul style="list-style-type: none"> <li>● Microsoft Windows XP Wireless Network Connection Manager</li> <li>● Broadcom Wireless Configuration Utility (required for Cisco Compatible Extensions support)</li> </ul> Microsoft Windows Vista <ul style="list-style-type: none"> <li>● Microsoft Windows Vista Wireless Network Connection Manager</li> <li>● Broadcom IHV extensions for Windows Vista available to support</li> </ul>

# QuickSpecs

## Technical Specifications

Cisco Compatible Extensions.

- LED Activity** LED Off - Radio OFF; Solid LED On - Radio ON
1. Check latest software/driver release for updates on supported security features.
  2. Maximum output power may vary by country according to local regulations.
  3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CCK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).
  4. WLAN supplier's client utility is required for Cisco Compatible Extensions support with Microsoft Windows XP. WLAN may also be compatible with certain third-party software supplicants. WLAN supplier IHV extensions required for Cisco Compatible Extensions support for Microsoft Windows Vista.

### Bluetooth 2.1 and 3.0 Wireless Technology

<b>Bluetooth Specification</b>	2.1+EDR and 3.0+HS Compliant
<b>Dimensions</b>	1.18 x 0.26 x 0.13 in (30 x 6.5 x 3.25 mm)
<b>Frequency Band</b>	2402 to 2480 MHz
<b>Number of Available Channels</b>	79 (1 MHz) available channels
<b>Data Rates and Throughput</b>	3 Mbps data rate; throughput up to 2.17 Mbps Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric or 1306.9 kbps symmetric
<b>Transmit Power</b>	Max 5.5 dBm (Bluetooth Class I)
<b>Receiver Sensitivity</b>	Better than -80 dBm at 0.1 % raw bit error rate
<b>Power Consumption</b>	Average 165mW Sleep <1 mW
<b>Antenna</b>	Internally integrated within module
<b>Range</b>	Up 33 ft (10 m)
<b>Electrical Interface</b>	USB 2.0 compliant Microsoft Windows Plug and Play compliant
<b>Bluetooth Software Supported</b>	Broadcom Bluetooth for Windows Microsoft Windows Bluetooth Software
<b>Link Topology</b>	Point to Point, Multipoint Pico Nets up to 7 slaves
<b>Security</b>	Full support of Bluetooth Security Provisions
<b>Power Management</b>	Microsoft Windows ACPI, and USB Bus Support Self configurable to optimize power conservation in all operating modes, including Standby, Hold, Park, and Sniff
<b>Certifications</b>	All necessary regulatory approvals for supported countries, including: FCC (47 CFR) Part 15C, Section 15.247 & 15.249 ETS 300 328, ETS 300 826 Low Voltage Directive IEC950 UL, CSA, and CE Mark
<b>Temperature</b>	Operating -4° to 158° F (-20° to 70° C) Non-operating -40° to 176° F (-40° to 80° C)
<b>Humidity</b>	Operating 10% to 90% Non-operating 5% to 95%
<b>Altitude</b>	Operating 15,000 ft (4,572 m) Non-operating 40,000 ft (12,192 m)
<b>Bluetooth Profiles Supported</b>	Serial Port Profile (SPP) <sup>1</sup> Service Discovery Application Profile (SDAP) Dial-Up Networking (DUN) <sup>1,2</sup>



# QuickSpecs

## Technical Specifications

- Generic Object Exchange Profile (GOEP)<sup>1,2</sup>
- Object Push Profile (OPP)<sup>1,2</sup>
- File Transfer Profile (FTP)
- Synchronization Profile (SYNC)
- Hard Copy Cable Replacement (HCRP)<sup>1,2</sup>
- Personal Area Networking Profile (PAN)<sup>1,2</sup>
- Human Interface Device Profile (HID)<sup>1,2,3</sup>
- FAX Profile (FAX)
- Basic Imaging Profile (BIP)<sup>2</sup>
- Headset Profile (HSP)
- Hands Free Profile (HFP)
- Advanced Audio Distribution Profile (A2DP)

1. indicates the profile is supported by Microsoft Windows XP SP2
2. indicates the profile is part of Windows Vista

<b>Atheros 9285GN 802.11b/g/n + BT 3.0 HS Combo Adapter</b>	<b>Wireless LAN Standards</b>	IEEE 802.11b IEEE 802.11g IEEE 802.11n
	<b>Interoperability</b>	Wi-Fi certified
	<b>Frequency Band</b>	2.4 GHz
	<b>Data Rates</b>	802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: many possible data rates, ranging from 6 Mbps to 300 Mbps, depending on the combination of Bandwidth, Modulation Coding Scheme, and Guard Interval used, as defined in IEEE 802.11n specification
	<b>Modulation</b>	Direct Sequence Spread Spectrum DBPSK, DQPSK, CCK, OFDM, BPSK, QPSK, 16-QAM, 64-QAM
	<b>Security<sup>1</sup></b>	Supports 64- and 128-bit WEP, WPA, WPA2, hardware-accelerated AES, 802.1x authentication types EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, LEAP, EAP-FAST.
	<b>Sub-channels</b>	Multinational support with frequency bands and channels compliant to local regulations.
	<b>Media Access Protocol</b>	CSMA/CA (Collision Avoidance) with ACK
	<b>Network Architecture</b>	Ad-hoc (Peer to Peer)
	<b>Models</b>	Infrastructure (Access Point Required)
	<b>Roaming</b>	IEEE 802.11 compliant roaming between access points
	<b>Output Power</b> (for CCK and OFDM) <sup>2</sup>	17 dBm, nominal
	<b>Output Power</b> (for OFDM; power varies by data rate) <sup>2</sup>	15 dBm, nominal
	<b>Power Consumption</b>	Transmit: 1.5 W (max) Receive: 1.0 W (max) Associated to Access Point, Idle: 300 mW nominal Wireless Button Off: 75 mW nominal
	<b>Power Management</b>	ACPI compliant power management 802.11 compliant power saving mode
	<b>Receiver Sensitivity<sup>3</sup></b>	54 Mbps: -75 dBm, 11 Mbps: -88 dBm , 1 Mbps: -93 dBm



# QuickSpecs

## Technical Specifications

<b>Antenna type</b>	High efficiency antenna with spatial diversity, mounted in the display enclosure	
<b>Form Factor</b>	PCI-Express Half-MiniCard	
<b>Weight</b>	0.013 lb (6 g)	
<b>Dimensions</b>	0.19 x 1.06 x 1.18 in (4.75 x 26.8 x 30 mm)	
<b>Operating Voltage</b>	3.3v +/- 9%	
<b>Temperature</b>	Operating	14° to 149° F (-10° to 65° C)
	Non-operating	-40° to 176° F (-40° to 80° C)
<b>Humidity</b>	Operating	10% to 90% (non-condensing)
	Non-operating	5% to 95% (non-condensing)
<b>Altitude</b>	Operating	0 to 10,000 ft (3,048 m)
	Non-operating	0 to 50,000 ft (15,240 m)
<b>LED Activity</b>	LED Off - Radio OFF; Solid LED On - Radio ON	
	<ol style="list-style-type: none"> <li>1. Check latest software/driver release for updates on supported security features.</li> <li>2. Maximum output power may vary by country according to local regulations.</li> <li>3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).</li> </ol>	

<b>Ralink 3592BC8 802.11a/b/g/n 2x2 WiFi and Bluetooth 3.0+HS Combo Adapter</b>	<b>Wireless LAN Standards</b>	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n
	<b>Interoperability</b>	Wi-Fi certified Cisco Compatible Extensions Program compliant with Microsoft Windows Vista and XP (details at: <a href="http://www.hp.com/go/notebooks/WLAN">http://www.hp.com/go/notebooks/WLAN</a> )
	<b>Frequency Band</b>	2.4 GHz and 5GHz
	<b>Data Rates</b>	802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: from 6 Mbps to 300 Mbps, depending on the combination of Bandwidth, Modulation Coding Scheme, and Guard Interval used, as defined in IEEE 802.11n specification
	<b>Modulation</b>	Direct Sequence Spread Spectrum DBPSK, DQPSK, CCK, OFDM, BPSK, QPSK, 16-QAM, 64-QAM
	<b>Security<sup>1</sup></b>	Supports 64- and 128-bit WEP, WPA, WPA2, hardware-accelerated AES, 802.1x authentication types EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, LEAP, EAP-FAST.  Support for Cisco Security Features (proven compatibility with Cisco Aironet infrastructure products through the Cisco Compatible Extensions Program Version 4) with Microsoft Windows Vista and XP only.
	<b>Sub-channels</b>	Multinational support with frequency bands and channels compliant to local regulations.
	<b>Media Access Protocol</b>	CSMA/CA (Collision Avoidance) with ACK
	<b>Network Architecture Models</b>	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
	<b>Roaming</b>	IEEE 802.11 compliant roaming between access points
<b>Output Power (for CCK and OFDM)<sup>2</sup></b>	17 dBm , nominal	

# QuickSpecs

## Technical Specifications

<b>Output Power</b> (for OFDM; power varies by data rate) <sup>2</sup>	15 dBm , nominal
<b>Power Consumption</b>	Idle associated: 250 mW Idle unassociated: 150 mW Transmit: 2.0 W (max) Receive: 2.0 W (max)
<b>Power Management</b>	ACPI compliant power management 802.11 compliant power saving mode
<b>Receiver Sensitivity</b> <sup>3</sup>	54 Mbps: -71 dBm, 11 Mbps: -85 dBm , 1 Mbps: -95 dBm
<b>Antenna type</b>	High efficiency dual band antenna with spatial diversity, mounted in the display enclosure
<b>Form Factor</b>	PCI-Express Half-MiniCard
<b>Weight</b>	0.013 lb (6 g)
<b>Dimensions</b>	0.19 x 1.06 x 1.18 in (4.75 x 26.8 x 30 mm)
<b>Operating Voltage</b>	3.3v +/- 10%
<b>Temperature</b>	Operating 14° to 149° F (-10° to 65° C) Non-operating -40° to 176° F (-40° to 80° C)
<b>Humidity</b>	Operating 10% to 90% (non-condensing) Non-operating 5% to 95% (non-condensing)
<b>Altitude</b>	Operating 0 to 10,000 ft (3,048 m) Non-operating 0 to 50,000 ft (15,240 m)
<b>Configuration Utility</b> <sup>4</sup>	Microsoft Windows XP Choice of Configuration Utility: <ul style="list-style-type: none"> <li>• Microsoft Windows XP Wireless Network Connection Manager</li> <li>• Broadcom Wireless Configuration Utility (required for Cisco Compatible Extensions support)</li> </ul> <p>Microsoft Windows Vista</p> <ul style="list-style-type: none"> <li>• Microsoft Windows Vista Wireless Network Connection Manager</li> <li>• Broadcom IHV extensions for Windows Vista available to support Cisco Compatible Extensions.</li> </ul>
<b>LED Activity</b>	LED Off - Radio OFF; Solid LED On - Radio ON <ol style="list-style-type: none"> <li>1. Check latest software/driver release for updates on supported security features.</li> <li>2. Maximum output power may vary by country according to local regulations.</li> <li>3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CCK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).</li> <li>4. WLAN supplier's client utility is required for Cisco Compatible Extensions support with Microsoft Windows XP. WLAN may also be compatible with certain third-party software supplicants. WLAN supplier IHV extensions required for Cisco Compatible Extensions support for Microsoft Windows Vista.</li> </ol>
<b>Bluetooth 2.1 and 3.0 Wireless Technology</b>	<b>Bluetooth Specification</b> 2.1+EDR and 3.0+HS Compliant
<b>Dimensions</b>	1.18 x 0.26 x 0.13 in (30 x 6.5 x 3.25 mm)
<b>Frequency Band</b>	2402 to 2480 MHz
<b>Number of Available Channels</b>	79 (1 MHz) available channels
<b>Data Rates and Throughput</b>	3 Mbps data rate; throughput up to 2.17 Mbps Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric or 1306.9 kbps symmetric





## Technical Specifications

<b>Transmit Power</b>	-6 dBm to 4 dBm (Bluetooth Class II)
<b>Receiver Sensitivity</b>	Better than -80 dBm at 0.1 % raw bit error rate
<b>Power Consumption</b>	Peak (Tx) 175 mW Peak (Rx) 160 mW Sleep <1 mW
<b>Antenna</b>	Internally integrated within module
<b>Range</b>	Up 33 ft (10 m)
<b>Electrical Interface</b>	USB 2.0 compliant Microsoft Windows Plug and Play compliant
<b>Bluetooth Software Supported</b>	Broadcom Bluetooth for Windows Microsoft Windows Bluetooth Software
<b>Link Topology</b>	Point to Point, Multipoint Pico Nets up to 7 slaves
<b>Security</b>	Full support of Bluetooth Security Provisions
<b>Power Management</b>	Microsoft Windows ACPI, and USB Bus Support Self configurable to optimize power conservation in all operating modes, including Standby, Hold, Park, and Sniff
<b>Certifications</b>	All necessary regulatory approvals for supported countries, including: FCC (47 CFR) Part 15C, Section 15.247 & 15.249 ETS 300 328, ETS 300 826 Low Voltage Directive IEC950 UL, CSA, and CE Mark
<b>Temperature</b>	Operating -4° to 158° F (-20° to 70° C) Non-operating -40° to 176° F (-40° to 80° C)
<b>Humidity</b>	Operating 10% to 90% Non-operating 5% to 95%
<b>Altitude</b>	Operating 15,000 ft (4,572 m) Non-operating 40,000 ft (12,192 m)
<b>Bluetooth Profiles Supported</b>	Serial Port Profile (SPP) <sup>1</sup> Service Discovery Application Profile (SDAP) Dial-Up Networking (DUN) <sup>1,2</sup> Generic Object Exchange Profile (GOEP) <sup>1,2</sup> Object Push Profile (OPP) <sup>1,2</sup> File Transfer Profile (FTP) Synchronization Profile (SYNC) Hard Copy Cable Replacement (HCRP) <sup>1,2</sup> Personal Area Networking Profile (PAN) <sup>1,2</sup> Human Interface Device Profile (HID) <sup>1,2,3</sup> FAX Profile (FAX) Basic Imaging Profile (BIP) <sup>2</sup> Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP)

1. indicates the profile is supported by Microsoft Windows XP SP2

2. indicates the profile is part of Windows Vista

Realtek 8188GN  
802.11b/g/n 1x1 WiFi  
Adapter

Wireless LAN  
Standards

IEEE 802.11b  
IEEE 802.11g  
IEEE 802.11n



# QuickSpecs

## Technical Specifications

<b>Interoperability</b>	Wi-Fi certified
<b>Frequency Band</b>	2.4 GHz
<b>Data Rates</b>	802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: many possible data rates, ranging from 6 Mbps to 150 Mbps, depending on the combination of Bandwidth, Modulation Coding Scheme, and Guard Interval used, as defined in IEEE 802.11n specification
<b>Modulation</b>	Direct Sequence Spread Spectrum DBPSK, DQPSK, CCK, OFDM, BPSK, QPSK, 16-QAM, 64-QAM
<b>Security<sup>1</sup></b>	Supports 64- and 128-bit WEP, WPA, WPA2, hardware-accelerated AES, 802.1x authentication types EAP-TLS, EAP-TTLS, PEAP-GTC, PEAP-MSCHAPv2, LEAP, EAP-FAST.
<b>Sub-channels</b>	Multinational support with frequency bands and channels compliant to local regulations.
<b>Media Access Protocol</b>	CSMA/CA (Collision Avoidance) with ACK
<b>Network Architecture Models</b>	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
<b>Roaming</b>	IEEE 802.11 compliant roaming between access points
<b>Output Power</b> (for CCK) <sup>2</sup>	17 dBm, nominal
<b>Output Power</b> (for OFDM; power varies by data rate) <sup>2</sup>	15 dBm, nominal
<b>Power Consumption</b>	Transmit: 1.5 W (max) Receive: 1.0 W (max) Associated to Access Point, Idle: 152 mW nominal Wireless Button Off: 33 mW nominal
<b>Power Management</b>	ACPI compliant power management 802.11 compliant power saving mode
<b>Receiver Sensitivity<sup>3</sup></b>	54 Mbps: -73 dBm, 11 Mbps: -82 dBm, 1 Mbps: -93 dBm, MCS7_HT20: -69dBm, MCS7_HT40: -67dBm
<b>Antenna type</b>	High efficiency antenna with spatial diversity, mounted in the display enclosure
<b>Form Factor</b>	PCI-Express Half-MiniCard
<b>Weight</b>	0.007 lb (3 g)
<b>Dimensions</b>	0.14 x 1.06 x 1.18 in (3.5 x 26.8 x 30 mm)
<b>Operating Voltage</b>	3.3v +/- 9%
<b>Temperature</b>	Operating 14° to 149° F (-10° to 65° C) Non-operating -40° to 176° F (-40° to 80° C)
<b>Humidity</b>	Operating 10% to 90% (non-condensing) Non-operating 5% to 95% (non-condensing)
<b>Altitude</b>	Operating 0 to 10,000 ft (3,048 m) Non-operating 0 to 50,000 ft (15,240 m)
<b>LED Activity</b>	LED Off - Radio OFF; Solid LED On - Radio ON

1. Check latest software/driver release for updates on supported security features.
2. Maximum output power may vary by country according to local regulations.
3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CCK modulation) and a packet error rate of 10% for 802.11a/g/n (OFDM modulation).

## Technical Specifications

**Environmental Data**      **Eco-Label Certifications**      This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- US ENERGY STAR®
- IT ECO declaration
- EPEAT - Gold where HP registers commercial notebook products. See <http://www.epeat.net> for registration status in your country.

**System Configuration**      The configuration used for the Energy Consumption and Declared Noise Emissions data for the Convertible Mini tower Desktop model is based on a "Typically Configured Notebook"

### HP ProBook 4330s Notebook PC

Energy Consumption	115 VAC	230 VAC	100 VAC
Normal Operation	9.75W	10.19 W	10.32 W
Sleep (Energy Star low power mode)	1.24 W	1.4 W	1.24 W
Off	0.57 W	0.66 W	0.56 W

Heat Dissipation*	115 VAC	230 VAC	100 VAC
Normal Operation	33 BTU/hr	35 BTU/hr	35 BTU/hr
Sleep	4 BTU/hr	5 BTU/hr	4 BTU/hr
Off	2 BTU/hr	2 BTU/hr	2 BTU/hr

\* Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

### Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)

System Fan Off	Sound Power (LWAd, bels)	Sound Pressure (LpAm, decibels)
Idle	3.5	31.6
Fixed Disk (random writes)	3.6	32.9

System fan is usually off except when charging the battery

**Batteries**      This battery(s) in this product comply with EU Directive 2006/66/EC

Batteries used in the product do not contain:

- Mercury greater the 5ppm by weight
- Cadmium greater than 10ppm by weight

The battery type and chemistry used in the product is: CR2032 (coin cell), Li-ion 6-cell high capacity Lithium-Ion battery (optional 8 cell available)

### Additional information

This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2002/95/EC.

This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC.

This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).



## Technical Specifications

This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold level, see [www.epeat.net](http://www.epeat.net)

Plastics parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043.

This product contains 0% post consumer recycled plastic (by wt.)

This product is greater than 93.9% recycle-able when properly disposed of at end of life.

### Packaging Materials

- External:
  - Corrugated Carton 385 g
  - Corrugated 115 g
  - CANON bags - Several layers 5 g
- Internal:
  - Polyethylene low density 15 g
  - Molded Pulp 180 g
- The Corrugated Carton packaging material is made from 80% recycled content.
- The Corrugated packaging material is made from 80% recycled content.
- The CANON bags - Several layers packaging material is made from 80% recycled content.
- The Polyethylene low density packaging material is made from 60% recycled content.
- The Molded Pulp packaging material is made from 60% recycled content.

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

## Technical Specifications

### HP ProBook 4430s Notebook PC

Energy Consumption	115 VAC	230 VAC	100 VAC
Normal Operation	9.75W	10.19 W	10.32 W
Sleep (Energy Star low power mode)	1.24 W	1.4 W	1.24 W
Off	0.57 W	0.66 W	0.56 W

Heat Dissipation*	115 VAC	230 VAC	100 VAC
Normal Operation	33 BTU/hr	35 BTU/hr	35 BTU/hr
Sleep	4 BTU/hr	5 BTU/hr	4 BTU/hr
Off	2 BTU/hr	2 BTU/hr	2 BTU/hr

\* Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

### Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)

System Fan Off	Sound Power (LWAd, bels)	Sound Pressure (LpAm, decibels)
Idle	3.5	32.2
Fixed Disk (random writes)	3.8	35.4

System fan is usually off except when charging the battery

**Batteries** This battery(s) in this product comply with EU Directive 2006/66/EC

Batteries used in the product do not contain:

- Mercury greater the 5ppm by weight
- Cadmium greater than 10ppm by weight

The battery type and chemistry used in the product is: CR2032 (coin cell), Li-ion 6-cell high capacity Lithium-Ion battery (optional 8 cell available)

### Additional information

This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2002/95/EC.

This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC.

This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).

This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold level, see [www.epeat.net](http://www.epeat.net)

Plastics parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043.

This product contains 0% post consumer recycled plastic (by wt.)

This product is greater than 94.4% recycle-able when properly disposed of at end of life.

## Technical Specifications

### Packaging Materials

- External:
  - Corrugated Carton 385 g
  - Corrugated 115 g
  - CANON bags - Several layers 5 g
- Internal:
  - Polyethylene low density 15 g
  - Molded Pulp 180 g
- The Corrugated Carton packaging material is made from 80% recycled content.
- The Corrugated packaging material is made from 80% recycled content.
- The CANON bags - Several layers packaging material is made from 80% recycled content.
- The Polyethylene low density packaging material is made from 60% recycled content.
- The Molded Pulp packaging material is made from 60% recycled content.

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

### HP ProBook 4530s Notebook PC

Energy Consumption	115 VAC	230 VAC	100 VAC
Normal Operation	9.29 W	10.44 W	9.23 W
Sleep (Energy Star low power mode)	1.18 W	1.08 W	1.16 W
Off	0.51 W	0.64 W	0.51 W
Heat Dissipation*	115 VAC	230 VAC	100 VAC
Normal Operation	31.7 BTU/hr	35.7 BTU/hr	31.5 BTU/hr
Sleep	4.03 BTU/hr	4 BTU/hr	4 BTU/hr
Off	2 BTU/hr	2.1 BTU/hr	2 BTU/hr

\* Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

**Declared Noise Emissions  
(in accordance with ISO 7779 and ISO 9296)**

## Technical Specifications

System Fan Off	Sound Power (LWAd, bels)	Sound Pressure (LpAm, decibels)
Idle	3.5	32.1
Fixed Disk (random writes)	4.1	37.8

System fan is usually off except when charging the battery

### Batteries

This battery(s) in this product comply with EU Directive 2006/66/EC

Batteries used in the product do not contain:

- Mercury greater the 5ppm by weight
- Cadmium greater than 10ppm by weight

The battery type and chemistry used in the product is:

CR2032 (coin cell), Li-ion

6-cell high capacity Lithium-Ion battery (optional 8 cell available)

### Additional information

This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2002/95/EC.

This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC.

This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).

This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold level, see [www.epeat.net](http://www.epeat.net)

Plastics parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043.

This product contains 0% post consumer recycled plastic (by wt.)

This product is greater than 95.1% recycle-able when properly disposed of at end of life.

### Packaging Materials

- External:
  - Corrugated 115 g
  - Corrugated Carton 455 g
  - Canon bag 5 g
- Internal:
  - Polyethylene low density 15g
  - Molded pulp 190g
- The Corrugated carton packaging material is made from 80% recycled content.
- The Corrugated packaging material is made from 80% recycled content.
- The Canon Bag packaging material is made from 80% recycled content.
- The Polyethylene low density packaging material is made from 60% recycled content.
- The Molded Pulp packaging material is made from 60% recycled content.

HP follows these guidelines to decrease the environmental impact of

## Technical Specifications

product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

### Material Usage

This product does not contain any of the following substances in excess of regulatory limits (for reference of these limits please refer to the HP General Specification of the Environment:

([http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen\\_specifications.html](http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html)):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants - may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) - except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

Nickel finishes that release greater than 0.5 µgrams/cm<sup>2</sup>/week, measured according to EN 1811:1998, are not used on any product surface designed to be frequently handled or touched by users.

### End-of-life Management and Recycling

Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <http://www.hp.com/go/reuse-recycle> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <http://www.hp.com/go/recyclers>.



## Technical Specifications

**Hewlett-Packard  
Corporate  
Environmental  
Information**

These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

For more information about HP's commitment to the environment:  
Global Citizenship Report

<http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html>

Environment website

<http://www.hp.com/environment>

Eco-label certifications

<http://www.hp.com/hpinfo/globalcitizenship/environment/productdesign/ecolabels.html>

ISO 14001 certificates:

<http://www.hp.com/hpinfo/globalcitizenship/environment/operations/envmanagement.html>

---

Copyright © 2011 Hewlett-Packard Development Company, L.P.

All rights reserved. Microsoft, Windows, Windows 7, Windows Vista and Windows XP are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. Intel, Core, and Celeron are registered trademarks or trademarks of Intel Corporation in the U.S. and/or other countries. Bluetooth is a registered trademark of Bluetooth SIG, Inc., in the U.S. and other countries. All other product names mentioned herein may be trademarks of their respective companies.

The information contained herein is subject to change without notice and is provided "as is" without warranty of any kind. The warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

## Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>