


HP recommends
Windows Vista® Business

Microtower



- | | |
|--|---|
| 1. (2) external 5.25" drive bays for optional optical drives | 6. (1) full-height PCI 2.3 slot, (2) PCIe x1 slots, (1) PCIe x16 slot |
| 2. (1) external 3.5" drive bay for optional media reader or diskette drive | 7. (2) internal 3.5" drive bays |
| 3. (2) USB 2.0 ports, audio ports | 8. PS/2 Scroll Mouse |
| 4. 250-watt max power supply | 9. HP Standard Keyboard |
| 5. (4) USB 2.0 ports, (2) PS/2, (1) RJ-45, (1) VGA, (1) audio in – (1) audio out – (1) MIC | 10. Monitor (sold separately) |

Overview

At A Glance

- Intel® Core™ 2 processors, Intel Pentium® processors, or Intel Celeron® processors
- Choice of operating systems:
 - Genuine Windows Vista Business 32
 - Genuine Windows Vista Home Premium
 - Genuine Windows Vista Home Basic 32
 - Redflag Linux (China Only)
 - FreeDOS
- Intel G31 Express Chipset
- Intel I/O Controller Hub 7 (ICH7)
- Intel Graphics Media Accelerator
- PCI and PCI Express I/O buses
- Serial ATA controller
- USB 2.0 support
- Realtek RTL8101E 10/100 Fast Ethernet controller
- Choice of hard drives and optical drives
- DDR2 SDRAM system memory
- Protected by HP Services. Terms and conditions vary by country. Certain restrictions and exclusions apply.

* RAID mode not supported

Standard Features and Configurable Components

Processor and Speed

One of the following

Intel Celeron Processors

Intel Celeron 420 Processor (1.60-GHz, 512-KB L2 cache, 800-MHz FSB)

Intel Celeron 430 Processor (1.80-GHz, 512-KB L2 cache, 800-MHz FSB)

Intel Celeron 440 Processor (2.00-GHz, 512-KB L2 cache, 800-MHz FSB)

Intel Celeron 450 Processor (2.2-GHz, 512K L2 cache, 800-MHz FSB)

Intel Celeron Dual-Core Processors

Intel Celeron Dual Core E1200 Processor (1.60-GHz, 512-KB L2 cache, 800-MHz FSB)

Intel Celeron Dual Core E1500 Processor (2.2-GHz, 512K L2 cache, 800-MHz FSB)

Intel Pentium Dual-Core Processors

Intel Pentium Dual-Core E2140 Processor (1.60-GHz, 1-MB L2 cache, 800-MHz FSB)

Intel Pentium Dual-Core E2160 Processor (1.80-GHz, 1-MB L2 cache, 800-MHz FSB)

Intel Pentium Dual-Core E2200 Processor (2.2-GHz, 1-MB L2 cache, 800-MHz FSB)

Intel Pentium Dual Core E5200 processor (2.50 GHz, 2 MB L2 cache, 800 MHz FSB)

Intel Pentium Dual Core E5300 Processor (2.6-GHz, 2MB L2 cache, 800-MHz FSB)

Intel Pentium Dual Core E5400 Processor (2.70-GHz, 2MB L2 cache, 800-MHz FSB)

Intel Core 2 Duo Processors

Intel Core 2 Duo E4500 Processor (2.20-GHz, 2-MB L2 cache, 800-MHz FSB)

Intel Core 2 Duo E4600 Processor (2.40-GHz, 2-MB L2 cache, 800-MHz FSB)

Intel Core 2 Duo E4700 Processor (2.60-GHz, 2-MB L2 cache, 800-MHz FSB)

Intel Core 2 Duo E7300 Processor (2.66-GHz, 3-MB L2 cache, 1066-MHz FSB)

Intel Core 2 Duo E7400 Processor (2.80-GHz, 3 MB L2 cache, 1066-MHz FSB)

Intel Core 2 Duo E7500 Processor (2.93-GHz, 3 MB L2 cache, 1066-MHz FSB)

Intel Core 2 Duo E8200 Processor (2.66-GHz, 6-MB L2 cache, 1333-MHz FSB)

Intel Core 2 Duo E8300 Processor (2.83-GHz, 6 MB L2 cache, 1333-MHz FSB)

Intel Core 2 Duo E8400 Processor (3.00-GHz, 6-MB L2 cache, 1333MHz FSB)

Intel Core 2 Duo E8500 Processor (3.16-GHz, 6-MB L2 cache, 1333MHz FSB)

Intel Core 2 Duo E8600 processor (3.33 GHz, 6 MB L2 cache, 1333 MHz FSB)

NOTE: Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families.

Standard Features and Configurable Components

Operating Systems and Genuine Windows Vista Business 32*

Application Software (availability varies by region)

- Genuine Windows Vista Home Premium
- Genuine Windows Vista Home Basic 32*
- RedFlag Linux (China Only)
- Free DOS

* Certain Windows Vista product features require advanced or additional hardware. See <http://www.microsoft.com/windowsvista/getready/hardwarereqs.mspx> and <http://www.microsoft.com/windowsvista/getready/capable.mspx> for details. Windows Vista Upgrade Advisor can help you determine which features of Windows Vista will run on your computer. To download the tool, visit <http://www.windowsvista.com/upgradeadvisor>

Microsoft Office 2007 Basic

Microsoft Office 2007 Small Business

Microsoft Office 2007 Professional

Microsoft Works 8.5

HP Power Manager 2.0

Roxio Easy Media Creator 9.x**

Intervideo WinDVD Player 5.x**

Sun Java Runtime Environment

Firefox-HP Virtual Browser

** Supporting software available with certain optical drive configurations

Hard Drives

- 80-GB Serial ATA 3.0-Gb/s Hard Drive (7200 rpm)
- 160-GB Serial ATA 3.0-Gb/s Hard Drive (7200 rpm)
- 250-GB Serial ATA 3.0-Gb/s Hard Drive (7200 rpm)
- 320-GB Serial ATA 3.0-Gb/s Hard Drive (7200 rpm)
- 500-GB Serial ATA 3.0-Gb/s Hard Drive (7200 rpm)

System Memory

- 512-MB DDR2 Synch DRAM PC2-6400 (800-MHz) Non-ECC (1 x 512MB)
- 1-GB DDR2 Synch DRAM PC2-6400 (800-MHz) Non-ECC (1 x 1GB)
- 2-GB DDR2 Synch DRAM PC2-6400 (800-MHz) Non-ECC (2 x 1GB)
- 2-GB DDR2 Synch DRAM PC2-6400 (800-MHz) Non-ECC (1 x 2GB)
- 4-GB DDR2 Synch DRAM PC2-6400 (800-MHz) Non-ECC (2 x 2GB)

Standard Features and Configurable Components

Storage – One or more of the following (see Storage section below)	Diskette Drive 1.44-MB Diskette Drive Media Reader HP 16-in-1 Media Reader and additional USB 2.0 port HP 22-in-1 Media Card Reader HP 22-in-1 Media Card Reader with 1394 port Optical Drives (Serial ATA) SATA DVD-ROM Drive SATA CD-RW/DVD-ROM Combo Drive SATA SuperMulti LightScribe DVD Writer Drive
---	---

Input Devices	Keyboard – One of the following HP PS/2 Standard Keyboard HP USB Standard Keyboard Mouse – One of the following PS/2 2-Button Optical Scroll Mouse USB 2-Button Optical Scroll Mouse USB 2-Button Laser Mouse
---------------	---

Audio	Realtek ALC662 High Definition audio codec 3D audio compliant and HD Audio compatible
-------	--

Communication	Integrated Realtek 8101E 10/100 Ethernet Controller Intel Gigabit CT Desktop NIC Intel PRO/1000 PT Gigabit PCIe Controller (full height) – optional Agere 56K PCI Modem – optional LSI PCIe x1 Hi-Speed 56K International SoftModem – optional HP Wireless A+G PCI Card (full height) HP Wireless 802.11 b/g/n PCIe Card
---------------	--

Standard Features and Configurable Components

Graphics

Intel Graphics Media Accelerator – integrated

NVIDIA GeForce 8400 GS (256MB) Single Head PCIe x16 – optional*

NVIDIA GeForce GT130 768MB PCIe x16

HP ADD2 SDVO PCIe x16 DVI-D Adapter – optional

ATI Radeon HD 2400XT (256MB DH) PCIe x16 – optional

ATI Radeon 3470 256MB Single Head graphics adapter (PCIe x16)

ATI Radeon HD 4650 512MB PCIe x16

HP DisplayPort to VGA Adapter

HP DisplayPort To DVI-D Adapter

* 1GB of system memory required. Graphics cards use part of the total system memory to enhance graphics performance.

Miscellaneous

HP FireWire / IEEE 1394 PCI Card (full height)

HP Serial/Parallel PCI Card (full height)

System Details

Base Unit	<ul style="list-style-type: none">• Micro ATX microtower chassis, including power supply and front bezel• Five (5) drive bays and four expansion slots• Microsoft operating system CD – optional• Active type heatsink• 92 x 92 x 25 mm chassis fan• System board with Intel G31 Express chipset, Intel I/O Controller Hub 7 (ICH7), Realtek RTL8101E 10/100 Ethernet controller, Intel GMA graphics, and Realtek audio, (1) full-height PCI 2.3 slot, (2) PCI Express x1 slots, (1) PCI Express x16 slot, (2) DDR2 DIMM memory slots, (4) Serial ATA data connectors• Product documentation on CD• HP system restore CD – optional• Power cord
-----------	---

Slots	PCI	One (1) full-height PCI 2.3 slot on PCA Two (2) full-height PCI Express x1 slots on PCA One (1) full-height PCI Express x16 slot on PCA (for graphic cards)
	Memory Expansion	Two (2) DDR2 SDRAM DIMM slots (4 GB maximum memory support)
<p>NOTE: For systems configured with more than 3 GB of memory and a 32-bit operating system, all memory may not be available due to system resource requirements. Addressing memory above 4 GB requires a 64-bit operating system.</p>		

Bays	Internal	Two (2) 3.5"
	External	Two (2) 5.25" One (1) 3.5"

USB Support	EHCI high-speed USB 2.0 controller Two (2) front ports; Four (4) rear ports, Two (2) internal ports on motherboard	
-------------	---	--

Interfaces (Legacy)	One (1) PS/2 keyboard port
	One (1) PS/2 mouse port
	One (1) analog VGA video port
	One (1) line in; one (1) line out; one (1) mic in
	One (1) RJ45 network port

System Details

Weight & Dimensions	Chassis Dimensions	15.16 x 7.28 x 16.38 in. with bezel
	(H x W x D)	(385 x 185 x 416 mm)
		14.88 x 6.50 x 16.10 in. without bezel
		(378 x 165 x 409 mm)
	Packaged Dimensions	19.13 x 21.875 x 10.13 in
	(L x W x H)	490 x 556 x 257 mm
	System Weight	22.4 lb (10.2 kg)
	Shipping Weight	30.8 lb (14.0 kg)

Technology and Features	Memory Type	PC2-6400 DDR2 SDRAM (800MHz) non-ECC Up to 4-GB maximum system memory supported
-------------------------	-------------	--

NOTE: For systems configured with more than 3 GB of memory and a 32-bit operating system, all memory may not be available due to system resource requirements. Addressing memory above 4 GB requires a 64-bit operating system.

Hard Drive Interfaces	Serial ATA Supported
-----------------------	-------------------------

Chassis	Front Panel	Power button Power On LED HDD Activity LED
	Cooling Solutions Supported	Power Supply Fan (variable speed) Active heatsink (variable speed) Chassis fan
	Slots Supported	Four (4) full-height expansion slots
	Front I/O	Two (2) USB 2.0 ports
	Rear I/O	Standard Micro ATX I/O connectors, including four (4) USB 2.0 ports
	Drive Bays	Two (2) 5-1/4" external One (1) 3-1/2" external Two (2) 3-1/2" internal
	Internal Speaker	N/A
	Security	Padlock loop Kensington Lock Support Support for chassis padlocks and cable lock devices Optional USB Port Disable at factory (user configurable via BIOS)
	Power Supply	250-watt ATX Power Supply – PFC/non-PFC with a 115v/230v line switch (varies by country/region)

System Details

Unit Environment and Operating Conditions

General Unit Operating Guidelines

- Keep the computer away from excessive moisture, direct moisture and the extremes of heat and cold, to ensure that unit is operated within the specified operating range.
- Leave a 4 in (10.2 cm) clearance on all vented sides of the computer to permit the required airflow.
- Never restrict airflow into the computer by blocking any vents or air intakes.
- Do not stack computers on top of each other or place computers so near each other that they are subject to each other's re-circulated or preheated air.
- Occasionally clean the air vents on the front, back, and any other vented side of the computer. Lint, dust and other foreign matter can block the vents and limit the airflow.
- If the computer is to be operated within a separate enclosure, intake and exhaust ventilation must be provided on the enclosure, and the same operating guidelines listed above will still apply.

Temperature Range	Operating	50° to 95° F (10° to 35° C)
	Non-operating	-22° to 140° F (-30° to 60° C)
Relative Humidity	Operating	10% to 90% (non-condensing at ambient)
	Non-operating	5% to 95% (non-condensing at ambient)
Maximum Altitude (unpressurized)	Operating	10,000 ft (3048 m)
	Non-operating	30,000 ft (9000 m)

NOTE: Operating temperature is de-rated 1.0 deg C per 1000 ft (300 m) to 10,000 ft (3000 m) above sea level, no direct sustained sunlight. Maximum rate of change is 10 deg C/Hr. The upper limit may be limited by the type and number of options installed.

System Board

Processor	Socket T; LGA775 industry standard Micro ATX form factor Support single Intel Core 2 Duo, Celeron 4xx or Dual Core
PWM	ISL6312 – 3 Phase
Chipset	Intel G31 Express Intel I/O Controller Hub 7 (ICH7)
Super I/O	Fintek F71882FG
Front Side Bus Frequency	800/1066/1333 MHz
Memory	DDR2 SDRAM 2 x DIMM slots
Clock Generator	RTM 876-665
Integrated Graphics	Intel Graphics Media Accelerator (GMA)
Audio	Realtek ALC662 HD Audio compatible codec with two channel audio 3D audio
LOM	Realtek RTL8101E 10/100 Fast Ethernet controller
Storage	Four Serial ATA interfaces
Expansion Slots	1 x PCI 2.3 slot 2 x PCI Express x1 slots 1 x PCI Express x16 slot
BIOS	SPI EEPROM

System Details

Industrial Standard	PCI 2.3 compliant USB 2.0
Rear Side I/O Ports	1 x PS/2 keyboard port 1 x PS/2 mouse port 4 x USB 2.0 ports 1 x RJ-45 10/100 port 1 x D-sub 15 pin analog VGA port 3 x audio ports
On Board I/O Interfaces	1 x ATX power connector 1 x +12V power connector 1 x Floppy connector 1 x Front panel connector, Switch, LED (ON/Flash/OFF) 2 x Fan headers for CPU, chassis, with voltage/fan speed control 1 x header to support 2 USB 2.0 ports at front side 1 x header to support 2 front (Headphone/Mic) audio ports 1 x header to support USB media reader
Board Size	Micro-ATX, PCB Size: 9.6 x 8.5 in (24.38 x 21.86 cm) 4-layer PCB with green color
Additional Features	<ul style="list-style-type: none"> • Bootable without keyboard, mouse or monitor • Keyboard/mouse/USB wake up • Support S1, S3, S4 and S5 • ACPI status • Hardware monitor capability • CPU fan speed control

Network Interface	Integrated Realtek 8101E 10/100 Fast Ethernet Controller	Hardware Highlights Features	PCIe x1 interface 10-Mbps and 100-Mbps operation Crossover detection and auto-correction Wake-on-Lan and remote Wake-up (Wake-on-LAN supported from S1, S3, S4 only. Not supported from S5)
	Intel PRO/1000 PT Gigabit PCIe Adapter	Hardware Highlights Features	PCI Express interface 10-Mbps, 100-Mbps and 1000-Mbps operation (Wake-on-LAN supported from S1, S3, S4 only. Not supported from S5)

Wireless Wireless A+G PCI Card (full height bracket)

System Details

Power Supply

- ATX Power Supply – Passive PFC/non-PFC with a 115v/230v line switch
- Passive Power Factor Correction (PFC) – with line switch set to 230V – No PFC in 115V line switch position
- 90 to 140VAC, or 180 to 264VAC operating voltage range
- 100 to 127VAC, or 200 to 240VAC rated voltage range
- 50-60 Hz rated line frequency
- 47-63 Hz operating line frequency range
- 250 watt maximum rated power
- 80-mm power supply fan – variable speed for optimum acoustics

Power Conservation 'Energy Saver'

- APM 1.2 support
- Screen blanking
- Hard drive 'Idle' mode
- System Idle mode
- ~2 watt power consumption in ES mode – suspend to RAM (S3) (instantly available PC)
- Processor/Cache memory power-down (S3)

System Environmental Specs

- Values are subject to change without notification and are for reference only.
- Performance of system, options, and ancillary equipment will vary depending on the system configuration.
- Levels presented do not account for non-HP/Compaq installed hardware.

Ambient Air Temperature	Operating	50° to 95°F (10° to 35°C) at sea level with an altitude de-rating of 1.0°C per every 1000 ft (300 m) above sea level to a maximum of 8000 ft (2500 m), no direct sustained sunlight. Maximum rate of change is 77°F/Hr (25°C/Hr). The upper limit may be limited by the type and number of options installed.
	Storage	-22° to 140°F (-30° to 60°C) – Maximum rate of change: 410°F/Hr (210°C/Hr).
Humidity	Operating	10% to 90% relative humidity (Rh), 86°F (30°C) maximum wet bulb temperature, non-condensing
	Storage	10% to 95% relative humidity (Rh), 101.66°F (38.7°C) maximum wet bulb temperature, non-condensing
Altitude	Operating	0 to 10,000 feet (0 to 3048 meters) – This value may be limited by the type and number of options installed. Maximum allowable altitude change rate is 1,000 ft/min (304.8 m/min).
	Non-Operating	0 to 30,000 feet (0 to 9,144 meters) – Maximum allowable altitude change rate is 1200 ft/min (365.76 m/min).

System Details

Shock	<p>Listed are the levels of shock the product can withstand with NO damage being incurred. The values represent peak input acceleration during a 2 to 3 ms half-sine shock pulse, 11 ms trapezoidal shock pulse.</p> <p>Non-Operating 35G's (Half-sine Shock) 35G's (Trapezoidal Shock)</p>
Vibration	<p>Listed are the levels of vibration the product can withstand with NO damage being incurred. The values represent a flat random vibration input acceleration profile across the given frequency range.</p> <p>Operating Random vibration at 5Hz@0.00025G²/Hz, 10Hz@0.01G²/Hz, 100Hz@0.01G²/Hz, 300Hz@0.00001G²/Hz 5Hz to 300Hz, (0.25G's nominal).</p> <p>Non-Operating Random vibration at 0.008G²/Hz, 10Hz to 500Hz, (2 Grms nominal).</p>
Acoustic Noise	<p>Listed are the declared A-WEIGHTED SOUND POWER LEVELS (LWAd) and declared average desktop seated operator position A-WEIGHTED SOUND PRESSURE LEVELS (LpAm) when the product is operating in a 73.4°F (23°C) ambient environment. Noise emissions were measured in accordance with ISO 7779 (ECMA 74) and declared in accordance with ISO 9296 (ECMA 109).</p> <p>IDLE (Fixed disk drive LWAd = 4.3 Bels, spinning) Desktop Average LpAm = 32dBA</p> <p>FIXED DISK (Random write) LWAd = 4.8 Bels, Desktop Average LpAm = 37dBA</p> <p>CD-ROM (Sequential LWAd = 5.0 Bels, Reads) Deskside Average LpAm = 39dBA</p>

Service and Support On-site Warranty ^{Note 1}: One-year (1-1-1) limited warranty delivers one year of on-site, next business-day ^{Note 2} service for parts and labor and includes free telephone support ^{Note 3} 24 x 7. Global coverage ^{Note 2} ensures that any product purchased in one country and transferred to another non-restricted country will remain fully covered under the original warranty and service offering. One-year onsite and labor are not available in all countries.

NOTE 1: Terms and conditions may vary by country. Certain restrictions and exclusions apply. Other warranty variations may be offered in your region

NOTE 2: On-site service may be provided pursuant to a service contract between HP and an authorized HP third-party provider, and is not available in certain countries. Global service response times are based on commercially reasonable best effort and may vary by country.

NOTE 3: Technical telephone support applies only to HP-configured Compaq and third-party HP-qualified hardware and software. Toll-free calling and 24 x 7 support may not be available in some countries.

After-Market Options

Communications	NICs	
	Intel Gigabit CT Desktop NIC	FH969AA
	Intel PRO/1000 PT Gigabit PCIe Controller (full height)	EH352AA
	Wireless LAN	
	HP Wireless A+G PCI Card (North America only)	EA118AA
	HP Wireless A+G PCI Card (WW except North America)	PZ928AA
	HP Wireless 802.11 b/g/n PCIe Card	FH971AA
	Modems	
	Agere 2006 PCI High-Speed 56K International SoftModem	EK694AA
LSI PCIe x1 Hi-Speed 56K International SoftModem	FH970AA	
Hard Disk Drives	HP 500-GB SATA 3.0-Gb/s Hard Drive	PV943A
	HP 320-GB SATA 3.0-Gb/s Hard Drive	FH963AA
	HP 250-GB SATA 3.0-Gb/s Hard Drive	PY278AA
	HP 160-GB SATA 3.0-Gb/s Hard Drive	PY277AA
	HP 80-GB SATA 3.0-Gb/s Hard Drive	PY276AA
Removable Storage Devices	Diskette Drive	
	HP 1.44-MB Internal Diskette Drive	AH053AA
	HP 1.44-MB USB Diskette Drive – External	DC141B
	HP 16-in-1 Media Reader	EM718AA
	HP 22-in-1 Media Card Reader	FX273AA
HP 22-in-1 Media Card Reader with 1394 port	KN518AA	
Input Devices	HP PS/2 Standard Keyboard	DT527A
	HP USB Standard Keyboard	DT528A
	HP 2.4 GHz Wireless Keyboard and Mouse	NB896AA#xxx
	HP USB 2-Button Laser Mouse	GW405AA
	HP PS/2 2-Button Optical Scroll Mouse	EY703AA
	HP USB 2-Button Optical Scroll Mouse	DC172B
Memory	HP 2-GB PC2-6400 (DDR2-800 MHz) DIMM	AH060AA
	HP 1-GB PC2-6400 (DDR2-800 MHz) DIMM	AH058AA
	HP 512-MB PC2-6400 (DDR2-800 MHz) DIMM	AH056AA
Audio	HP Satellite Speakers	ZD929AA

After-Market Options

Graphics	NVIDIA GeForce 8400 GS 256MB SH PCIe x16 Graphics Card*	GJ119AA
	NVIDIA GeForce GT130 768MB PCIe x16	AR957AA
	ATI Radeon HD 2400XT 256MB DH PCIe x16 Graphics Card	KD060AA
	ATI Radeon 3470 256MB SH PCIe x16	FH972AA
	ATI Radeon HD 4650 512MB PCIe x16	AR956AA
	HP DisplayPort To DVI-D Adapter	FH973AA
	HP DisplayPort to VGA Adapter	AS615AA
	HP ADD2 SDVO DVI-D Adapter	DY674A

* 1 GB of system memory required. Graphics cards use part of the total system memory to enhance graphics performance.

Optical Drives	HP SATA CD-RW/DVD-ROM Combo Drive	AH046AA
	HP SATA DVD-ROM Drive	AH047AA
	HP SATA SuperMulti LightScribe DVD Writer Drive	GF343AA

Security	HP Business PC Security Lock Kit	PV606AA
----------	----------------------------------	---------

Miscellaneous Accessories	HP FireWire / IEEE 1394 PCI Card	PA997A
---------------------------	----------------------------------	--------

Monitors*	CRTs	
	HP s7540 17" (16.0" vis) CRT Monitor	PF997AA#XXX
	HP v7650 17" (16.0" vis) Flat-face CRT Monitor	PF996AA#XXX
	TFTs	
	HP L1506 15" TFT Flat Panel Monitor – Analog only	PX848AA#XXX
	HP L1706 17" TFT Flat Panel Monitor – Analog only	PX849AA#XXX
	HP L1740 17" TFT Flat Panel Display – Analog/Digital	PL766AA#XXX
	HP L1755 17" TFT Flat Panel Display – Analog/Digital	PL777AA#XXX
	HP L1906 19" TFT Flat Panel Display – Analog only	PX850AA#XXX
	HP L1940T 19" TFT Flat Panel Display – Analog/Digital	EM869AA#XXX
	HP L1955 19" TFT Flat Panel Display – Analog/Digital	PD974AA#XXX
	HP L2065 20" TFT Flat Panel Display – Analog/Digital	EF227A4#XXX
	HP LP2465 24" TFT Widescreen Flat Panel Display – Analog/Digital	EF224A4#XXX
	GSA Monitors	
	HP L717g 17" GSA Flat Panel Monitor	EE191AA#XXX
	HP L919g 19" GSA Flat Panel Monitor	EE192AA#XXX
	Options	
	HP Flat Panel Speaker Bar	EE418AA
	HP CRT Monitor Multimedia Base	PM552AA

After-Market Options

*This is only representative, not an exhaustive list.

Memory

DDR SYNCH DRAM NON-ECC MEMORY

The Intel G31 Express chipset supports non-ECC DDR2 memory up to PC2-6400 (800-MHz). Memory upgrades are accomplished by adding single or dual DIMMs of the same or varied sizes. This chart does not represent all possible memory configurations.

CAUTION: You must shut down the computer and disconnect the power cord before adding or removing memory modules. Regardless of the power-on state, voltage is always supplied to the memory modules as long as the computer is plugged in to an active AC outlet. Adding or removing memory modules while voltage is present may cause irreparable damage to the memory modules or system board.

HP recommends dual-channel symmetric configurations for maximum performance.

For best performance, add the same amount of total memory to each channel and do not mix speeds. For dual-channel symmetric performance, the total amount of memory in each channel must be equal. If speeds are mixed, speed will default to the slowest DIMM.

STANDARD MEMORY

512-MB, 1-GB, 2-GB, or 4-GB DDR2 SYNCH DRAM


OPTIONAL MEMORY UPGRADES

Supports up to 4 GB of DDR2 SYNCH DRAM. Not all memory configurations possible are represented below.

NOTE: For systems configured with more than 3 GB of memory and a 32-bit operating system, all memory may not be available due to system resource requirements. Addressing memory above 4 GB requires a 64-bit operating system.

DIMM Size	Slot 1	Slot 2
512-MB	512-MB	
1-GB	1-GB	
2-GB (dual-channel symmetric)	1-GB	1-GB
4-GB (dual-channel symmetric)	2-GB	2-GB

Storage



HP Compaq dx2390 Microtower Business PC

Drive Support	Maximum Quantity Supported	Position Supported	Controller
Diskette Drives	1	3	SIO
Media Reader	1	3	Internal USB 2.0 port
DVD-ROM Drives	2	1, 2	SATA
CD-RW/Combo Drives	2	1, 2	SATA
SuperMulti LightScribe DVD Writer Drives	2	1, 2	SATA
3.5" Serial ATA Hard Drives	2	4,5	SATA

Technical Specifications - Audio

Integrated Realtek ALC662 Audio	Type	Integrated
	HD Audio compatible	Yes
	codec	5:1 channel
	Sampling	Supports 48/96 KHz
	Audio Jacks	Mic-In Line-In Line-Out / Headphone Out
	Power Support	Digital: 3.3V Analog: 5V
	Other	Meets performance requirements for audio on PC99/2001 systems High-performance DACs with 97dB SNR(A-Weighting) ADCs with 90dB NR(A-Weighting)

Technical Specifications - Communications

Integrated Realtek 8101E Controller	8101E-GR
GR 10/100 Fast Ethernet Controller	N/A
Data rates supported	2.5GHz data rate with X1 link width
Compliance	IEEE802.3, IEEE 802.3u, IEEE 802.3ab
Bus architecture	PClexpress 1.1
Data transfer mode	Half/Full Duplex Operation
Hardware certifications	MS NDIS5, IPv4, IPv6, TCP, UDP
Power requirement	100mbps (heavy traffic) TBD mW max.
	10mbps (heavy traffic) TBD mW max.
	S3 with Link TBD mW
	Link Down @S0 TBD mW
	Link Down @S3/S5 TBD mW
Boot ROM support	EEPROM, 1Kb, 2Kb
Network transfer rate	10/100Mbps over CAT.5 10Mbps over CAT.3
Dimensions	9mm x 9mm
Management capabilities	ACPI rev 2.0, PM rev 1.1, ASPM v1.0a

Intel Gigabit CT Desktop NIC	Connector	RJ-45
	Controller	Intel WG82574L Gigabit Ethernet Controller
	Memory	Integrated Dual 48K configurable transmit receive FIFO Buffers
	Data rates supported	10/100/1000 Mbps
	Compliance	IEEE 802.1P, 802.1Q, 802.2, 802.3, 802.3AB and 802.3u compliant, 802.3x flow control
	Bus architecture	PCI-E 1.0a
	Data path width	X1, 250 MB/s, Bi-directional interface
	Data transfer mode	Bus-master DMA
	Hardware certifications	FCC, B, CE, TUV- cTUVus Mark Canada and United States, TUV- GS Mark for European Union
	Power requirement	Aux 3.3V, 3.0 Watts in 1000base-T and 2.0 Watts in 100Base-T
	Boot ROM support	Yes
	Network transfer rate	10BASE-T (half-duplex) 10 Mbps 10BASE-T (full-duplex) 20 Mbps 100BASE-TX (half-duplex) 100 Mbps 100BASE-TX (full-duplex) 200 Mbps 1000BASE-T (full-duplex) 2000 Mbps

Technical Specifications - Communications

Environmental	Operating temperature	32° to 131°F (0° to 55° C)
	Operating humidity	85% at 131° F (55° C)
Dimensions	4.75 x 2.25 x 0.8 in (12.1 x 5.7 x 2.0 cm)	
Operating system driver support	Windows Vista Business 64*, Windows Vista Business 32*, Windows Vista Home Basic 32*, Windows XP Professional or Windows XP Home 32*. No driver is required for this device. Native support is provided by the operating system. Red Hat Linux 7.2, Linux 7.3 and Red Hat Enterprise Linux 3	
	* Certain Windows Vista product features require advanced or additional hardware. Windows Vista Upgrade Advisor can help you determine which features of Windows Vista will run on your computer. To download the tool, visit: http://www.windowsvista.com/upgradeadvisor . For Windows Vista system requirements, visit: http://www.windowsvista.com/systemrequirements .	
Management capabilities	WOL, PXE, DMI, WFM 2.0	

Intel PRO/1000 PT Gigabit PCIe Controller	Connector	RJ-45
	Controller	Intel 82572EI Gigabit Ethernet Controller
	Memory	Integrated Dual 48K configurable transmit receive FIFO Buffers
	Data rates supported	10/100/1000 Mbps
	Compliance	IEEE 802.1P, 802.1Q, 802.2, 802.3, 802.3AB and 802.3u compliant, 802.3x flow control
	Bus architecture	PCI Express 1.0a
	Data transfer mode	Bus-master DMA
	Hardware certifications	FCC, B, CE, TUV- cTUVus Mark Canada and United States, TUV- GS Mark for European Union
	Power requirement	Aux 3.3V, 3.0 Watts in 1000base-T and 2.0 Watts in 100Base-T
	Boot ROM support	Yes
	Network transfer rate	10BASE-T (half-duplex) 10 Mbps 10BASE-T (full-duplex) 20 Mbps 100BASE-TX (half-duplex) 100 Mbps 100BASE-TX (full-duplex) 200 Mbps 1000BASE-T (full-duplex) 2000 Mbps (actual rate limited by PCI Bus)
Environmental	Operating temperature	32° to 131°F (0° to 55° C)
	Operating humidity	85% at 131° F (55° C)
Dimensions	6.4 x 2.6 x 0.8 in (16.3 x 6.6 x 1.9 cm)	
Management capabilities	ASF, WOL, PXE, DMI, WFM 2.0. (Wake-on-LAN supported from S1, S3, S4 only. Not supported from S5)	

Technical Specifications - Communications

HP Wireless A+G PCI	Dimensions	4.99 x 2.54 x 0.71 in (126.8 x 64.4 x 18.0 mm)	
	Weight	0.268 lb (65 g)	
	Controller	Atheros AR5414X chipset	
	system interface	PCI Spec 2.2	
	Network standard	IEEE 802.11a/b/g	
	Frequency band	5.1500 to 5.8500 GHz 2.4000 to 2.4835 GHz 2.4465 to 2.4835 GHz (Europe, Middle East, Asia and Asia Pacific – excluding Japan) 2.4000 to 2.4697 GHz (Japan)	
	Operating Temperature	32° to 140° F (0° to 60° C), operating	
	Storage temperature	-4° to 176° F (-20° to 80° C), non-operating	
	Humidity	10% to 85% non-condensing	
	Operating voltage	5V ± 5%	
	Power consumption	Tx/Rx peak 560/250mA @ 3.3V (max.)	
	Output power (approximately)	15 dBm ±2dB	
	Receive sensitivity	-90dBm at 11 Mbps (typical)	
	Data transfer rate	Standard rates of 1, 2, 5.5, 11, 6, 9, 12, 18, 24, 48, 54 and Super AG Mode108-Mbps	
	Spreading	DSSS (Direct Sequence Spread Spectrum)	
	Security	64(40h) bit, 128(104h) bit, WPA, IEEE802.1X, AES-OCB, AES-CCM, Microsoft PEAP,TKIP, WEP	
	Antenna	External 5dBi antenna	
	Throughput	108 Mbps (only with Belkin 54G or 200 ft (60.96 m) – Indoor above router that supports 108 Mbps speed)	
		54 Mbps	200 ft (60.96 m) – Indoor
		11 Mbps	200 ft (60.96 m) – Indoor
	Certifications	Wi-Fi certified	
	Certifications for use by country	North America: United States, Canada Europe: Austria, Belgium, Cyprus, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Liechtenstein, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland, United Kingdom Australia, New Zealand	

HP Wireless 802.11b/g/n PCIe	Dimensions (L x H)	3.3 x 4.7 inches (8.5 x 12 cm)
	Weight	0.08 pounds (40 g)
	Controller	Ralink RT2790
	System interface	PCIExpress x1
	Network standard	802.11 b/g/n



Technical Specifications - Communications

Frequency band	2.400 - 2.497 GHz		
Operating temperature	14° to 149°F, operating (-10° to 65°C, operating)		
Storage temperature	-40° to 176°F, non-operating (-40° to 80°C, non-operating)		
Humidity	10-90% operating 5-95% non-operating		
Operating voltage	3.3V +/- 9% 12V +/- 8%		
Power consumption	Platform/WLAN Mode	Power Consumption	
	Maximum Power Consumption	10 Watts	
	Transmit Only	4 Watts maximum averaged power over 1 second	
	Transmit Packet or Active Scanning	1000 mA peak current for 100 microseconds or longer	
	Receive Only Mode or Idle without IEEE PSP mode enabled	3 Watts maximum averaged over 1 second	
	Idle, with IEEE PSP mode enabled	1.0 Watts maximum averaged over 1 second	
	Transmit Disabled (turned off in software)	50 mW maximum, averaged over 1 second	
	Platform in S3 or S4 (power removed from Low Profile PCI Express Card)	5 mW maximum, averaged over 1 second	
Output power (approximately)	802.11b modes +19 dBm +/- 1.0 dB maximum	802.11g modes +17 dBm +/- 1.0 dB maximum	EWC modes +17 dBm +/- 1.0 dB maximum (total power in all transmit chains)
Receive sensitivity	Mode	Data rate	Sensitivity
	802.11b	1 Mbps	-94 dBm
	802.11b	11 Mbps	-85 dBm
	802.11g	6 Mbps	-91 dBm
	802.11g	18 Mbps	-85 dBm
	802.11g	48 Mbps	-75 dBm
	802.11g	54 Mbps	-72 dBm
	EWC (2.4 GHz)	6.5 Mbps	-87 dBm
	EWC (2.4 GHz)	54 Mbps	-82 dBm
	EWC (2.4 GHz)	81 Mbps	-78 dBm
	EWC (2.4 GHz)	162 Mbps	-74 dBm
	EWC (2.4 GHz)	270 Mbps	-68 dBm
	EWC (2.4 GHz)	300 Mbps	-64 dBm
Data transfer rate	Data Rate (MCS)	Minimum Throughput	

Technical Specifications - Communications

1 Mbps (802.11 b)	700 kbps
2 Mbps (802.11 b)	1.4 Mbps
5.5 Mbps (802.11 b)	3.5 Mbps
11 Mbps (802.11 b)	5.9 Mbps
12 Mbps (802.11 g)	6 Mbps
18 Mbps (802.11 g)	9 Mbps
24 Mbps (802.11 g)	12 Mbps
36 Mbps (802.11 g)	18 Mbps
48 Mbps (802.11 g)	21 Mbps
54 Mbps (802.11 g)	22.5 Mbps
6.5 Mbps (20 MHz EWC)	4.5 Mbps
13 Mbps (20 MHz EWC)	9 Mbps
19.5 Mbps (20 MHz EWC)	13.5 Mbps
26 Mbps (20 MHz EWC)	18 Mbps
39 Mbps (20 MHz EWC)	27 Mbps
52 Mbps (20 MHz EWC)	36 Mbps
58.5 Mbps (20 MHz EWC)	40 Mbps
65 Mbps (20 MHz EWC)	45 Mbps
78 Mbps (20 MHz EWC)	54 Mbps
104 Mbps (20 MHz EWC)	72 Mbps
117 Mbps (20 MHz EWC)	81 Mbps
130 Mbps (20 MHz EWC)	91 Mbps
13.5 Mbps (40 MHz EWC)	8 Mbps
27 Mbps (40 MHz EWC)	16 Mbps
40.5 Mbps (40 MHz EWC)	24 Mbps
54 Mbps (40 MHz EWC)	32 Mbps

Technical Specifications - Communications

	81 Mbps (40 MHz EWC)	48 Mbps
	108 Mbps (40 MHz EWC)	64 Mbps
	121.5 Mbps (40 MHz EWC)	72 Mbps
	135 Mbps (40 MHz EWC)	81 Mbps
Security	<ul style="list-style-type: none"> • IEEE and WiFi compliant 64 / 128 bit WEP encryption • AES: CCM • 802.1x authentication • WPA: 802.1x, WPA-PSK and TKIP • WPA2 certification • IEEE 802.11i • Cisco Certified Extensions, all versions through V5 	
Antenna	HP part number 497792-001	
Certifications	Wi-Fi certified	
Certifications for use by country	United States, Canada, Peru, Taiwan	

Agere 56K PCI Modem	Data Transmission	56,000 Kbps maximum downstream data
		<i>NOTE: 56 Kbps technology refers to download speeds only and requires compatible modems at server sites. Other conditions may limit modem speed. FCC limitations allow a maximum of 53 Kbps during download transmissions.</i>
	Data Speeds	(Upload only) 33,600/31,200/28,800/26,400/21,600/19,200/16,800/14,400/ 12,000/9,600/7,200/4,800/2,400/1,200/300
	Data Standards	ITU-T V.90, ITU-T, ITU-T V.34, V.44, V.42, V.42bis, V.32bis, Bell 212A, and Bell 103
	Fax Speeds	14,400/12,000/9,600/7,200/4,800/2,400/300 b/s
	Fax Mode Capabilities	ITU-T T.31 class 1 FAX, V. 17, V.29, V.27ter, and V.21 Channel 2
	Error Correction and Data Compression	V.44, 42bis, V.42 and MNP2-5
	Power Management	ACPI; PPMI 1.1 and wake support with PME and Vaux; meets PCI 2.3 requirements and PC 2001 requirements
	Upgradeability	Driver upgradeable for future enhancements
	Video	ITU-T V.80 video ready interface
	Other	TIA/EIA 602 standard AT command set
		Integrated DTE interface with speeds of up to 115.2 Kbps, parallel 16550a UART-compatible interface
		Optional ring wakeup signal
	Operating Temperature	32° to 158° F (0° to 70° C)

Technical Specifications - Communications

Operating Humidity	20% to 90%, non-condensing
Power	Requires a 3.3-V auxiliary power rail on PCI bus Uses only one PCI load (i.e., one grant/request pair), one shared IRQ, one electrical load
Chipset	Agere Systems SV92PL – Integrated PCI interface with 5-V tolerant buffers and CardBus support
Dimensions (L X H)	Complies with PCI low profile specifications-6.7 x 2.3 in (17.0 x 5.8 cm) and supports high- and low-profile brackets
Connection	Single RJ-11 connector
Other Features	Digital line protection, call progress monitoring via on-board piezo device, support for high profile and low profile brackets, PnP ID support
Safety	UL recognized to UL 1950, 3rd edition (U.S. and Canada); IEC 950 (TUV, NEMKO, DEMKO, SEMKO); CE Mark, EC 950 (TUV, NEMKO, DEMKO, SEMKO, CE mark
EMC	FCC Part 15, IC ES003, EN 55022, 3rd edition, EN 55024, annex A, EN 61000-4-6, EN 61000-4-8
Telecom	FCC Part 68, IC-CS-03 (Canada); Worldwide PTT approvals Not available in Korea or the Republic of South Africa.
Health	Bare PCB material compliant to 94V-0 or better (marked as such)
Other	PC 2001 compliant, PCI version 2.3, WHQL approved; ACPI compliant

LSI PCIe x1 56K International SoftModem	Data Transmission	Technology speeds: 56,000 Kbps maximum downstream data, controllerless NOTE: 56 Kbps technology refers to download speeds only and requires compatible modems at server sites. Other conditions may limit modem speed. FCC limitations allow a maximum of 53 Kbps during download transmissions.
	Data Speeds	(Upload only) 33,600/31,200/28,800/26,400/21,600/19,200/16,800/14,400/12,000/9,600/7,200/4,800/2,400/1,200/300
	Data Standards	ITU-T V.90, ITU-T, ITU-T V.34, V.44, V.42, V.42bis21, V.32bis, Bell 212A, and Bell 103
	Fax Speeds	14,400/12,000/9,600/7,200/4,800/2,400/1,200/300 b/s
	Fax Mode Capabilities	ITU-T T.31 class 1 FAX, V. 17, V.29, V.27ter, and V.21 Channel 2
	Error Correction and Data Compression	V.44, 42bis, V.42 and MNP2-5
	Power Management	PCI Bus Power Management Interface Specification (PCI-PM) Revision 1.2, Appendix A. D0, D3hot, and D3cold. Wake on Ring state when in D3cold. If the power management event (PME) feature is enabled in D3cold, a modem can wake the system via WAKE# (WAKEN) or beacon. Meets PCI Express 1.1 standard.
	Upgradeability	Driver upgradeable for future enhancements
	Video	ITU-T V.80 video ready interface

Technical Specifications - Communications

Other	TIA/EIA 602 standard AT command set Integrated DTE interface with speeds of up to 115.2 Kbps, parallel 16550a UART-compatible interface Optional ring wakeup signal
Operating Temperature	32° to 158° F (0° to 70° C)
Operating Humidity	20% to 90%, non-condensing
Power	Requires a 3.3-V auxiliary power rail on PCI express bus Uses only one PCI express load (i.e., one grant/request pair), one shared IRQ, one electrical load
Chipset	LSI SV92EX – Integrated PCI interface with 3.3-V tolerant buffers and CardBus support
Dimensions (L X H)	Complies with PCI express low profile specifications—6.7 x 2.3 in (17.0 x 5.8 cm) and supports high- and low-profile brackets
Connection	Single RJ-11 connector
Other Features	Digital line protection, call progress monitoring via on-board piezo device, support for high profile and low profile brackets, PnP ID support
Safety	UL recognized to UL 1950, 3 rd edition (U.S. and Canada); IEC 950 (TUV, NEMKO, DEMKO, SEMKO); CE Mark, EC 950 (TUV, NEMKO, DEMKO, SEMKO, CE mark
EMC	FCC Part 15, IC ES003, EN 55022, 3 rd edition, EN 55024, annex A, EN 61000-4-6, EN 61000-4-8
Telecom	FCC Part 68, IC-CS-03 (Canada); Worldwide PTT approvals Not available in Korea or the Republic of South Africa.
Other	The SV92EX device is packaged in a 32-pin micro leadless chip carrier (MLCC). The SV92EX is fully compliant with the PCI Express revision 1.1 specification. WHQL approved; ASPM compliant.

Technical Specifications - Graphics

Integrated Graphics Media Accelerator	3D/2D Controller	Microsoft DirectX® 9 based with support for Pixel Shader 2.0, 4:1 anisotropic filtering, Gaussian texture filtering, shadow maps, volumetric textures, double-sided stencil buffers, and 4 pixel pipes.
	VGA Controller	Integrated
	Bus Type	PCI Express™ x16 (If an external graphics card is installed in a PCI slot, the internal graphics can be enabled or disabled using the system's BIOS setup utility. If an external graphics card is installed in the PCI Express™ slot, the internal graphics cannot be enabled).
	RAMDAC	Integrated, 350 MHz
	Memory	Graphics memory is shared with system memory. Graphics memory usage varies depending on the amount of system memory installed and system load. 8 MB is pre-allocated for graphics use at system boot time. Additional memory is allocated for graphics as needed using Intel's Dynamic Video Memory Technology (DVMT), to provide an optimal balance between graphics and system memory use. System memory equal or greater than 512 MB 8 MB pre-allocated + 248 MB DVMT = max frame buffer of 256 MB
	Controller Clock Speed	250 MHz
	Overlay Planes	Single overlay support with 5x3 filtering
	Maximum Color Depth	32 bits/pixel
	Maximum Vertical Refresh Rate	75 Hz at up to 2048 x 1536 analog, 60 Hz at up to 1920 x 1200 for flat panel, 85 Hz at up to 1400 x 1050 for digital CRT/HDTV. Varies with mode and configuration. See table below.
	Multi-display Support	Support for one CRT via the motherboard's VGA connector. Support for an additional DVI-D display via the optional DVI ADD2 card. Dual independent displays and dual synchronous (Twin or Clone mode) displays are supported.
	Graphics/Video API Support	Microsoft DirectX®9, DirectXVA®, VMR9, GDI/GDI+; OpenGL® 1.4.

Resolutions Supported ¹	Resolution	Maximum Refresh Rate (Hz)		
		Analog Monitor	Digital Monitor	
			Flat Panel	CRT / HDTV
	640 x 480	75	60	85
	800 x 600	75	60	85
	1024 x 768	75	60	85
	1280 x 1024	75	60	85
	1400 x 1050	75	60	85
	1600 x 1200	75	60	N/A
	1920 x 1080	75	60	N/A
	1920 x 1200	75	60	N/A
	1920 x 1440	75	N/A	N/A
	2048 x 1536	75	N/A	N/A

Technical Specifications - Graphics

1 Modes listed are supported with a single active display. The supported mode list for multiple active displays is a subset of this list. Not all modes will support video playback and some supported modes may use software MC (motion compensation) rather than hardware MC. Not all modes will support 3D acceleration depending on the system configuration (e.g., resolution selected, size of frame buffer, number of installed memory modules, etc.).

NOTE: Other resolutions and refresh rates may be selectable but are not recommended.

NVIDIA GeForce 8400 GS (256 MB SH) PCIe x16 Graphics Controller	Bus type	PCI Express (x16 lanes)										
	Maximum vertical refresh rate	85 Hz										
	Display support	Integrated 400 MHz RAMDAC										
	Display max resolution	2048 x 1536 (analog), 2560 x 1600 (digital)										
	Input/Output connectors	DVI-I (DVI port supports dual-link and HDCP) TV-out (4 pin S-video)										
	Board display options	DVI-I + TV DVI-I supports analog CRT or flat panel or digital flat panel (using DVI-A, DVI-D or DVI-I connector) DVI-I supports analog CRT or flat panel (with VGA connector and DVI-I to VGA dongle) TV connector is a 4-pin mini-DIN S-video connector										
	Board configuration	<table border="0"> <thead> <tr> <th>Specification</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>Graphics Chip</td> <td>NVIDIA GeForce 8400 GS</td> </tr> <tr> <td>Core clock</td> <td>460 MHz</td> </tr> <tr> <td>Memory clock</td> <td>200 MHz</td> </tr> <tr> <td>Frame buffer</td> <td>256 MB DDR2</td> </tr> </tbody> </table>	Specification	Description	Graphics Chip	NVIDIA GeForce 8400 GS	Core clock	460 MHz	Memory clock	200 MHz	Frame buffer	256 MB DDR2
Specification	Description											
Graphics Chip	NVIDIA GeForce 8400 GS											
Core clock	460 MHz											
Memory clock	200 MHz											
Frame buffer	256 MB DDR2											
	Languages supported	24 languages: English, Arabic, Chinese Simplified, Chinese Traditional, Czechoslovakian, Danish, Dutch, Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Thai, Turkish										
	Core power	25 W (Max board power)										

NVIDIA GeForce 8400 GS (256 MB SH) PCIe x16 Graphics Controller display resolutions and refresh rates

NOTE: Other resolutions may be available but are not recommended as they may not have been tested and qualified by HP.

Technical Specifications - Graphics

Resolution	Maximum Refresh Rate (Hz)	
	Analog Connection	Digital Connection
640x480	85	60
800x600	85	60
1024x768	85	60
1280x720	85	60
1280x1024	85	60
1440x900	75	60
1600x1200	85	60
1680x1050	75	60
1920x1080	85	60-R
1920x1200	85	60-R
1920x1440	85	N/A
2048x1536	75	N/A
2560x1600	N/A	60*

* Only supported when using a dual-link DVI or DP connection

NOTE: 60-R denotes reduced blanking timings are used on single-link DVI connections and may be used with other digital connections

NVIDIA GeForce Bus type PCI Express (x16 lanes)
 GT130 768MB Input/Output DVI (DVI port supports dual-link and HDCP)
 PCIe x16 connectors VGA and HDMI
 Graphics Card Board display Supports two displays through any combination of two of the three output ports.
 options

Board configuration	Specification	Description
Graphics Chip		NVIDIA GeForce GT130
Core clock		550 MHz
Memory clock		500 MHz
Frame buffer		768MB DDR2

Maximum vertical refresh rate 85 Hz

Display support Integrated 400 MHz RAMDAC

Display max resolution 2048 x 1536 (analog), 2560x1600 (digital)

NVIDIA GeForce GT130 768MB PCIe x16 Graphics Controller display resolutions and refresh rates

NOTE: Other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

Technical Specifications - Graphics

Resolution	Maximum Refresh Rate (Hz)	
	Analog Connection	Digital Connection
640x480	85	60
800x600	85	60
1024x768	85	60
1280x720	85	60
1280x1024	85	60
1440x900	75	60
1600x1200	85	60
1680x1050	75	60
1920x1080	85	60-R*
1920x1200	85	60-R
1920x1440	85	N/A
2048x1536	75	N/A
2560x1600	N/A	60**

* Max HDMI resolution is 1080p

** Only supported when using a dualLink DVI connection

NOTE: 60-R denotes reduced blanking timings are used on single-link DVI connections and may be used with other digital connections

Languages supported 24 languages: English, Arabic, Chinese Simplified, Chinese Traditional, Czechoslovakian, Danish, Dutch, Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Thai, Turkish

Operating systems support Windows Vista Home Basic 32*
FreeDOS
Linux® x86 and x86_64 distributions using XFree86® or X.Org**

* Certain Windows Vista product features require advanced or additional hardware. Windows Vista Upgrade Advisor can help you determine which features of Windows Vista will run on your computer. To download the tool, visit: <http://www.windowsvista.com/upgradeadvisor>. For Windows Vista system requirements, visit: <http://www.windowsvista.com/systemrequirements>.

** Linux drivers are available from NVIDIA's website and may be available in a Linux distribution. Refer to the Open Source and Linux from HP website (<http://www.hp.com/wwsolutions/linux/products/clients/>) for support information.

Maximum power 70W

Option kit contents

- NVIDIA GeForce GT130 768MB PCIe x16 Graphics Card
- Software CD with graphics drivers
- Warranty documentation

Compliance standards EMC Emissions:
a. CISPR22: 1997/EN 55022:1998 - Class B - Limits and methods of measurement of radio disturbance characteristics of Information Technology Equipment

EMC Immunity:
CISPR 24:1997/EN 55024:1998 - Information Technology Equipment - Immunity Characteristics - Limits and Methods of Measurement.

Technical Specifications - Graphics

HP ADD2 SDVO PCIe x16 DVI-D Adapter	Models	HP ADD2 SDVO DVI-D Out Adapter
	Form Factor	Low-profile card
	DVI-D Connector	Digital connection only
	Dual Head Support	Yes, when used with the integrated VGA connector
	Display Devices Supported	HP L1740 HP L1940T HP L2045W HP LP1965

NOTE: These graphics adapters offer optimal performance with any display that meets applicable VESA standards.

Color Depth	All modes support 8-bpp, 16-bpp, and 24-bpp color depths
Host Interface Connector	Mechanically compliant with PCIe standard Complies with the Intel ADD2 and Intel Serial Digital Video Output (SDVO) specifications
Dot Clock	165 MHz maximum
Display Modes	Supports display modes that require up to 165-MHz bandwidth on the link, as shown in the following table.

Resolution		60-Hz LCD	60-Hz	75-Hz	85-Hz
Blanking		5% reduced	GTF	GTF	GTF
640 x 480	VGA	Yes	Yes	Yes	Yes
800 x 600	SVGA	Yes	Yes	Yes	Yes
1024 x 768	XGA	Yes	Yes	Yes	Yes
1280 x 1024	SXGA	Yes	Yes	No	No
1600 x 1200	UXGA	Yes	Yes	No	No

HP DisplayPort to VGA Adapter	Connectors	DisplayPort and VGA connector
	Adapter length	8 in (20 cm)
	Adapter weight	.1 lbs (.06 kg)
	Option kit contents	HP DisplayPort to VGA Adapter, documentation
	Maximum vertical refresh rate	85 Hz
	Display support	162 MHz RAMDAC
Display max resolution	1600x1200	

Technical Specifications - Graphics

HP DisplayPort to VGA adapter display resolutions and refresh rates

NOTE: Other resolutions may be available but are not recommended as they may not have been tested and qualified by HP. Using the HP DisplayPort to VGA Adapter may require an update to the graphics driver installed on your system. To install the most up-to-date graphics driver go to: www.hp.com.

Resolution	Max refresh rate
640x480	85
800x600	85
1024x768	85
1280x720	85
1280x1024	85
1440x900	75
1600x1200	60
1680x1050	60
1920x1080	60-R
1920x1200	60-R

NOTE: 60-R denotes reduced blanking timings are used. Not all monitors support reduced blanking timing.

ATI Radeon HD 2400XT (256MB DH) PCIe Graphics Card	Bus type	PCI Express (x16 lanes)										
	Maximum vertical refresh rate	85 Hz										
	Display support	Integrated 400 MHz RAMDAC										
	Display max resolution	2560 x 1600 digital, 2048 x 1536 analog										
	Board display options	Supports two displays via included DMS-59 to dual VGA cable or 2 DVI monitors via optional DMS-59 to dual DVI cable kit part number: DL139A. 4-pin mini-DIN S-video connector for TV output										
	Board configuration	<table border="1"> <thead> <tr> <th>Specification</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>Graphics Chip</td> <td>RV610</td> </tr> <tr> <td>Core clock</td> <td>650 MHz</td> </tr> <tr> <td>Memory clock</td> <td>500 MHz</td> </tr> <tr> <td>Frame buffer</td> <td>256 MB DDR2, 128 bit wide</td> </tr> </tbody> </table>	Specification	Description	Graphics Chip	RV610	Core clock	650 MHz	Memory clock	500 MHz	Frame buffer	256 MB DDR2, 128 bit wide
Specification	Description											
Graphics Chip	RV610											
Core clock	650 MHz											
Memory clock	500 MHz											
Frame buffer	256 MB DDR2, 128 bit wide											
	Languages supported	24 languages: English, Arabic, Chinese Simplified, Chinese Traditional, Czechoslovakian, Danish, Dutch, Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Thai, Turkish										
	Core power	21 W										
	Compliance standards	<p><u>EMC Emissions:</u></p> <p>a) FCC Part 15, Subpart B – Unintentional Radiators, Class B Computing Devices for Home & Office Use</p> <p>b) CISPR22: 1997/EN 55022:1998 – Class B – Limits and methods of measurement of radio disturbance characteristics of Information Technology Equipment</p> <p>c) Canadian Standard ICES-003 is equivalent to CISPR22</p>										

Technical Specifications - Graphics

d) Taiwanese Standard BSMI

e) Japanese VCCI

f) Australian C-Tick

g) Korean (MIC)

EMC Immunity:

CISPR 24:1997/EN 55024:1998 – Information Technology Equipment – Immunity Characteristics – Limits and Methods of Measurement.

ATI Radeon HD 2400XT (256MB DH) PCIe Graphics Card display resolutions and refresh rates

NOTE: Other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

Resolution	Maximum Refresh Rate (Hz)	
	Analog Connection	Digital Connection
640x480	85	60
800x600	85	60
1024x768	85	60
1280x720	85	60
1280x1024	85	60
1440x900	75	60
1600x1200	85	60
1680x1050	75	60
1920x1080	85	60-R
1920x1200	85	60-R
1920x1440	85	N/A
2048x1536	75	N/A
2560x1600	N/A	N/A

NOTE: 60-R denotes reduced blanking timings are used on single-link DVI connections and may be used with other digital connections

ATI Radeon HD 3470 (256MB SH) PCIe x16 Graphics Card
 Bus type ATI Radeon HD 3470 (256MB SH) PCIe x16 Graphics Card
 Maximum vertical refresh rate 85 Hz
 Display support Integrated 400 MHz RAMDAC

Display max resolution 2560x1600 digital, 2048 x 1536 analog

Board display options Supports two displays via the DisplayPort and DVI connectors

Board configuration	Specification	Description
Graphics Chip		RV620
Core clock		750 MHz
Memory clock		500 MHz
Frame buffer		256 MB DDR2, 64 bit wide

Languages supported 24 languages: English, Arabic, Chinese Simplified, Chinese Traditional, Czechoslovakian, Danish, Dutch, Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Thai, Turkish

Technical Specifications - Graphics

Operating systems support Windows Vista Business 64*, Windows Vista Business 32*, Windows Vista Home Basic 32*, Windows XP Professional or Windows XP Home 32*.

* Certain Windows Vista product features require advanced or additional hardware. Windows Vista Upgrade Advisor can help you determine which features of Windows Vista will run on your computer. To download the tool, visit:

<http://www.windowsvista.com/upgradeadvisor>. For Windows Vista system requirements, visit: <http://www.windowsvista.com/systemrequirements>.

Linux x86 and x86_64 distributions using XFree86 or X.Org**.

** Linux drivers are available from ATI's website and may be available in a Linux distribution. Refer to the Open Source and Linux from HP website:

<http://www.hp.com/wwwsolutions/linux/products/clients/> for support information.

Core power 22 W (max)

Dimensions (H x D) 2.71 in x 6.60 in (68.90 mm x 167.65 mm)

Weight 0.30 lb (134.3 g)

Option kit contents

- ATI Radeon HD 3470 (256MB SH) PCIe x16 Graphics Card with full height bracket attached
- DVI to VGA adapter
- Software CD with graphics drivers
- Low profile bracket to convert the card for using in a low profile chassis
- Warranty documentation

Compliance standards EMC Emissions:

- FCC Part 15, Subpart B - Unintentional Radiators, Class B Computing Devices for Home & Office Use
- CISPR22: 1997/EN 55022:1998 - Class B - Limits and methods of measurement of radio disturbance characteristics of Information Technology Equipment
- Canadian Standard ICES-003 is equivalent to CISPR22
- Taiwanese Standard BSMI
- Japanese VCCI
- Australian C-Tick
- Korean (MIC)

EMC Immunity:

CISPR 24:1997/EN 55024:1998 - Information Technology Equipment - Immunity Characteristics - Limits and Methods of Measurement.

ATI Radeon HD 3470 (256MB SH) PCIe x16 Graphics Card display resolutions and refresh rates

NOTE: Other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

Technical Specifications - Graphics

Resolution	Maximum Refresh Rate (Hz)	
	Analog Connection	Digital Connection
640x480	85	60
800x600	85	60
1024x768	85	60
1280x720	85	60
1280x1024	85	60
1440x900	75	60
1600x1200	85	60
1680x1050	75	60
1920x1080	85	60-R
1920x1200	85	60-R
1920x1440	85	N/A
2048x1536	75	N/A
2560x1600	N/A	60*

* Only supported when using a dual-link DVI or DisplayPort connection

NOTE: 60-R denotes reduced blanking timings are used on single-link DVI connections and may be used with other digital connections

ATI Radeon HD 4650 512MB
PCI Express (x16 lanes)
Maximum vertical refresh rate 85 Hz
PCIe x16 Graphics Card
Display support Integrated 400 MHz RAMDAC
Display max resolution 2560 x 1600 digital, 2048 x 1536 analog

ATI Radeon HD 4650 (512MB) PCIe x16 Graphics Card display resolutions and refresh rates

NOTE: Other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

Resolution	Maximum Refresh Rate (Hz)	
	Analog Connection	Digital Connection
640x480	85	60
800x600	85	60
1024x768	85	60
1280x720	85	60
1280x1024	85	60
1440x900	75	60
1600x1200	85	60
1680x1050	75	60
1920x1080	85	60-R*
1920x1200	85	60-R
1920x1440	85	N/A
2048x1536	75	N/A
2560x1600	N/A	60**

Technical Specifications - Graphics

* Max HDMI resolution is 1080p

** Only supported when using a dualLink DVI connection

NOTE: 60-R denotes reduced blanking timings are used on single-link DVI connections and may be used with other digital connections

Board display options Supports two displays through any combination of two of the three output ports.

Board configuration	Specification	Description
	Graphics Chip	RV730Pro
	Core clock	600MHz
	Memory clock	500 MHz
	Frame buffer	512 MB DDR2, 128 bit wide

Maximum power 55 W

Languages supported 24 languages: English, Arabic, Chinese Simplified, Chinese Traditional, Czechoslovakian, Danish, Dutch, Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Thai, Turkish

Operating systems support Windows Vista Home Basic 32*, FreeDOS

* Certain Windows Vista product features require advanced or additional hardware. Windows Vista Upgrade Advisor can help you determine which features of Windows Vista will run on your computer. To download the tool, visit:

<http://www.windowsvista.com/upgradeadvisor>. For Windows Vista system requirements, visit: <http://www.windowsvista.com/systemrequirements>.

Linux x86 and x86_64 distributions using XFree86 or X.Org**

** Linux drivers are available from ATI's website and may be available in a Linux distribution. Refer to the Open Source and Linux from HP website: <http://www.hp.com/wwwsolutions/linux/products/clients/> for support information.

Option kit contents

- ATI Radeon HD 4650 512MB PCIe x16 Graphics Card
- Software CD with graphics drivers
- Warranty documentation

Compliance standards EMC Emissions:

a) CISPR22: 1997/EN 55022:1998 - Class B - Limits and methods of measurement of radio disturbance characteristics of Information Technology Equipment

EMC Immunity:

CISPR 24:1997/EN 55024:1998 - Information Technology Equipment - Immunity Characteristics - Limits and Methods of Measurement.

Technical Specifications - Input Devices

HP PS/2 or USB Standard Keyboard	Physical characteristics	Keys	104, 105, 106, 107, 109 layout (depending upon country)
		Dimensions (L x W x H)	18.0 x 6.4 x 0.98 in (45.8 x 16.3 x 2.5 cm)
Electrical		Weight	2 lb (0.9 kg) minimum
		Operating voltage	+ 5VDC ± 5%
		Power consumption	50-mA maximum (with three LEDs ON)
		ESD	CE level 4, 15-kV air discharge
		EMI – RFI	Conforms to FCC rules for a Class B computing device
		Microsoft PC 99 – 2000	Functionally compliant
		Microsoft PC 99 – 2000	Functionally compliant
Mechanical		Languages	38 available
		Keycaps	Low-profile design
		Switch actuation	55-g nominal peak force with tactile feedback
		Switch life	20 million keystrokes (using Hasco modified tester)
		Switch type	Contamination-resistant switch membrane
		Key-leveling mechanisms	For all double-wide and greater-length keys
		Cable length	6 ft (1.8 m)
Environmental		Microsoft PC 99 – 2000	Mechanically compliant
		Acoustics	43-dBA maximum sound pressure level
		Operating temperature	50° to 122° F (10° to 50° C)
		Non-operating temperature	-22° to 140° F (-30° to 60° C)
		Operating humidity	10% to 90% (non-condensing at ambient)
		Non-operating humidity	20% to 80% (non-condensing at ambient)
		Operating shock	40 g, six surfaces
		Non-operating shock	80 g, six surfaces
		Operating vibration	2-g peak acceleration
		Non-operating vibration	4-g peak acceleration
		Drop (out of box)	26 in (66 cm) on carpet, six-drop sequence
Drop (in box)	42 in (107 cm) on concrete, 16-drop sequence		
Approvals	UL, CSA, FCC, CE Mark, TUV, TUV GS, VCCI, BSMI, C-Tick, MIC		
Ergonomic compliance	ANSI HFS 100, ISO 9241-4, and TUVGS		

Technical Specifications - Input Devices

HP USB 2-Button Laser Scroll Wheel	24
Maximum Rotation Speed	48 rats/sec
Switch Type	wheel
Switch Life	Button – 3,000,000 Wheel – 1,000,000 times Tilt switch – 500,000 times
Environmental	Operating Temperature 32° to 104° F (0° to 40° C) Non-operating Temperature -4° to 140° F (-20° to 60° C) Operating Humidity 10% to 90% (non-condensing at ambient) Non-operating Humidity 20% to 80% (non-condensing at ambient) Operating Shock 40 g, six surfaces Non-operating Shock 80 g, six surfaces Operating Vibration 2-g peak acceleration Non-operating Vibration 4-g peak acceleration
Electrical	Operating Voltage + 5VDC ± 5% Power Consumption MTBF > 150,000 hrs ESD IEC-61000-4-2 criteria B, Contact discharge: +/- 4kV, Air discharge: +/- 8kV EMI-RFI FCC Class B
Mechanical	PC98 PC 99 Compliant Resolution 800dpi Tracking Speed 25 cm/sec Acceleration 0.5mm Switch Actuation 0.6N (60gf) Switch Life Button – 3,000,000 Wheel – 1,000,000 times Tilt switch – 500,000 times Cable Length 1850mm PC98-99 PC99 compliant
Regulatory Approvals	UL60950-1, UL 94, UL 746 (A-E), UL 796 TUV/GS: EN 60950-1, EN 60825-1 FCC Class B, UL 1950, cUL, TUV GS, CE, C-tick, VCCI, BSMI, RRL

Technical Specifications - Input Devices

HP PS/2 Optical Scroll Mouse	Dimensions (H x L x W)	3.95 x 6.21 x 11.7 cm (1.56 x 2.44 x 4.61 in)
	Weight	4.44 oz (126 g)
	Environmental	Operating temperature -32° to 104°F (0° to 40° C) Non-operating temperature -4° to 140°F (-20° to 60° C)
		Operating humidity 10% to 90% (non condensing at ambient) Non-operating humidity 10% to 90% non condensing
		Operating shock 40 g, 6 surfaces Non-operating shock 80 g, 6 surfaces
		Operating vibration 2 g peak acceleration Non-operating vibration 4 g peak acceleration
		Drop (out of box) 80 cm height onto asphalt tile over concrete or equivalent, 5-drop in 5 direction except the cable face
	Electrical	Operating voltage 5 VDC ± 10% Power consumption 100mA System consumption PS/2 mini-din connector ESD CE level 4, 15 kV air discharge EMI-RFI Conforms to FCC rules for a Class B computing device
	Mechanical	Microsoft PC99 – 200 Functionally compliant Resolution 400 ± 20% DPI Tracking speed 10 in/s (25.4 cm/s) maximum Acceleration 100 in/s/s (2.54 m/s/s) Switch actuation 61 g nominal peak force Switch life 3,000,000 operations (using Hasco modified tester) Switch type Low force micro-switches Tracking mechanism life 155 mi (250 km) at average speed of 10 in/s Cable length 6 ft (1.8 m)
	Scroll wheel	Microsoft PC99 – 200 Mechanically compliant Width 8 mm Diameter 1.01 in (25.6 mm) Maximum rotation speed 48 rats/sec Switch type Light force micro-switch Switch life 1 million operations Mechanical life Minimum 200,000 revolutions
	Regulatory approvals	Compliant UL, CSA, FCC, CE Mark, TUV, TUV GS, VCCI, BSMI, C-Tick, MIC

Technical Specifications - Input Devices

HP USB Optical Scroll Mouse	Dimensions (H x L x W)	1.5 x 4.5 x 2.5 in (3.8 x 11.6 x 6.3 cm)
	Weight	0.27 lb (0.12 kg)
	Cable length	72.8 in (185 cm)

Technical Specifications - Hard Drives

Serial ATA Hard Drives 80 GB (7200 rpm)

Capacity	80,026,361,856 bytes	
Height	1 in (2.54 cm)	
Width	Media diameter: 3.5 in (8.9 cm) Physical size: 4 in (10.2 cm)	
Interface	Serial ATA (3.0 Gb/s)	
Synchronous Transfer Rate (Maximum)	3.0 Gb/s	
Buffer	8 MB	
Seek Time (typical reads, Single Track includes controller overhead, including settling)	Single Track	2.0 ms
	Average	11 ms
	Full-Stroke	21 ms
Rotational Speed	7,200 rpm	
Logical Blocks	156,301,488	
Operating Temperature	32° to 140° F (0° to 60° C)	

160 GB

Capacity	160,041,885,696 bytes	
Height	1 in (2.54 cm)	
Width	Media diameter: 3.5 in (8.89 cm) Physical size: 4 in (10.2 cm)	
Interface	Serial ATA (3.0 Gb/s)	
Synchronous Transfer Rate (Maximum)	3.0 Gb/s	
Buffer	8 MB	
Seek Time (typical reads, Single Track includes controller overhead, including settling)	Single Track	2.0 ms
	Average	11 ms
	Full-Stroke	21 ms
Rotational Speed	7,200 rpm	
Logical Blocks	312,581,808	
Operating Temperature	32° to 140° F (0° to 60° C)	

250 GB

Capacity	250,059,350,016 bytes	
Height	1 in (2.54 cm)	
Width	Media diameter: 3.5 in (8.89 cm) Physical size: 4 in (10.2 cm)	
Interface	Serial ATA (3.0 Gb/s)	
Synchronous Transfer Rate (Maximum)	3.0 Gb/s	
Buffer	8 MB	

Technical Specifications - Hard Drives

	Seek Time (typical reads, Single Track includes controller overhead, including settling)	Average	2.0 ms 11 ms 21 ms
	Rotational Speed	7,200 rpm	
	Logical Blocks	488,397,168	
	Operating Temperature	41° to 131° F (5° to 55° C)	
320 GB	Capacity	320,072,933,376 bytes	
	Height	1 in (2.54 cm)	
	Width	Media diameter: 3.5 in (8.9 cm) Physical size: 4 in (10.2 cm)	
	Interface	Serial ATA (3.0 Gb/s)	
	Synchronous Transfer Rate (Maximum)	Up to 3 Gb/s	
	Buffer	8 MB	
	Seek Time (typical reads, Single Track includes controller overhead, including settling)	Average	2.0 ms 11 ms 21 ms
	Rotational Speed	7,200 rpm	
	Logical Blocks	625,142,448	
	Operating Temperature	41° to 131° F (5° to 55° C)	
500 GB	Capacity	500,107,862,016 bytes	
	Height	1 in (2.54 cm)	
	Width	Media diameter: 3.5 in (8.89 cm) Physical size: 4 in (10.2 cm)	
	Interface	Serial ATA (3.0 Gb/s)	
	Synchronous Transfer Rate (Maximum)	3.0 Gb/s	
	Buffer	8 MB	
	Seek Time (typical reads, Single Track includes controller overhead, including settling)	Average	2.0 ms 11 ms 21 ms
	Rotational Speed	7,200 rpm	
	Logical Blocks	976,773,168	
	Operating Temperature	41° to 131° F (5° to 55° C)	

Technical Specifications - Optical Storage

SATA DVD-ROM Drive	Height	5.25-inch, half-height, tray-load		
	Orientation	Either horizontal or vertical		
	Interface type	SATA/ATAPI		
	Disc capacity	Single layer: Up to 4.7 GB (6 times capacity of CD-ROM) Double layer: Up to 8.5 GB (12 times capacity of CD-ROM)		
	Dimensions (W x H x D)	5.9 x 1.7 x 8.0 in (15.0 x 4.4 x 20.3 cm)		
	Weight (max)	2.6 lb (1.2 kg)		
	Read speeds	DVD+R/-R/+RW/ -RW/+R DL /-R DL	Up to 8X	
		DVD-ROM	Up to 16X	
		DVD-RAM	Up to 4X	
		CD-ROM, CD-R	Up to 48X	
CD-RW		Up to 32X		
Removable Storage - Media Compatibility - DVD-ROM	Media	Read	Write	
	CD-ROM	Yes	No	
	CD-R	Yes	No	
	CD-RW	Yes	No	
	DVD-ROM	Yes	No	
	DVD-ROM DL	Yes	No	
	DVD-RAM	Yes	No	
	DVD+R	Yes	No	
	DVD+R DL	Yes	No	
	DVD+RW	Yes	No	
	DVD-R	Yes	No	
	DVD-RW	Yes	No	
	DVD-R DL	Yes	No	
Access times (typical reads, including setting)	Random	DVD: < 140 ms (typical), CD: < 125 ms (typical)		
	Full Stroke	DVD: < 250 ms (seek), CD: < 210 ms (seek)		
	Cache Buffer	2 MB (minimum)		
	Data Transfer Modes	ATA PIO mode 4 (16.7 MB/s); ATA Multi-word DMA mode 2 (16.7 MB/s); ATA UltraDMA Mode 3 (44.4 MB/s -default)		
Power	Source	SATA DC power receptacle		
	DC Power Requirement	5 VDC ± 5%-100 mV ripple p-p 12 VDC ± 5%-200 mV ripple p-p		
	DC Current	5 VDC - <1000 mA typical, < 1600 mA maximum 12 VDC - < 600 mA typical, < 1400 mA maximum		

Technical Specifications - Optical Storage

Environmental (all conditions non-condensing)	Temperature	41° to 122° F (5° to 50° C)
	Relative Humidity	10% to 90%
	Maximum Wet Bulb Temperature	86° F (30° C)

SATA CD-RW/DVD-ROM Combo Drive	Height	5.25-inch, half-height, tray-load
	Orientation	Either horizontal or vertical
	Interface type	SATA/ATAPI
	Disc capacity	Single layer: Up to 4.7 GB (6 times capacity of CD-ROM) Double layer: Up to 8.5 GB (12 times capacity of CD-ROM)
	Dimensions (W x H x D)	5.9 x 1.7 x 8.0 in (15.0 x 4.4 x 20.3 cm)
	Weight (max)	2.6 lb (1.2 kg)
	Write speeds	CD-R Up to 48X CD-RW Up to 32X
	Read speeds	DVD+R/-R/+RW/ -RW/+R DL /-R DL Up to 8X DVD-ROM Up to 16X CD-ROM, CD-R Up to 48X CD-RW Up to 32X
	Access times (typical reads, including setting)	Random DVD: < 140 ms (typical), CD: < 125 ms (typical) Full Stroke DVD: < 250 ms (typical), CD: < 210 ms (typical)
	Power	Source SATA DC power receptacle DC Power Requirement 5 VDC ± 5%-100 mV ripple p-p 12 VDC ± 5%-200 mV ripple p-p DC Current 5 VDC - <1000 mA typical, < 1600 mA maximum 12 VDC - < 600 mA typical, < 1400 mA maximum
	Environmental (all conditions non-condensing)	Temperature 41° to 122° F (5° to 50° C) Relative Humidity 10% to 90% Maximum Wet Bulb Temperature 86° F (30° C)

Technical Specifications - Optical Storage

HP SATA SuperMulti LightScribe DVD Writer Drive	Height	5.25-inch, half-height, tray-load
	Orientation	Either horizontal or vertical
	Interface type	SATA/ATAPI
	Disc capacity	8.5 GB DL or 4.7 GB standard
	Dimensions (W x H x D)	5.9 x 1.7 x 8.0 in (15.0 x 4.4 x 20.3 cm)
	Weight (max)	2.6 lb (1.2 kg)
	Write speeds	DVD-RAM Up to 12X DVD+R Up to 16X DVD+RW Up to 8X DVD+R DL Up to 8X DVD-R DL Up to 8X DVD-R Up to 16X DVD-RW Up to 6X CD-R Up to 48X CD-RW Up to 32X
	Read speeds	DVD-RAM Up to 12X DVD+R/-R/+RW/-RW/+R DL /-R DL Up to 8X DVD-ROM DL Up to 8X DVD-ROM, DVD+R, DVD-R Up to 16X CD-ROM, CD-R Up to 48X CD-RW Up to 32X
	Access times (typical reads, including setting)	Random DVD: < 140 ms (typical), CD: < 125 ms (typical) Full Stroke DVD: < 250 ms (seek), CD: < 210 ms (seek)
	Power	Source SATA DC power receptacle DC Power Requirement 5 VDC ± 5%-100 mV ripple p-p 12 VDC ± 5%-200 mV ripple p-p DC Current 5 VDC - <1000 mA typical, < 1600 mA maximum 12 VDC - < 600 mA typical, < 1400 mA maximum
	Environmental (all conditions non-condensing)	Temperature 41° to 122° F (5° to 50° C) Relative Humidity 10% to 90% Maximum Wet Bulb Temperature 86° F (30° C)

Technical Specifications - Removable Storage

1.44-MB Diskette Drive Size	3.5 in (8.89 cm)
LED Indicators (front panel)	Green
Read/Write Capacity per Diskette (high/low)	1.44 MB/720 KB
Drive Height	One-third
Drive Rotation	300 rpm
Transfer Rate (high/low)	500/250 KB/s
Bytes/Sector	512
Sectors/Track (high/low)	18/9
Tracks/Side (high/low)	80/80
Access Times	Track-to-Track (high/low) 3/6 ms
	Average (high/low) 94/173 ms
	Settling Time 15 ms
	Latency Average 100 ms
Cylinders (high/low)	80/80
Read/Write Heads	Two

HP 16-in-1 Media Card USB interface Reader	USB 2.0 High-speed device via PCI card or pass-through via internal USB port of system board				
Advance protocol support	<ul style="list-style-type: none"> • Supports hardware ECC (Error Correction Code) function • Supports hardware CRC (Cyclic Redundancy Check) function • Supports MS 4-bit parallel transfer mode • Supports MS-PRO 4-bit parallel transfer mode • Supports SD 4-bit parallel transfer mode • Supports high-speed 50 MHz SD 4-bit card (version 1.1) • Support high-speed 52 MHz MMC 8-bit card (version 4.x) 				
Supported media types	<ul style="list-style-type: none"> • Supports CompactFlash Card Type I (CF I), CompactFlash Card Type II (CF II), MicroDrive (MD) • Supports 3.3V SmartMedia Card (SM), SmartMedia ROM (SM ROM), xD-Picture Card (xD) • Supports Secure Digital Card (SD), Secure Digital ROM Card (SD ROM), miniSD, MultiMediaCard (MMC), Secure MultiMediaCard (Secure MMC), ROM Type MultiMediaCard (MMC ROM), Reduced Size MultiMediaCard (RS MMC), MultiMediaCard 4.0 (MMC Plus), Reduced Size MultiMediaCard 4.0 (MMC Mobile) • Support Memory Stick (MS), Memory Stick ROM (MS ROM), MagicGate Memory Stick (MG), Memory Stick Select, Memory Stick Duo (MS Duo), Memory Stick PRO (MS-PRO), Memory Stick PRO Duo (MS PRO Duo) 				
Mechanical	<table> <tr> <td>Length (3.5")</td> <td>124.7 cm</td> </tr> <tr> <td>Width (3.5")</td> <td>101.6 cm</td> </tr> </table>	Length (3.5")	124.7 cm	Width (3.5")	101.6 cm
Length (3.5")	124.7 cm				
Width (3.5")	101.6 cm				

Technical Specifications - Removable Storage

	Height (3.5")	25.4 cm
	Length (5.25")	171.6 cm
	Width (5.25")	148.9 cm
	Height (5.25")	42.7 cm
Environmental	Operational	Test Parameters/Conditions – Power applied, unit environmental extremes operating on system $\pm 5\%$ nominal supply voltage. 10°C 10% R.H. \geq 24 hours 10°C 90% R.H. \geq 24 hours 20°C 90% R.H. \geq 24 hours 30°C 90% R.H. \geq 24 hours 40°C 90% R.H. \geq 24 hours 50°C 90% R.H. \geq 24 hours 50°C 10% R.H. \geq 24 hours
	Storage environmental extremes	Test Parameters/Conditions 60°C @ 80% R.H. for 96 hours -30°C @ 20% R.H. for 48 hours No power applied Delta °C < 1.0°C/min Delta % R.H. < 1.5% R.H./min
Approvals	USB-IF, WHQL, Compliant with USB Mass Storage Class Bulk only Transport Specification Rev. 1.0, Compliant Intel Front Panel I/O Connectivity Design Guide V. 1.2 FCC, CE, BSMI, C-Tick, VCCI, MIC, cUL, TUV-T	

HP 22-in-1 Media Card USB Interface Reader (with 1394 port)

USB 2.0 High-speed interface

NOTE: Requires the USB cable to be connected to the internal USB 2.0 port or a USB 2.0 PCI card.

1394 Interface	Two IEEE-1394a external ports; 1 IEEE-1394a internal port (connects to the pass through cable on the media card reader)
Advance protocol support	<ul style="list-style-type: none"> • Supports hardware ECC (Error Correction Code) function • Supports hardware CRC (Cyclic Redundancy Check) function • Supports MS 4-bit parallel transfer mode • Supports MS-PRO 4-bit parallel transfer mode • Supports MS PRO-HG Duo 4-bit parallel transfer mode • Supports SD 4-bit parallel transfer mode • Supports high-speed 50Mhz SD 4-bit card (version 2.0) • Supports high-speed 52Mhz MMC 8-bit card (version 4.2) • Supports CF v4.0 with PIO mode 6 and Ultra DMA mode
Supported media type	<ul style="list-style-type: none"> • CompactFlash Type I • CompactFlash Type II • Microdrive • MultiMediaCard (MMC) • Reduced Size MultiMediaCard (RS MMC) • MultiMediaCard 4.2 (MMC Plus, including MMC Plus HC)

Technical Specifications - Removable Storage

- Reduced Size MultiMediaCard 4.2 (MMC Mobile, including MMC Mobile HC)
- Secure Digital Card (SD)
- Secure Digital High Capacity (SDHC)
- miniSD
- miniSD High Capacity
- Micro SD (T-Flash)
- Micro SD HC
- Memory Stick
- Memory Stick Select
- Memory Stick Duo (MS Duo)
- Memory Stick PRO (MS PRO)
- Memory Stick PRO Duo (MS PRO Duo)
- Memory Stick PRO-HG Duo
- MagicGate Memory Stick (MG)
- MagicGate Memory Stick Duo
- xD-Picture Card
- Memory Stick Micro (M2)
- MMC Micro

Supported media type
with card adapter

Environmental

Operational

Test Parameters/Conditions - Power applied, unit

Environmental Extremesoperating on system $\pm 5\%$

nominal supply voltage.

10°C 10% R.H. \geq 24 hours

10°C 90% R.H. \geq 24 hours

20°C 90% R.H. \geq 24 hours

30°C 90% R.H. \geq 24 hours

40°C 90% R.H. \geq 24 hours

50°C 90% R.H. \geq 24 hours

50°C 10% R.H. \geq 24 hours

Storage Environmental
Extremes

Test Parameters/Conditions

140°F (60°C) @ 80% R.H. for 96 hours

-22°F (-30°C) @ 20% R.H. for 48 hours

No power applied

Delta °C < 1.0°C/min

Delta % R.H. < 1.5% R.H./min

Approvals

USB-IF, WHQL, Compliant with USB Mass Storage Class Bulk only Transport Specification Rev. 1.0, Compliant Intel Front Panel I/O Connectivity Design Guide V. 1.3

FCC, CE, BSMI, C-Tick, VCCI, MIC, cUL, TUV-T

Technical Specifications - Environmental Data

Eco-Label Certifications & declarations

This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

Hewlett-Packard Corporate Environmental Information

For more information about HP's commitment to the environment:

Global Citizenship Report

<http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html>

Eco-label certifications

<http://www.hp.com/hpinfo/globalcitizenship/environment/productdesign/ecolabels.html>

ISO 14001 certificates:

<http://www.hp.com/hpinfo/globalcitizenship/environment/operations/envmanagement.html>

© Copyright 2009 Hewlett-Packard Development Company, L.P.

All rights reserved.

The information contained herein is subject to change without notice.

Intel and Pentium are U.S. registered trademarks of Intel Corporation. Microsoft and Windows are U.S. registered trademarks of Microsoft Corporation. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Free Manuals Download Website

<http://myh66.com>

<http://usermanuals.us>

<http://www.somanuals.com>

<http://www.4manuals.cc>

<http://www.manual-lib.com>

<http://www.404manual.com>

<http://www.luxmanual.com>

<http://aubethermostatmanual.com>

Golf course search by state

<http://golfingnear.com>

Email search by domain

<http://emailbydomain.com>

Auto manuals search

<http://auto.somanuals.com>

TV manuals search

<http://tv.somanuals.com>